


MISSION OPERATIONS AND DATA SYSTEMS DIRECTORATE

**Landsat 7 System
Calibration Parameter File
Definition**

Revision 1 |

January 1998~~September 1997~~ |



National Aeronautics and
Space Administration

Goddard Space Flight Center
Greenbelt, Maryland

Landsat 7 System Calibration Parameter File Definition

Revision 1

January September 19987

Prepared by:

Concurred by:

Richard Irish
Senior Systems Engineer
Landsat 7 Project Science Office
Science Systems and Applications, Inc.

Dan Devito
Systems Engineering Manager
ESDIS Project, Code 505
Goddard Space Flight Center

Brian Markam
Lead Calibration Scientist
Landsat 7 Processing System
Code 923
Goddard Space Flight Center

Joy Henegar
Project Manager
LPGS/IAS, Code 514
Goddard Space Flight Center

Darrel Williams Date
Project Scientist, Landsat 7 Project
Code 923.0
Goddard Space Flight Center

Goddard Space Flight Center Greenbelt, Maryland

Table of Contents

Section 1. Introduction

1.1	Document Organization	1–1
1.2	Applicable Documents.....	1–1
1.3	File Structure.....	1–1
1.4	Calibration Parameter File Updates.....	1–2
1.4.1	Time Stamps.....	1–2
1.4.2	File-Naming Conventions	1–2
1.5	File Content Description.....	1–4

Section 2. CPF Parameters

Section 3. CPF ODL

3.1	Introduction.....	3–1
3.2	ODL Construct.....	3–1

Acronyms and Abbreviations

Section 1. Introduction

This document describes the contents of the calibration parameter file (CPF) generated by the Image Assessment System (IAS), an element of the Landsat 7 Ground Segment. The IAS is responsible for offline assessment of image quality to ensure compliance with the radiometric and geometric requirements of the spacecraft and the Enhanced Thematic Mapper Plus (ETM+) sensor throughout the mission's life.

In addition to its assessment functions, the IAS is responsible for the radiometric and geometric calibration of the Landsat 7 satellite and ETM+. The IAS periodically performs radiometric and geometric calibration and updates the CPF. This file is stamped with applicability dates and sent to the Earth Resources Observation System (EROS) Data Center (EDC) Distributed Active Archive Center (DAAC) for storage and eventual bundling with outbound Level 0R products. The CPF also is sent to international ground stations via the Landsat 7 Mission Operations Center. The CPF supplies the radiometric and geometric correction parameters required during Level 1 processing to create superior products of uniform consistency across the Landsat 7 system.

1.1 Document Organization

Section 1 provides an introduction to the CPF. It describes the CPF structure and language; the CPF updates, time stamps, and file-naming conventions; and the attributes used to characterize the calibration parameters. Section 2 contains a table that lists and describes the actual CPF parameters. Section 3 presents the syntax of the CPF Object Description Language (ODL) and a CPF construct that illustrates the actual appearance of the file. Following these sections is a list of the acronyms and abbreviations used in this document.

1.2 Applicable Document

A useful ODL document is the Jet Propulsion Laboratory (JPL), California Institute of Technology's *Planetary Data System Standards Reference, Version 3.2*, Chapter 12, "Object Description Language Specification and Usage," July 24, 1995.

This document can be accessed online at URL <http://pds.jpl.nasa.gov/stdref/chap12.htm>.

1.3 File Structure

All parameters are stored as American Standard Code for Information Interchange (ASCII) text using the ODL syntax developed by JPL. ODL is a tagged keyword language developed to provide a human-readable data structure to encode data for simplified interchange. The ODL interpreter developed by JPL may, in certain cases, provide for the handling of lexical elements (for example, building blocks) that are included in the Consultative Committee for Space Data Systems (CCSDS) specification of the Parameter Value Language (PVL). PVL is a superset of ODL. The IAS CPF is a pure ODL implementation without any PVL extensions.

The body of the file is composed of two statement types:

1. Attribute assignment statement used to assign values to parameters
2. Group statements used to aid in file organization and enhance parsing granularity of parameter sets

ODL details can be found in the *Planetary Data System Standards Reference*.

1.4 Calibration Parameter File Updates

The IAS will update and distribute the CPF at least every 90 days. Updates will likely be more frequent during early orbit checkout and also will occur between the regular 90-day cycles, as necessary. Irregular updates, however, will not affect the 90-day schedule. The timed release of a new CPF must be maintained because of the Universal Time Code corrected (UT1) time corrections and pole wander predictions included in the file. These parameters span a 180-day interval time centered on the effective start date of the new IAS CPF.

1.4.1 Time Stamps

The CPF is time-stamped with an effective date range. The first two parameters in the file—Effective_Date_Begin and Effective_Date_End—designate the range and are in MM/DD/YYYY format. The Effective_Date_End for the most recent parameter file is its Effective_Date_Begin plus 90 days. After this date, the file is without applicable UT1 time predictions. The Earth Observing System Data and Information System (EOSDIS) Core System (ECS) maintains a database of CPF names and their effective dates for associating product orders with the appropriate parameter files. The parameter file that accompanies an order has an effective date range that includes the acquisition date of the image ordered.

1.4.2 File Naming Conventions

Through the course of the mission, a serial collection of CPF calibration parameter files will be generated and sent to the EDC -DAAC for coupling to OR distribution products. The probability exists that a CPF calibration parameter file will be replaced due to improved calibration parameters for a given period or perhaps file error. The need for unique file sequence numbers becomes necessary as file contents change. The following file-naming procedure is used by the IAS to name the CPF calibration parameter file.

L7CPFyyyymmdd_yyyymmdd.nn

where

L7 _____ = constant for Landsat 7

CPF = 3-letter calibration parameter file (CPF) designator
yyy = 4-digit effectivity starting year
mm = 2-letter effectivity starting month
dd = 2-letter effectivity starting day
— = effectivity starting/ending date separator
yyy = 4-digit effectivity ending year
mm = 2-letter effectivity ending month
dd = 2-letter effectivity ending day
nn = sequence number for this file

As an example, suppose four calibration files were created by the IAS on 90-day intervals and sent to the EDC - DAAC during the first year of the mission. Further suppose that the first file was updated twice and the second and third files were updated once. The assigned file names would be:

File 1 L7CPF19980601_19980829.00
L7CPF19980601_19980829.01
L7CPF19980601_19980829.02

File 2 L7CPF19980830_19981127.01
L7CPF19980830_19981127.02

File 3 L7CPF19981128_19990225.01
L7CPF19981128_19990225.02

File 4 L7CPF19990226_19990526.01

It is worth noting the **00** sequence number assigned to the original CPF. This reserve sequence number uniquely identifies the pre-launch CPF. Sequence numbers for subsequent time periods all begin with 01. New versions or updates are incremented by one.

This example assumes the effectivity dates do not change. The effectivity date range for a file can change, however, if a specific problem (e.g., detector outage) is discovered somewhere within the nominal 90-day effectivity range. Assuming this scenario, two CPFs with new names and effectivity date ranges are spawned for the time period under consideration. The effective date end for a new pre-problem CPF would change to the day before the problem occurred. The effective date begin remains unchanged. A post-problem CPFcalibration parameter file with a new file name would be created with an effective date begin corresponding to the imaging date the problem occurred. The effective date end assigned would be the original effective date end for the time period under consideration. New versions of all other CPFcalibration parameter files affected by the erroneous parameter also would also be created.

Using this example, presented above suppose a dead detector is discovered to have occurred on January 31, 1999. Two new CPFs are created that supersede the time period represented by file number three, version 2, and a new version of file number four is created. The new file names and sequence numbers become:

File 3 L7CPF19981128_19990225.01
L7CPF19981128_19990225.02
L7CPF19981128_19990131.01
L7CPF19990201_19990225.01

File 4 L7CPF19990226_19990526.01

L7CPF19990226_19990526.02

Through the course of the mission, a serial collection of CPFs will be generated and sent to the EDC DAAC for coupling to Level 0 reformatted (0R) distribution products. The probability exists that a CPF will be replaced due to improved calibration parameters for a given period or perhaps file error. The need for file version numbers becomes necessary as file contents change. Also, the following file naming procedure, developed for the Flight Dynamics Facility, will be used by the IAS to name the CPF:

L7YYYYDDDIASCAL.VNN

where

L7 = Constant for Landsat 7

YYYY = 4 digit year

DDD = 3 digit day of the year of file creation

~~IAS~~ = Acronym for the Image Assessment System
~~CAL~~ = 3-letter file type for calibration
~~V~~ = Letter designating the version number
~~NN~~ = Sequence number for this file

The following example illustrates the convention for naming CPFs:

Four calibration files were created by the IAS on 90-day intervals and sent to the EDC DAAC during the first year of the mission. If the first file were updated twice and the second and third files were updated once, the assigned file names would be as follows:

~~File 1~~ L71998001IASCAL.A01
 L71998001IASCAL.B01
 L71998001IASCAL.C01

~~File 2~~ L71998091IASCAL.A02
 L71998091IASCAL.B02

~~File 3~~ L71998181IASCAL.A03
 L71998181IASCAL.B03

~~File 4~~ L71998271IASCAL.A04

This example assumes that effective dates do not change. The effective date range for a file can change, however, if a specific problem (for example, a detector outage) is discovered somewhere within the nominal 90-day effective range. Assuming this scenario, an additional CPF is required for the time period under consideration. The Effective_Date_End for the pre-problem CPF would change to the imaging date the problem occurred, and a new version of the file would be created. A post-problem CPF with a new file name would be created with an Effective_Date_Begin corresponding to the imaging date the problem occurred. The Effective_Date_End assigned would be the original Effective_Date_End for the time period under consideration. New versions of all other CPFs affected by the erroneous parameter also would be created.

1.5 File Content Description

Each parameter entry is characterized by five attributes:

1. Parameter group—Identifies a related set of parameters.
2. Parameter name—Uniquely identifies and describes the content of each parameter.
3. Value type—Describes the parameter as either static or dynamic. A static value remains unchanged over the mission's life. A dynamic value will change or has the potential to change over the life of the mission. Significant changes to dynamic values trigger a CPF update.

4. Data type—Referred to using Hierarchical Data Format (HDF) number type nomenclature, type#, where type is either char (character), int (integer), or float (floating point), and # is a decimal count of the number of bits used to represent the data type. The type mnemonics int and char may be preceded by the letter u, indicating an unsigned value. For example, the data type uint32 refers to an unsigned 32-bit integer value. Data types relevant to the CPF are as follows:

Data Type	HDF Nomenclature
8-bit character	char8
8-bit unsigned integer	uint8
16-bit signed integer	int16
32-bit signed integer	int32
32-bit floating point number	float32
64-bit floating point number	float64

5. Description—Short description of the parameter, its format, and its nominal or expected value(s).

Section 2. CPF Parameters

The following table lists the CPF parameters.

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
File Attributes	Effective_Date_Begin	Dynamic	char8	Effective start date for this file Valid format: YYYY-MM-DD, where YYYY = 1998–2050, MM = 01–12, and DD = 01–31	Yes	Yes	IAS
File Attributes	Effective_Date_End	Dynamic	char8	Effective end date for this file Valid format: YYYY-MM-DD, where YYYY = 1998–2050, MM = 01–12, and DD = 01–31	Yes	Yes	IAS
File Attributes	CPF_File_Name	Dynamic	char8	Original file name assigned by IAS Valid format: L7CPFyyymdd_ _yyymdd.nn where yyymdd = effective start date and effective end date, respectfully, and -nn = incrementing version for within a quarter (01–99)	Yes	Yes	IAS
Earth Constants	Ellipsoid_Name	Static	Char8	Name of ellipsoid used to represent semi-major and semi-minor axes of Earth Valid format: SSSSS, where SSSSS = WGS84	Yes	Yes	EDC
Earth Constants	Semi_Major_Axis	Static	float64	Earth semi-major axis; distance in meters from center of Earth to equator Valid format: NNNNNNN.NNN, where NNNNNNN.NNN = 6378137.000	Yes	Yes	EDC
Earth Constants	Semi_Minor_Axis	Static	float64	Earth semi-minor axis; distance in meters from center of Earth to poles Valid format: NNNNNNN.NNN, where NNNNNNN.NNN = 6356752.314	Yes	Yes	EDC
Earth Constants	Ellipticity	Static	float64	Ratio describing polar flattening or Earth's deviation from an exact sphere (WG584 standard) Valid format: N.NNNNNNNNNN, where N.NNNNNNNNNN = (1/298.257223563)	Yes	Yes	EDC
Earth Constants	Eccentricity	Static	float64	Number describing polar flattening or Earth's deviation from an exact sphere (WG584 standard) Valid format: N.NNNNNNNNNN, where N.NNNNNNNNNN = (1/298.257223563)0.06694380	Yes	Yes	EDC
Earth Constants	Earth_Spin_Rate	Static	float64	Earth's diurnal spin rate in radians per second Valid format: NN.NNNNNNNNNNNNNN, where NN.NNNNNNNNNNNNNN = 72.92115855E-06	Yes	Yes	EDC

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Earth Constants	Gravity_Constant	Static	float64	Universal gravitational constant times mass of Earth Valid format: N.NNNNNNENN, where N.NNNNNNENN = 3.986012E14	Yes	Yes	EDC
Earth Constants	J2_Earth_Model_Term	Static	float64	Term that describes Earth's spherical harmonic Valid format: NNNN.NNESNN, where NNNN.NNESNN = 1082.64E-06	Yes	Yes	EDC
Orbit_Parameters	WRS_Cycle_Days	Static	uint8	Time period, in days, required for satellite to view Earth once Valid format: NN, where NN = 16	No	Yes	IAS
Orbit_Parameters	WRS_Cycle_Orbits	Static	uint8	Number of orbits or paths in a complete World Reference System (WRS) cycle Valid format: NNN, where NNN = 233	No	Yes	IAS
Orbit_Parameters	Scenes_Per_Orbit	Static	uint8	Number of scenes or row locations per orbit Valid format: NNN, where NNN = 248	No	Yes	IAS
Orbit_Parameters	Orbital_Period	Static	float64	Time required, in seconds, to complete one orbit Valid format: NNNN.NNNN, where NNNN.NNNN = 5933.0472	No	Yes	LMC System Spec
Orbit_Parameters	Angular_Momentum	Static	float64	Angular momentum in orbit, specified in meters squared per second Valid format: NN.NNNNNNNEN, where NN.NNNNNNNEN = 53.104278E7	No	Yes	LMC System Spec
Orbit_Parameters	Orbit_Radius	Static	float64	Nominal distance in km from Earth's center to spacecraft track Valid format: NNNN.NNN, where NNNN.NNN = 7083.437	No	Yes	LMC System Spec
Orbit_Parameters	Orbit_Semimajor_Axis	Static	float64	Nominal semi-major axis in km of satellite's orbit Valid format: NNNN.NNNN, where NNNN.NNNN = 7077.9000	No	Yes	LMC System Spec
Orbit_Parameters	Orbit_Seminor_Axis	Static	float64	Nominal semi-minor axis in km of satellite's orbit Valid format: NNNN.NNNN, where NNNN.NNNN = 7069.5800	No	Yes	LMC System Spec
Orbit_Parameters	Orbit_Eccentricity	Static	float64	Nominal eccentricity of satellite's orbit Valid format: N.NNNNN, where N.NNNNN = 0.00118	No	Yes	LMC System Spec
Orbit_Parameters	Inclination_Angle	Static	float64	Angle in degrees formed by Earth equatorial and satellite plane Valid format: NN.NNNN, where NN.NNNN = 98.2098	No	Yes	LMC System Spec
Orbit_Parameters	Argument_Of_Perigee	Static	float32	Nominal angle in degrees of point nearest Earth in orbit as measured from ascending node in direction of satellite motion Valid format: NN.N, where NN.N = 90.0	No	Yes	LMC System Spec
Orbit_Parameters	Descending_Node_Row	Static	uint8	Row corresponding to Earth's equator Valid format: NN, where NN = 60	No	Yes	IAS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Orbit_Parameters	Long_Path1_Row60	Static	float32	Longitude in degrees west of point at which path 1 crossed equator (row 60) Valid format: SNN.N, where SNN.N = - 64.6	No	Yes	LMC System Spec
Orbit_Parameters	Descending_Node_Time_Min	Static	char8	Minimum local solar time of descending node in AM hours and minutes Valid format: HH:MM, where HH:MM = 09:45	No	Yes	IAS
Orbit_Parameters	Descending_Node_Time_Max	Static	char8	Maximum local solar time of descending node in AM hours and minutes Valid format: HH:MM, where HH:MM = 10:00	No	Yes	IAS
Orbit_Parameters	Nodal_Regression_Rate	Static	float64	Rate in degrees per day that orbital plane rotates with respect to Earth Valid format: N.NNNNNNNN, where N.NNNNNNNN = 0.9856473	No	Yes	LMC System Spec
Scanner_Parameters	Lines_Per_Scan_30	Static	uint8	Detectors per scan for bands 1–5 and 7 Valid format: NN, where NN = 16	Yes	Yes	IAS
Scanner_Parameters	Lines_Per_Scan_60	Static	uint8	Detectors per scan for band 6 Valid format: N, where N = 8	Yes	Yes	IAS
Scanner_Parameters	Lines_Per_Scan_15	Static	uint8	Detectors per scan for band 8 Valid format: NN, where NN = 32	Yes	Yes	IAS
Scanner_Parameters	Scans_Per_Scene	Static	int16	Scans per nominal WRS scene Valid format: NNN, where NN = 374	Yes	Yes	IAS
Scanner_Parameters	Swath_Angle	Dynamic	float32	Object space angle in radians of scan mirror travel during active scan time Valid format: N.NNNNNN, where N.NNNNNN = 0.26868 (TBS after measurement of as-built ETM+)	No	Yes	SBRS
Scanner_Parameters	Scan_Rate	Static	float32	Angular scan velocity in radians per second of scan mirror Valid format: N.NNNNNN, where N.NNNNNN = 2.21095 (TBS)	No	Yes	SBRS
Scanner_Parameters	Dwell_Time_30	Static	float64	Detector sample time in microseconds for bands 1–5 and 7 Valid format: N.NNNNNNNN, where N.NNNNNNNN = 9.6109603	No	Yes	SBRS
Scanner_Parameters	Dwell_Time_60	Static	float64	Detector sample time in microseconds for band 6 Valid format: N.NNNNNNNN, where N.NNN = 4.8060000	No	Yes	SBRS
Scanner_Parameters	Dwell_Time_15	Static	float64	Detector sample time in microseconds for band 8 Valid format: N.NNNNNNNN, where N.NNN = 19.2220000	No	Yes	SBRS
Scanner_Parameters	IC_Line_Length_30	Static	int16	Nominal number of detector samples for internal calibrator for bands 1–5 and 7 Valid format: NNNN, where NNNN = 1100	No	Yes	SBRS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Scanner_Parameters	IC_Line_Length_60	Static	int16	Nominal number of detector samples for internal calibrator for band 6 Valid format: NNNN, where NNNN = 550	No	Yes	SBRS
Scanner_Parameters	IC_Line_Length_15	Static	int16	Nominal number of detector samples for internal calibrator for band 8 Valid format: NNNNN, where NNNNN = 2200	No	Yes	SBRS
Scanner_Parameters	Scan_Line_Length_30	Static	int16	Nominal number of detector samples during active scan time for bands 1–5 and 7 Valid format: NNNN, where NNNN = 6330	No	Yes	SBRS
Scanner_Parameters	Scan_Line_Length_60	Static	int16	Nominal number of detector samples during active scan time for band 6 Valid format: NNNN, where NNNN = 3165	No	Yes	SBRS
Scanner_Parameters	Scan_Line_Length_15	Static	int16	Nominal number of detector samples during active scan time for band 8 Valid format: NNNNN, where NNNNN = 12660	No	Yes	SBRS
Scanner_Parameters	Filter_Frequency_30	Static	float32	Bandwidth in kHz of detector presample filter (defined by 3-dB roll-off point) for bands 1–5 and 7 Valid format: NN.NN, where NN.NN = 52.02	No	Yes	SBRS
Scanner_Parameters	Filter_Frequency_60	Static	float32	Bandwidth in kHz of detector presample filter (defined by 3-dB roll-off point) for band 6 Valid format: NN.NN, where NN.NN = 26.01	No	Yes	SBRS
Scanner_Parameters	Filter_Frequency_15	Static	float32	Bandwidth in kHz of detector presample filter (defined by 3-dB roll-off point) for band 8 Valid format: NNN.NN, where NNN.NN = 115.00	No	Yes	SBRS
Scanner_Parameters	IFOV_B1234	Static	float32	Angle in :rad subtended by detector when scanning motion is stopped Valid format: NN.NNNN, where NN.NNNN = 42.5000 (TBS)	No	Yes	SBRS
Scanner_Parameters	IFOV_B57_along_scan	Static	float32	Angle in :rad subtended by detector when scanning motion is stopped Valid format: NN.N, where NN.N = 39.6 (TBS)	No	Yes	SBRS
Scanner_Parameters	IFOV_B57_across_scan	Static	float32	Angle in :rad subtended by detector when scanning motion is stopped Valid format: NN.N, where NN.N = 42.5 (TBS)	No	Yes	SBRS
Scanner_Parameters	IFOV_B6	Static	float32	Angle in :rad subtended by detector when scanning motion is stopped Valid format: NN.N, where NN.N = 85.0 (TBS)	No	Yes	SBRS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Scanner_Parameters	IFOV_B8_along_scan	Static	float32	Angle in :rad subtended by detector when scanning motion is stopped Valid format: NN.N, where NN.N = 18.5 (TBS)	No	Yes	SBRS
Scanner_Parameters	IFOV_B8_across_scan	Static	float32	Angle in :rad subtended by detector when scanning motion is stopped Valid format: NN.N, where NN.N = 21.3 (TBS)	No	Yes	SBRS
Scanner_Parameters	Scan_Period	Static	float64	Time in milliseconds of a complete scan cycle, including forward and reverse scans Valid format: NNN.NNNNNN, where NNN.NNNNNN = 142.925000	No	Yes	SBRS
Scanner_Parameters	Scan_Frequency	Static	float32	Number of scans in 1 second (Hz) Valid format: N.NNNN, where N.NNNN = 6.9967	No	Yes	SBRS
Scanner_Parameters	Active_Scan_Time	Static	float32	Time in μ s required for scan mirror to travel from its scan-line-start to end-of-line (EOL) Valid format: NNNNN.N, where NNNNN.N = 60743.0	No	Yes	SBRS
Scanner_Parameters	Turn_Around_Time	Static	float32	Time in milliseconds from EOL to next scan-line-start, during which scan mirror motion reverses direction Valid format: NN.NNN, where: NN.NNN = 10.719 (TBS)	No	Yes	SBRS
Spacecraft_Parameters	ADS_Interval	Static	float32	Time in milliseconds between ADS samples Valid format: N.N, where N.N = 2.0	No	Yes	SBRS
Spacecraft_Parameters	ADS_Roll_Offset	Static	float32	Amount of time in milliseconds from start of a payload correction data (PCD) cycle to roll axis measurement Valid format: N.NNN, where N.NNN = 0.375	No	Yes	SBRS
Spacecraft_Parameters	ADS_Yaw_Offset	Static	float32	Amount of time in milliseconds from start of a PCD cycle to yaw axis measurement Valid format: N.NNN, where N.NNN = 0.875	No	Yes	SBRS
Spacecraft_Parameters	ADS_Pitch_Offset	Static	float32	Amount of time in milliseconds from start of a PCD cycle to pitch axis measurement Valid format: N.NNN, where N.NNN = 1.375	No	Yes	SBRS
Spacecraft_Parameters	Data_Rate	Static	float32	ETM+ output bit rate in Mbps Valid format: NN.NNN, where NN.NNN = 74.903 (TBS)	No	Yes	SBRS
Mirror_Parameters GROUP: Angles_SME1_SAM	Forward_Along_SME1_SAM	Static	float64 array (6 values)	Fifth-order polynomial coefficients that describe departure from linearity of forward along scan mirror motion; scan angle monitor (SAM) with scan mirror electronics (SME) number 1 Valid format: for each term: SN.NNNNESN, where S = '+' or '-', N = 0 to 9, and E = 'E'	No	Yes	SBRS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Mirror_Parameters GROUP: Angles_SME1_SAM	Forward_Cross_SME1_SAM	Static	float64 array (6 values)	Fifth-order polynomial coefficients that describe deviation of forward cross scan mirror motion from linear; SAM mode Valid format: for each term: SN.NNNNESN, where S = '+' or '−', N = 0 to 9, and E = 'E'	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME1_SAM	Forward_Angle1_SME1_SAM	Static	float32	Angle in μ rad from start of scan to mid-scan point in forward direction; SAM mode Valid format: NNNNN.N, where NNNNN.N = 67171.0	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME1_SAM	Forward_Angle2_SME1_SAM	Static	float32	Angle in μ rad from mid-scan point to end of scan in forward direction; SAM mode Valid format: NNNNN.N, where NNNNN.N = 67159.0	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME1_SAM	Reverse_Along_SME1_SAM	Static	float64 array (6 values)	Fifth-order polynomial coefficients that describe deviation of reverse along scan mirror motion from linear; SAM mode Valid format: for each term: SN.NNNNESN, where S = '+' or '−', N = 0 to 9, and E = 'E'	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME1_SAM	Reverse_Cross_SME1_SAM	Static	float64 array (6 values)	Fifth-order polynomial coefficients that describe deviation of reverse cross scan mirror motion from linear; SAM mode Valid format: for each term: SN.NNNNESN, where S = '+' or '−', N = 0 to 9, and E = 'E'	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME1_SAM	Reverse_angle1_SME1_SAM	Static	float32	Angle in μ rad from start of scan to mid-scan point in reverse direction; SAM mode Valid format: NNNNN.N, where NNNNN.N = 67159.0	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME1_SAM	Reverse_angle2_SME1_SAM	Static	float32	Angle in μ rad from mid-scan point to end of scan in reverse direction; SAM mode Valid format: NNNNN.N, where NNNNN.N = 67171.0	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME2_SAM	Forward_Along_SME2_SAM	Static	float64 array (6 values)	Fifth-order polynomial coefficients that describe deviation of forward along scan mirror motion from linear; SAM mode Valid format: for each term: SN.NNNNESN, where S = '+' or '−', N = 0 to 9, and E = 'E'	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME2_SAM	Forward_Cross_SME2_SAM	Static	float64 array (6 values)	Fifth-order polynomial coefficients that describe deviation of forward cross scan mirror motion from linear; SAM mode Valid format: for each term: SN.NNNNESN, where S = '+' or '−', N = 0 to 9, and E = 'E'	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME2_SAM	Forward_Angle1_SME2_SAM	Static	float32	Angle in μ rad from start of scan to mid-scan point in forward direction; SAM mode Valid format: NNNNN.N, where NNNNN.N = 67182.0	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME2_SAM	Forward_Angle2_SME2_SAM	Static	float32	Angle in μ rad from mid-scan point to end of scan in forward direction; SAM mode Valid format: NNNNN.N, where NNNNN.N = 67160.0	No	Yes	SBRS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Mirror_Parameters GROUP: Angles_SME2_SAM	Reverse_Along_SME2_SAM	Static	float64 array (6 values)	Fifth-order polynomial coefficients that describe deviation of reverse along scan mirror motion from linear; SAM mode Valid format: for each term: SN.NNNNESN, where S = '+' or '−', N = 0 to 9, and E = 'E'	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME2_SAM	Reverse_Cross_SME2_SAM	Static	float64 array (6 values)	Fifth-order polynomial coefficients that describe deviation of reverse cross scan mirror motion from linear; SAM mode Valid format: for each term: SN.NNNNESN, where S = '+' or '−', N = 0 to 9, and E = 'E'	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME2_SAM	Reverse_angle1_SME2_SAM	Static	float32	Angle in μ rad from start of scan to mid-scan point in reverse direction; SAM mode Valid format: NNNNN.N, where NNNNN.N = 67160.0	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME2_SAM	Reverse_angle2_SME2_SAM	Static	float32	Angle in μ rad from mid-scan point to end of scan in reverse direction; SAM mode Valid format: NNNNN.N, where NNNNN.N = 67182.0	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME1_Bump	Forward_Along_SME1_Bump	Static	float64 array (6 values)	Fifth-order polynomial coefficients that describe deviation of forward along scan mirror motion from linear; Bumper mode Valid format: for each term: SN.NNNNESN, where S = '+' or '−', N = 0 to 9, and E = 'E'	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME1_Bump	Forward_Cross_SME1_Bump	Static	float64 array (6 values)	Fifth-order polynomial coefficients that describe deviation of forward cross scan mirror motion from linear; Bumper mode Valid format: for each term: SN.NNNNESN, where S = '+' or '−', N = 0 to 9, and E = 'E'	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME1_Bump	Forward_Angle1_SME1_Bump	Static	float32	Angle in μ rad from start of scan to mid-scan point in forward direction; Bumper mode Valid format: NNNNN.N, where NNNNN.N = 67171.0	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME1_Bump	Forward_Angle2_SME1_Bump	Static	float32	Angle in μ rad from mid-scan point to end of scan in forward direction; Bumper mode Valid format: NNNNN.N, where NNNNN.N = 67159.0	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME1_Bump	Reverse_Along_SME1_Bump	Static	float64 array (6 values)	Fifth-order polynomial coefficients that describe deviation of reverse along scan mirror motion from linear; Bumper mode Valid format: SN.NNNNESN, where S = '+' or '−', N = 0 to 9, and E = 'E'	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME1_Bump	Reverse_Cross_SME1_Bump	Static	float64 array (6 values)	Fifth-order polynomial coefficients that describe deviation of reverse cross scan mirror motion from linear; Bumper mode Valid format: SN.NNNNESN, where S = '+' or '−', N = 0 to 9, and E = 'E'	No	Yes	SBRS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Mirror_Parameters GROUP: Angles_SME1_Bump	Reverse_Angle1_SME1_Bump	Static	float32	Angle in μ rad from start of scan to mid-scan point in reverse direction; Bumper mode Valid format: NNNNN.N, where NNNNN.N = 67159.0	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME1_Bump	Reverse_Angle2_SME1_Bump	Static	float32	Angle in μ rad from mid-scan point to end of scan in reverse direction; Bumper mode Valid format: NNNNN.N, where NNNNN.N = 67171.0	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME2_Bump	Forward_Along_SME2_Bump	Static	float64 array (6 values)	Fifth-order polynomial coefficients that describe deviation of forward along scan mirror motion from linear; Bumper mode Valid format: SN.NNNNESN, where S = '+' or '−', N = 0 to 9, and E = 'E'	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME2_Bump	Forward_Cross_SME2_Bump	Static	float64 array (6 values)	Fifth-order polynomial coefficients that describe deviation of forward cross scan mirror motion from linear; Bumper mode Valid format: SN.NNNNESN, where S = '+' or '−', N = 0 to 9, and E = 'E'	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME2_Bump	Forward_Angle1_SME2_Bump	Static	float32	Angle in μ rad from start of scan to mid-scan point in forward direction; Bumper mode Valid format: NNNNN.N, where NNNNN.N = 67182.0	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME2_Bump	Forward_Angle2_SME2_Bump	Static	float32	Angle in μ rad from mid-scan point to end of scan in forward direction; Bumper mode Valid format: NNNNN.N, where NNNNN.N = 67162.0	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME2_Bump	Reverse_Along_SME2_Bump	Static	float64 array (6 values)	Fifth-order polynomial coefficients that describe deviation of reverse along scan mirror motion from linear; Bumper mode Valid format: for each term: SN.NNNNESN, where S = '+' or '−', N = 0 to 9, and E = 'E'	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME2_Bump	Reverse_Cross_SME2_Bump	Static	float64 array (6 values)	Fifth-order polynomial coefficients that describe deviation of reverse cross scan mirror motion from linear; Bumper mode Valid format: for each term: SN.NNNNESN, where S = '+' or '−', N = 0 to 9, and E = 'E'	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME2_Bump	Reverse_Angle1_SME2_Bump	Static	float32	Angle in μ rad from start of scan to mid-scan point in reverse direction; Bumper mode Valid format: NNNNN.N, where NNNNN.N = 67160.0	No	Yes	SBRS
Group: Mirror_Parameters GROUP: Angles_SME2_Bump	Reverse_Angle2_SME2_Bump	Static	float32	Angle in μ rad from mid-scan point to end of scan in reverse direction; Bumper mode Valid format: NNNNN.N, where NNNNN.N = 67182.0	No	Yes	SBRS
Group: Mirror_Parameters	Error_Conversion_Factor	Static	Real	First half and second half scan mirror error measurement units in microseconds Valid format. = N.NNNNNESN, where N.NNNNNESN = 0.18845E-6 (5.306437 MHz)	No	Yes	SBRS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Scan_Line_Corrector	Primary_Angular_Velocity	Static	float32	Angular velocity in radians per second of primary scan line corrector Valid format: N.NNNNN, where N.NNNNN = 0.00966	No	Yes	SBRS
Group: Scan_Line_Corrector	Secondary_Angular_Velocity	Static	float32	Angular velocity in radians per second of secondary scan line corrector Valid format: N.NNNNN, where N.NNNNN = 0.00960	No	Yes	SBRS
Group: Scan_Line_Corrector	Primary_Corrector_Motion	Static	float32 array (6 values)	Fifth-order polynomial coefficients that describe motion of primary scan line corrector Valid format: for each term: N.NNNNN, where N.NNNNN = 0.0 (TBS)	No	Yes	SBRS
Group: Scan_Line_Corrector	Secondary_Corrector_Motion	Static	float32 array (6 values)	Fifth-order polynomial coefficients that describe motion of secondary scan line corrector Valid format: for each term: N.NNNNN, where N.NNNNN = 0.0 (TBS)	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Band_Offsets	Along_Scan_Band_Offset_S	Static	float32 array (8 values)	Nominal displacement in μ rad from center of focal plane to each band's optical axis Valid format: NNNN.NNN, where NNNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Band_Offsets	Across_Scan_Band_Offsets	Static	float32 array (8 values)	Nominal displacement in μ rad from center of focal plane to each band's scan motion axis Valid format: NNNN.NNN, where NNNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Band_Offsets	Forward_Focal_Plane_Offsets	Static	float32 array (8 values)	Offset in instrument fields of view (IFOVs) for focal plane forward scans Valid format: NNN.NNN, where NNN.NNN = TBS	Yes	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Band_Offsets	Reverse_Focal_Plane_Offsets	Static	float32 array (8 values)	Offset in IFOVs for focal plane reverse scans Valid format: NNN.NNN, where NNN.NNN = TBS	Yes	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Forward_Along_Scan_DO_B1	Static	float32 array (16 values)	Forward along scan detector offsets in IFOV for each detector in band 1 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Reverse_Along_Scan_DO_B1	Static	float32 array (16 values)	Reverse along scan detector offsets in IFOV for each detector in band 1 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Forward_Along_Scan_DO_B2	Static	float32 array (16 values)	Forward along scan detector offsets in IFOV for each detector in band 2 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Reverse_Along_Scan_DO_B2	Static	float32 array (16 values)	Reverse along scan detector offsets in IFOV for each detector in band 2 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Forward_Along_Scan_DO_B3	Static	float32 array (16 values)	Forward along scan detector offsets in IFOV for each detector in band 3 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Reverse_Along_Scan_DO_B3	Static	float32 array (16 values)	Reverse along scan detector offsets in IFOV for each detector in band 3 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Forward_Along_Scan_DO_B4	Static	float32 array (16 values)	Forward along scan detector offsets in IFOV for each detector in band 4 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Reverse_Along_Scan_DO_B4	Static	float32 array (16 values)	Reverse along scan detector offsets in IFOV for each detector in band 4 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Forward_Along_Scan_DO_B5	Static	float32 array (16 values)	Forward along scan detector offsets in IFOV for each detector in band 5 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Reverse_Along_Scan_DO_B5	Static	float32 array (16 values)	Reverse along scan detector offsets in IFOV for each detector in band 5 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Forward_Along_Scan_DO_B6	Static	float32 array (8 values)	Forward along scan detector offsets in IFOV for each detector in band 6 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Reverse_Along_Scan_DO_B6	Static	float32 array (8 values)	Reverse along scan detector offsets in IFOV for each detector in band 6 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Forward_Along_Scan_DO_B7	Static	float32 array (16 values)	Forward along scan detector offsets in IFOV for each detector in band 7 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Reverse_Along_Scan_DO_B7	Static	float32 array (16 values)	Reverse along scan detector offsets in IFOV for each detector in band 7 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Forward_Along_Scan_DO_B8	Static	float32 array (32 values)	Forward along scan detector offsets in IFOV for each detector in band 8 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Reverse_Along_Scan_DO_B8	Static	float32 array (32 values)	Reverse along scan detector offsets in IFOV for each detector in band 8 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Forward_Across_Scan_DO_B1	Static	float32 array (16 values)	Forward along scan detector offsets in IFOV for each detector in band 1 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Reverse_Across_Scan_DO_B1	Static	float32 array (16 values)	Reverse along scan detector offsets in IFOV for each detector in band 1 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Forward_Across_Scan_DO_B2	Static	float32 array (16 values)	Forward along scan detector offsets in IFOV for each detector in band 2 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Reverse_Across_Scan_DO_B2	Static	float32 array (16 values)	Reverse along scan detector offsets in IFOV for each detector in band 2 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Forward_Across_Scan_DO_B3	Static	float32 array (16 values)	Forward along scan detector offsets in IFOV for each detector in band 3 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Reverse_Across_Scan_DO_B3	Static	float32 array (16 values)	Reverse along scan detector offsets in IFOV for each detector in band 3 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Forward_Across_Scan_DO_B4	Static	float32 array (16 values)	Forward along scan detector offsets in IFOV for each detector in band 4 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Reverse_Across_Scan_DO_B4	Static	float32 array (16 values)	Reverse along scan detector offsets in IFOV for each detector in band 4 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Forward_Across_Scan_DO_B5	Static	float32 array (16 values)	Forward along scan detector offsets in IFOV for each detector in band 5 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Reverse_Across_Scan_DO_B5	Static	float32 array (16 values)	Reverse along scan detector offsets in IFOV for each detector in band 5 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Forward_Across_Scan_DO_B6	Static	float32 array (8 values)	Forward along scan detector offsets in IFOV for each detector in band 6 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Reverse_Across_Scan_DO_B6	Static	float32 array (8 values)	Reverse along scan detector offsets in IFOV for each detector in band 6 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Forward_Across_Scan_DO_B7	Static	float32 array (16 values)	Forward along scan detector offsets in IFOV for each detector in band 7 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Reverse_Across_Scan_DO_B7	Static	float32 array (16 values)	Reverse along scan detector offsets in IFOV for each detector in band 7 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Forward_Across_Scan_DO_B8	Static	float32 array (32 values)	Forward along scan detector offsets in IFOV for each detector in band 8 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Detector_Offsets	Reverse_Across_Scan_DO_B8	Static	float32 array (32 values)	Reverse along scan detector offsets in IFOV for each detector in band 8 Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Odd_Even_Offsets	Forward_Even_Detector_Shift	Static	float32 array (8 values)	Adjustments in IFOVs to compensate for forward band offsets, even detector layout geometry and multiplexer sampling for bands 1 through 8 Valid format: NNN.NNN, where NNN.NNN = TBS	Yes	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Odd_Even_Offsets	Forward_Odd_Detector_Shift	Static	float32 array (8 values)	Adjustments in IFOVs to compensate for forward band offsets, odd detector layout geometry and multiplexer sampling for bands 1 through 8 Valid format: NNN.NNN, where NNN.NNN = TBS	Yes	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Odd_Even_Offsets	Reverse_Even_Detector_Shift	Static	float32 array (8 values)	Adjustments in IFOVs to compensate for reverse band offsets, even detector layout geometry and multiplexer sampling for bands 1 through 8 Valid format: NNN.NNN, where NNN.NNN = TBS	Yes	Yes	SBRS
Group: Focal_Plane_Parameters GROUP: Odd_Even_Offsets	Reverse_Odd_Detector_Shift	Static	float32 array (8 values)	Adjustments in IFOVs to compensate for reverse band offsets, odd detector layout geometry and multiplexer sampling for bands 1 through 8 Valid format: NNN.NNN, where NNN.NNN = TBS	Yes	Yes	SBRS
Group: Attitude_Parameters	Gyro_To_Attitude_Matrix	Static	float32 array (9 values)	Matrix describing relationship of gyro axis to attitude control reference axis Valid format: N.N, where N.N = 0.0 (TBS)	Yes	Yes	LMC
Group: Attitude_Parameters	ADSA_To_ETM_Matrix	Static	float32 array (9 values)	Matrix describing relationship of ADSA to ETM+ optical Axis Valid format: N.N, where N.N = 0.0 (TBS)	Yes	Yes	LMC
Group: Attitude_Parameters	Attitude_To_ETM_Matrix	Static	float32 array (9 values)	Matrix describing relationship of attitude control reference axis to ETM+ optical axis Valid format: N.NNNNNNNN, where N.NNNNNNNN = 0.0 (TBS)	Yes	Yes	LMC
Group: Attitude_Parameters	Spacecraft_Roll_Bias	Static	float32	Spacecraft roll bias in radians Valid format: N.NNNNNNNN, where N.NNNNNNNN = TBS	Yes	Yes	LMC

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Attitude_Parameters	Spacecraft_Pitch_Bias	Static	float32	Spacecraft pitch bias in radians Valid format: N.NNNNNNNN, where N.NNNNNNNN = TBS	Yes	Yes	LMC
Group: Attitude_Parameters	Spacecraft_Yaw_Bias	Static	float32	Spacecraft yaw bias in radians Valid format: N.NNNNNNNN, where N.NNNNNNNN = TBS	Yes	Yes	LMC
Group: Time_Parameters	Scan_Time	Static	float32	Nominal scan time in μ rad per second Valid format: NNNNN.N, where NNNNN.N = 60743.0	No	Yes	SBRS
Group: Time_Parameters	Forward_First_Half_Time	Static	float32	Nominal forward first half scan time in μ rad per second Valid format: NNNNN.N, where NNNNN.N = 30371.4	No	Yes	SBRS
Group: Time_Parameters	Forward_Second_Half_Time	Static	float32	Nominal forward second half scan time in μ rad per second Valid format: NNNNN.N, where NNNNN.N = 30371.6	No	Yes	SBRS
Group: Time_Parameters	Reverse_First_Half_Time	Static	float32	Nominal reverse first half scan time in μ rad per second Valid format: NNNNN.N, where NNNNN.N = 30371.6	No	Yes	SBRS
Group: Time_Parameters	Reverse_Second_Half_Time	Static	float32	Nominal reverse second half scan time in μ rad per second Valid format: NNNNN.N, where NNNNN.N = 30371.4	No	Yes	SBRS
Group: Transfer_Function GROUP: IMU	Fn	Static	float64	Inertial measurement unit transfer function resonant frequency (Hz) Valid format: N.NNNN, where N.NNNN = TBS	No	Yes	LMC
Group: Transfer_Function GROUP: IMU	Zeta	Static	float64	Inertial measurement unit transfer function damping coefficient Valid format: N.NNNN, where N.NNNN = TBS	No	Yes	LMC
Group: Transfer_Function GROUP: IMU	Tau	Static	float64	Inertial measurement unit transfer function denominator time constant (seconds) Valid format: NN.NNNNENN, where NN.NNNNENN = TBS	No	Yes	LMC
Group: Transfer_Function GROUP: IMU	P	Static	float64	Inertial measurement unit transfer function numerator time constant (seconds) Valid format: NN.NNNNENN, where NN.NNNNENN = TBS	No	Yes	LMC
Group: Transfer_Function GROUP: IMU	Ak	Static	float64	Inertial measurement unit transfer function DC gain Valid format: N.NNNNN, where N.NNNNN = TBS	No	Yes	LMC
Group: Transfer_Function GROUP: ADS	ADS_num	Static	float64 array (18 values)	Transfer function numerator coefficients in order a0, a1, a2, a3, a4, a5; one set of six coefficients for each of three ADS units; determined at 15 degrees C Valid format: N.NNNNEN, where N.NNNNEN = TBS	No	Yes	LMC
Group: Transfer_Function GROUP: ADS	ADS_den	Static	float64 array (18 values)	Transfer function denominator coefficients in order b0, b1, b2, b3, b4, b5; one set of six coefficients for each of three ADS units; determined at 15 degrees C Valid format: N.NNNNEN, where N.NNNNEN = TBS	No	Yes	LMC

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Transfer_Function GROUP: ADS	ADS_num_temp	Static	float64 array (18 values)	Temperature dependent part of ADS transfer function numerator coefficients in order da0, da1, da2, da3, da4, da5; one set of six coefficients for each of three ADS units; change per degree C Valid format: N.NNNNNEN, where: N.NNNNNEN = TBS	No	Yes	LMC
Group: Transfer_Function GROUP: ADS	ADS_den_temp	Static	float64 array (18 values)	Temperature dependent part of ADS transfer function denominator coefficients in order da0, da1, da2, da3, da4, da5. One set of six coefficients for each of three ADS units. Change per degree C Valid format: N.NNNNNEN, where: N.NNNNNEN = TBS	No	Yes	LMC
Group: Transfer_Function GROUP: Prefilter	ADSPre_W	Static	float64 array (5 values)	ADS prefilter transfer function quadratic term resonant periods (Note: Given as period instead of frequency because was used in L6 so that transfer f function can be set to unity if necessary.) Valid format: N.NNNNNNNN, where N.NNNNNNNN = TBS	No	Yes	LMC
Group: Transfer_Function GROUP: Prefilter	ADSPre_H	Static	float64 array (5 values)	ADS prefilter transfer function quadratic term damping coefficients Valid format: N.NNNNNNNN, where N.NNNNNNNN = TBS	No	Yes	LMC
Group: Transfer_Function GROUP: Prefilter	ADSPre_T	Static	float64 array (5 values)	ADS prefilter transfer function linear term time constants Valid format: N.NNNNNNNN, where N.NNNNNNNN = TBS	No	Yes	LMC
Group: UT1_Time_Parameters	UT1_Year	Dynamic	int16 array (180 values)	Year of UT1 time correction prediction; values span 180 days Valid format: YYYY, where YYYY = 1998–2008	Yes	Yes	Natl. Earth Orientation Service
Group: UT1_Time_Parameters	UT1_Month	Dynamic	char8 array (180 values)	Month of UT1 time correction prediction; values span 180 days Valid format: MMM, where MMM = Jan, Feb, Mar, Apr, May, Jun, Jul, Aug, Sep, Oct, Nov, or Dec	Yes	Yes	NEOS
Group: UT1_Time_Parameters	UT1_Day	Dynamic	uint8 array (180 values)	Day of UT1 time correction prediction; values span 180 days Valid format: NN, where NN = 1–31	Yes	Yes	NEOS
Group: UT1_Time_Parameters	UT1_Modified_Julian	Dynamic	int32 array (180 values)	Modified Julian day; values span 180 days: MJD = Julian day – 2 400 000.5; Julian date is a running day count starting 1 January 4713 B.C Valid format: NNNNN, where NNNNN = 50234 (May 31, 1996)	Yes	Yes	NEOS
Group: UT1_Time_Parameters	UT1_X	Dynamic	float32 array (180 values)	X shift pole wander in arc seconds; values span 180 days Valid format: N.NNNNN, where N.NNNNN = e.g. 0.45431	Yes	Yes	NEOS
Group: UT1_Time_Parameters	UT1_Y	Dynamic	float32 array (180 values)	Y shift pole wander in arc seconds; values span 180 days Valid format: N.NNNNN, where N.NNNNN = e.g., 0.13454	Yes	Yes	NEOS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: UT1_Time_Parameters	UT1_UTC	Dynamic	float32 array (180 values)	UT1 – UTC time difference in seconds. Values span180 days Valid format: N.NNNNN, where N.NNNNN = (e.g., 0.44321)	Yes	Yes	NEOS
Group: Detector_Status	Status_Band 1	Dynamic	char8 array (16 values)	Health status of band 1's 16 detectors Valid format: ABCDE, where A = 0 (live), 1 (dead), 2 (intermittent) B = 0 (noise in spec, low gain), 1 (noisy low signal), 2 (noisy high signal), 3(noisy both signals) C = 0 (noise in spec, high gain), 1 (noisy low signal), 2 (noisy high signal), 3(noisy both signals) D = 0 (dynamic range in spec, low gain) 1 (fail, high end), 2 (fail, low end), 3 (fail, both ends) E = 0 (dynamic range in spec, high gain), 1 (fail, low end), 2 (fail, low end), 3 (fail, both ends)	No	Yes	AC02/ AC48
Group: Detector_Status	Status_Band 2	Dynamic	char8 array (16 values)	Health status of band 2's 16 detectors Valid format: as above	No	Yes	AC02/ AC48
Group: Detector_Status	Status_Band 3	Dynamic	char8 array (16 values)	Health status of band 3's 16 detectors Valid format: as above.	No	Yes	AC02/ AC48
Group: Detector_Status	Status_Band 4	Dynamic	char8 array (16 values)	Health status of band 4's 16 detectors Valid format: as above	No	Yes	AC02/ AC48
Group: Detector_Status	Status_Band 5	Dynamic	char8 array (16 values)	Health status of band 5's 16 detectors Valid format: as above	No	Yes	AC02/ AC48
Group: Detector_Status	Status_Band 6	Dynamic	char8 array (8 values)	Health status of band 6's 8 detectors Valid format: as above	No	Yes	BL10 in thermal vacuum
Group: Detector_Status	Status_Band 7	Dynamic	char8 array (16 values)	Health status of band 7's 16 detectors Valid format: as above	No	Yes	AC02/ AC48
Group: Detector_Status	Status_Band 8	Dynamic	char8 array (32 values)	Health status of band 8's 32 detectors Valid format: as above	No	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_Low	B1L_Prelaunch	Static	float <u>32</u> array (16 values)	Band 1 prelaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_Low	B1L_Postlaunch	Static	float <u>32</u> array (16 values)	Band 1 postlaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Detector_Gains GROUP: Detector_Gains_Low	B1L_Current	Dynamic	float <u>32</u> array (16 values)	Band 1 current gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	Yes	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_Low	B2L_Prelaunch	Static	float <u>32</u> array (16 values)	Band 2 prelaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	AC02/ AC48

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Detector_Gains GROUP: Detector_Gains_Low	B2L_Postlaunch	Static	float ₃₂ array (16 values)	Band 2 postlaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Detector_Gains GROUP: Detector_Gains_Low	B2L_Current	Dynamic	float ₃₂ array (16 values)	Band 2 current gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	Yes	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_Low	B3L_Prelaunch	Static	float ₃₂ array (16 values)	Band 3 prelaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_Low	B3L_Postlaunch	Static	float ₃₂ array (16 values)	Band 3 postlaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Detector_Gains GROUP: Detector_Gains_Low	B3L_Current	Dynamic	float ₃₂ array (16 values)	Band 3 current gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	Yes	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_Low	B4L_Prelaunch	Static	float ₃₂ array (16 values)	Band 4 prelaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_Low	B4L_Postlaunch	Static	float ₃₂ array (16 values)	Band 4 postlaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Detector_Gains GROUP: Detector_Gains_Low	B4L_Current	Dynamic	float ₃₂ array (16 values)	Band 4 current gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	Yes	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_Low	B5L_Prelaunch	Static	float ₃₂ array16 values)	Band 5 prelaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_Low	B5L_Postlaunch	Static	float ₃₂ array (16 values)	Band 5 postlaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Detector_Gains GROUP: Detector_Gains_Low	B5L_Current	Dynamic	float ₃₂ array (16 values)	Band 5 current gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	Yes	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_Low	B6L_Prelaunch	Static	float ₃₂ array (8 values)	Band 6 prelaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	BL10 in thermal vacuum
Group: Detector_Gains GROUP: Detector_Gains_Low	B6L_Postlaunch	Static	float ₃₂ array (8 values)	Band 6 postlaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Detector_Gains GROUP: Detector_Gains_Low	B6L_Current	Dynamic	float ₃₂ array (8 values)	Band 6 current gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	Yes	Yes	BL10 in thermal vacuum
Group: Detector_Gains GROUP: Detector_Gains_Low	B7L_Prelaunch	Static	float ₃₂ array (16 values)	Band 7 prelaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	AC02/ AC48

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Detector_Gains GROUP: Detector_Gains_Low	B7L_Postlaunch	Static	float ₃₂ array (16 values)	Band 7 postlaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Detector_Gains GROUP: Detector_Gains_Low	B7L_Current	Dynamic	float ₃₂ array (16 values)	Band 7 current gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	Yes	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_Low	B8L_Prelaunch	Static	float ₃₂ array (32 values)	Band 8 prelaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_Low	B8L_Postlaunch	Static	float ₃₂ array (32 values)	Band 8 postlaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Detector_Gains GROUP: Detector_Gains_Low	B8L_Current	Dynamic	float ₃₂ array (32 values)	Band 8 current gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	Yes	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_High	B1H_Prelaunch	Static	float ₃₂ array (16 values)	Band 1 prelaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_High	B1H_Postlaunch	Static	float ₃₂ array (16 values)	Band 1 postlaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Detector_Gains GROUP: Detector_Gains_High	B1H_Current	Dynamic	float ₃₂ array (16 values)	Band 1 current gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	Yes	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_High	B2H_Prelaunch	Static	float ₃₂ array (16 values)	Band 2 prelaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_High	B2H_Postlaunch	Static	float ₃₂ array (16 values)	Band 2 postlaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Detector_Gains GROUP: Detector_Gains_High	B2H_Current	Dynamic	float ₃₂ array (16 values)	Band 2 current gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	Yes	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_High	B3H_Prelaunch	Static	float ₃₂ array (16 values)	Band 3 prelaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_High	B3H_Postlaunch	Static	float ₃₂ array (16 values)	Band 3 postlaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Detector_Gains GROUP: Detector_Gains_High	B3H_Current	Dynamic	float ₃₂ array (16 values)	Band 3 current gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	Yes	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_High	B4H_Prelaunch	Static	float ₃₂ array (16 values)	Band 4 prelaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	AC02/ AC48

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Detector_Gains GROUP: Detector_Gains_High	B4H_Postlaunch	Static	float ₃₂ array (16 values)	Band 4 postlaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Detector_Gains GROUP: Detector_Gains_High	B4H_Current	Dynamic	float ₃₂ array (16 values)	Band 4 current gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	Yes	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_High	B5H_Prelaunch	Static	float ₃₂ array (16 values)	Band 5 prelaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_High	B5H_Postlaunch	Static	float ₃₂ array (16 values)	Band 5 postlaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Detector_Gains GROUP: Detector_Gains_High	B5H_Current	Dynamic	float ₃₂ array (16 values)	Band 5 current gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	Yes	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_High	B6H_Prelaunch	Static	float ₃₂ array (8 values)	Band 6 prelaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	BL10 in thermal vacuum
Group: Detector_Gains GROUP: Detector_Gains_High	B6H_Postlaunch	Static	float ₃₂ array (8 values)	Band 6 postlaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Detector_Gains GROUP: Detector_Gains_High	B6H_Current	Dynamic	float ₃₂ array (8 values)	Band 6 current gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	Yes	Yes	BL10 in thermal vacuum
Group: Detector_Gains GROUP: Detector_Gains_High	B7H_Prelaunch	Static	float ₃₂ array (16 values)	Band 7 prelaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_High	B7H_Postlaunch	Static	float ₃₂ array (16 values)	Band 7 postlaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Detector_Gains GROUP: Detector_Gains_High	B7H_Current	Dynamic	float ₃₂ array (16 values)	Band 7 current gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	Yes	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_High	B8H_Prelaunch	Static	float ₃₂ array (32 values)	Band 8 prelaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	AC02/ AC48
Group: Detector_Gains GROUP: Detector_Gains_High	B8H_Postlaunch	Static	float ₃₂ array (32 values)	Band 8 postlaunch gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Detector_Gains GROUP: Detector_Gains_High	B8H_Current	Dynamic	float ₃₂ array (32 values)	Band 8 current gain in counts/W/m^2-ster-μm Valid format: NNN.NNNN, where NNN.NNNN = TBS	Yes	Yes	AC02/ AC48
Group: Bias_Locations	Forward_Bias_Location_30	Static	int16	Offset from internal calibrator pulse to per-line bias location starting point for bands 1–5 and 7 Valid format: NNN, where NNN = TBS	No	Yes	LPSO – From prelaunch AC02/ AC48

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Bias_Locations	Reverse_Bias_Length_30	Static	int16	Minor frames to use in calculating per-line bias for bands 1–5 and 7 Valid format: NNN, where NNN = TBS	No	Yes	LPSO – From prelaunch AC02/ AC48
Group: Bias_Locations	Forward_Bias_Location_60	Static	int16	Offset from internal calibrator pulse to per-line bias location starting point for band 6 Valid format: NNN, where NNN = TBS	No	Yes	LPSO – from prelaunch BL10
Group: Bias_Locations	Reverse_Bias_Length_60	Static	int16	Minor frames to use in calculating per-line bias for band 6 Valid format: NNN, where NNN = TBS	No	Yes	LPSO – from prelaunch BL10
Group: Bias_Locations	Forward_Bias_Location_15	Static	int16	Offset from internal calibrator pulse to per-line bias location starting point for band 8 Valid format: NNN, where NNN = TBS	No	Yes	LPSO – From prelaunch AC02/ AC48
Group: Bias_Locations	Reverse_Bias_Length_15	Static	int16	Minor frames to use in calculating per-line bias for band 8 Valid format: NNN, where NNN = TBS	No	Yes	LPSO – From prelaunch AC02/ AC48
Group: Detector_Biases_B6 GROUP: Detector_Biases_B6_Low	B6L_Bias_Prelaunch	Static	float ₃₂ array (8 values)	Band 6 prelaunch low gain bias in digital counts Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	BL10 in thermal vacuum
Group: Detector_Biases_B6 GROUP: Detector_Biases_B6_Low	B6L_Bias_PostLaunch	Static	float ₃₂ array (8 values)	Band 6 postlaunch low gain bias in digital counts Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Detector_Biases_B6 GROUP: Detector_Biases_B6_Low	B6L_Bias_Current	Dynamic	float ₃₂ array (8 values)	Band 6 current low gain bias in digital counts Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	BL10 in thermal vacuum
Group: Detector_Biases_B6 GROUP: Detector_Biases_B6_High	B6H_Bias_Prelaunch	Static	float ₃₂ array (8 values)	Band 6 prelaunch high gain bias in digital counts Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	BL10 in thermal vacuum
Group: Detector_Biases_B6 GROUP: Detector_Biases_B6_High	B6H_Bias_PostLaunch	Static	float ₃₂ array (8 values)	Band 6 postlaunch high gain bias in digital counts Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Detector_Biases_B6 GROUP: Detector_Biases_B6_High	B6H_Bias_Current	Dynamic	float ₃₂ array (8 values)	Band 6 current high gain bias in digital counts Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	BL10 in thermal vacuum
Group: ACCA_Biases GROUP: ACCA_Biases_Low	B1L_ACCA_Bias	Dynamic	float32 array (16 values)	Band 1 low-gain ACCA bias in digital counts for detectors 1–16 Valid format: NNN.NNN, where NNN.NNN = TBS	Yes	No	LPSO
Group: ACCA_Biases GROUP: ACCA_Biases_Low	B2L_ACCA_Bias	Dynamic	float32 array (16 values)	Band 2 low-gain ACCA bias in digital counts for detectors 1–16 Valid format: NNN.NNN, where NNN.NNN = TBS	Yes	No	LPSO
Group: ACCA_Biases GROUP: ACCA_Biases_Low	B3L_ACCA_Bias	Dynamic	float32 array (16 values)	Band 3 low-gain ACCA bias in digital counts for detectors 1–16 Valid format: NNN.NNN, where NNN.NNN = TBS	Yes	No	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: ACCA_Biases GROUP: ACCA_Biases_Low	B4L_ACCA_Bias	Dynamic	float32 array (16 values)	Band 4 low-gain ACCA bias in digital counts for detectors 1–16 Valid format: NNN.NNN, where NNN.NNN = TBS	Yes	No	LPSO
Group: ACCA_Biases GROUP: ACCA_Biases_Low	B5L_ACCA_Bias	Dynamic	float32 array (16 values)	Band 5 low-gain ACCA bias in digital counts for detectors 1–16 Valid format: NNN.NNN, where NNN.NNN = TBS	Yes	No	LPSO
Group: ACCA_Biases GROUP: ACCA_Biases_Low	B6L_ACCA_Bias	Dynamic	float32 array (8 values)	Band 6 low-gain ACCA bias in digital counts for detectors 1–8 Valid format: NNN.NNN, where NNN.NNN = TBS	Yes	No	LPSO
Group: ACCA_Biases GROUP: ACCA_Biases_Low	B7L_ACCA_Bias	Dynamic	float32 array (16 values)	Band 7 low-gain ACCA bias in digital counts for detectors 1–16 Valid format: NNN.NNN, where NNN.NNN = TBS	Yes	No	LPSO
Group: ACCA_Biases GROUP: ACCA_Biases_Low	B8L_ACCA_Bias	Dynamic	float32 array (32 values)	Band 8 low-gain ACCA bias in digital counts for detectors 1–32 Valid format: NNN.NNN, where NNN.NNN = TBS	Yes	No	LPSO
Group: ACCA_Biases GROUP: ACCA_Biases_High	B1H_ACCA_Bias	Dynamic	float32 array (16 values)	Band 1 high gain ACCA bias in digital counts for detectors 1–16 Valid format: NNN.NNN, where NNN.NNN = TBS	Yes	No	LPSO
Group: ACCA_Biases GROUP: ACCA_Biases_High	B2H_ACCA_Bias	Dynamic	float32 array (16 values)	Band 2 high gain ACCA bias in digital counts for detectors 1–16 Valid format: NNN.NNN, where NNN.NNN = TBS	Yes	No	LPSO
Group: ACCA_Biases GROUP: ACCA_Biases_High	B3H_ACCA_Bias	Dynamic	float32 array (16 values)	Band 3 high gain ACCA bias in digital counts for detectors 1–16 Valid format: NNN.NNN, where NNN.NNN = TBS	Yes	No	LPSO
Group: ACCA_Biases GROUP: ACCA_Biases_High	B4H_ACCA_Bias	Dynamic	float32 array (16 values)	Band 4 high gain ACCA bias in digital counts for detectors 1–16 Valid format: NNN.NNN, where NNN.NNN = TBS	Yes	No	LPSO
Group: ACCA_Biases GROUP: ACCA_Biases_High	B5H_ACCA_Bias	Dynamic	float32 array (16 values)	Band 5 high gain ACCA bias in digital counts for detectors 1–16 Valid format: NNN.NNN, where NNN.NNN = TBS	Yes	No	LPSO
Group: ACCA_Biases GROUP: ACCA_Biases_High	B6H_ACCA_Bias	Dynamic	float32 array (8 values)	Band 6 high gain ACCA bias in digital counts for detectors 1–8 Valid format: NNN.NNN, where NNN.NNN = TBS	Yes	No	LPSO
Group: ACCA_Biases GROUP: ACCA_Biases_High	B7H_ACCA_Bias	Dynamic	float32 array (16 values)	Band 7 high gain ACCA bias in digital counts for detectors 1–16 Valid format: NNN.NNN, where NNN.NNN = TBS	Yes	No	LPSO
Group: ACCA_Biases GROUP: ACCA_Biases_High	B8H_ACCA_Bias	Dynamic	float32 array (32 values)	Band 8 high gain ACCA bias in digital counts for detectors 1–32 Valid format: NNN.NNN, where NNN.NNN = TBS	Yes	No	LPSO
Group: ACCA_Thresholds	Thresh_B3	Dynamic	float32	Band 3 ACCA threshold Valid format: N.NNNN, where N.NNNN = 0.3000	Yes	No	LPSO
Group: ACCA_Thresholds	Thresh_B3_Lower	Dynamic	float32	Band 3 ACCA land reflectance threshold Valid format: NN.NN, where NN.NN = 0.06	Yes	No	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: ACCA_Thresholds	Thresh_B56_High	Dynamic	float32	Band 5-6 high composite threshold Valid format: NNN.NNN, where NNN.NNN = 225.000	Yes	No	LPSO
Group: ACCA_Thresholds	Thresh_B56_Low	Dynamic	float32	Band 5-6 low composite threshold Valid format: NNN.NNN, where NNN.NNN = 210.000	Yes	No	LPSO
Group: ACCA_Thresholds	Thresh_B6	Dynamic	float32	Band 6 threshold – maximum cloud temperature Valid format: NNN.NNN, where NNN.NNN = 300.000	Yes	No	LPSO
Group: ACCA_Thresholds	Thresh_B45_Ratio	Dynamic	float32	Band 4-5 ratio threshold Valid format: N.NNNN, where N.NNNN = 1.0750	Yes	No	LPSO
Group: ACCA_Thresholds	Thresh_B42_Ratio	Dynamic	float32	Band 4-2 ratio threshold Valid format: N.NNNN, where N.NNNN = 2.0000	Yes	No	LPSO
Group: ACCA_Thresholds	Thresh_B43_Ratio	Dynamic	float32	Band 4-3 ratio threshold Valid format: N.NNNN, where N.NNNN = 2.0000	Yes	No	LPSO
Group: ACCA_Thresholds	Thresh_NDSI_Max	Dynamic	float32	Normalized snow difference index ceiling Valid format: N.NNNN, where N.NNNN = 0.7000	Yes	No	LPSO
Group: ACCA_Thresholds	Thresh_NDSI_Min	Dynamic	float32	Normalized snow difference index floor Valid format: N.NNNN, where N.NNNN = -0.2500	Yes	No	LPSO
Group: ACCA_Thresholds	Thresh_NDSI_Snow	Dynamic	float32	NDSI threshold used to identify snow Valid format: NN.NNNN, where NN.NNNN = 0.8000	Yes	No	LPSO
Group: ACCA_Thresholds	Cloud_Percent_Min	Dynamic	float32	Minimum cloud cover percentage required for pass two Valid format: N.NNNN, where N.NNNN = 0.4000	Yes	No	LPSO
Group: ACCA_Thresholds	Desert_Index	Dynamic	float32	Desert index (Thresh_45_Ratio/Thresh_42_Ratio) Valid format: N.NNNN, where N.NNNN = 0.5000	Yes	No	LPSO
Group: ACCA_Thresholds	Thresh_Snow_Percent	Dynamic	float32	Maximum snow cover percentage allowed to use looser cloud properties for pass two Valid format: N.NNN, where N.NNN = 1.000	Yes	No	LPSO
Group: ACCA_Thresholds	Thermal_Effect_High	Dynamic	float32	Maximum allowable pass two percentage cloud cover increase allowed using looser cloud properties Valid format: NNN.NNN, where NNN.NNN = 40.000	Yes	No	LPSO
Group: ACCA_Thresholds	Thermal_Effect_Low	Dynamic	float32	Maximum allowable pass two percentage cloud cover increase allowed using narrower cloud properties Valid format: NNN.NNN, where NNN.NNN = 30.000	Yes	No	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: ACCA_Thresholds	B6max_Maxthresh_Diff	Dynamic	float32	Minimum difference allowed between maximum cloud temperature and maximum thermal threshold Valid format: NN.NNN, where NN.NNN = 2.000	Yes	No	LPSO
Group: Solar_Spectral_Irradiances	B1_Solar_Irradiance	Static	float32	Mean solar exoatmospheric irradiance for band 1 in W/m^2-ster-μm Valid format: NNNN.NNN, where NNNN.NNN = 1957.000	Yes	No	LPSO
Group: Solar_Spectral_Irradiances	B2_Solar_Irradiance	Static	float32	Mean solar exoatmosphere irradiance for band 2 in W/m^2-ster-μm Valid format: NNNN.NNN, where NNNN.NNN = 1829.000	Yes	No	LPSO
Group: Solar_Spectral_Irradiances	B3_Solar_Irradiance	Static	float32	Mean solar exoatmosphere irradiance for band 3 in W/m^2-ster-μm Valid format: NNNN.NNN, where NNNN.NNN = 1557.000	Yes	No	LPSO
Group: Solar_Spectral_Irradiances	B4_Solar_Irradiance	Static	float32	Mean solar exoatmosphere irradiance for band 4 in W/m^2-ster-μm Valid format: NNNN.NNN, where NNNN.NNN = 1047.000	Yes	No	LPSO
Group: Solar_Spectral_Irradiances	B5_Solar_Irradiance	Static	float32	Mean solar exoatmosphere irradiance for band 5 in W/m^2-ster-μm Valid format: NNNN.NNN, where NNNN.NNN = 219.300	Yes	No	LPSO
Group: Solar_Spectral_Irradiances	B7_Solar_Irradiance	Static	float32	Mean solar exoatmosphere irradiance for band 7 in W/m^2-ster-μm Valid format: NNNN.NNN, where NNNN.NNN = 74.520	Yes	No	LPSO
Group: Solar_Spectral_Irradiances	B8_Solar_Irradiance	Static	float32	Mean solar exoatmosphere irradiance for band 8 in W/m^2-ster-μm Valid format: NNNN.NNN, where NNNN.NNN = TBS	Yes	No	LPSO
Group: Solar_Spectral_Irradiances	K1_Constant	Stati	float32	Thermal calibration Constant 1 in W/m^2-ster-μm Valid format: NNNN.N.NNN, where NNNN.N.NNN = 607.76	Yes	No	LPSO
Group: Solar_Spectral_Irradiances	K2_Constant	Static	float 32	Thermal calibration Constant 2 in W/m^2-ster-μm Valid format: NNNN.N.NNN, where NNNN.N.NNN = 12065.6	Yes	No	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Scaling_Parameters GROUP: Scaling_Parameters_Low	B1L_Lmin_Lmax	Static	float32 array (2 values)	Postcalibration 8-bit dynamic range scaling factors for band 1, low gain, W/m^2-ster-μm Valid format: NN.NNN, where NN.NNN = TBS	Yes	Yes	Postlaunch
Group: Scaling_Parameters GROUP: Scaling_Parameters_Low	B2L_Lmin_Lmax	Static	float32 array (2 values)	Postcalibration 8-bit dynamic range scaling factors for band 2, low gain, W/m^2-ster-μm Valid format: NN.NNN, where NN.NNN = TBS	Yes	Yes	Postlaunch
Group: Scaling_Parameters GROUP: Scaling_Parameters_Low	B3L_Lmin_Lmax	Static	float32 array (2 values)	Postcalibration 8-bit dynamic range scaling factors for band 3, low gain, W/m^2-ster-μm Valid format: NN.NNN, where NN.NNN = TBS	Yes	Yes	Postlaunch
Group: Scaling_Parameters GROUP: Scaling_Parameters_Low	B4L_Lmin_Lmax	Static	float32 array (2 values)	Postcalibration 8-bit dynamic range scaling factors for band 4, low gain, W/m^2-ster-μm Valid format: NN.NNN, where NN.NNN = TBS	Yes	Yes	Postlaunch
Group: Scaling_Parameters GROUP: Scaling_Parameters_Low	B5L_Lmin_Lmax	Static	float32 array (2 values)	Postcalibration 8-bit dynamic range scaling factors for band 5, low gain, W/m^2-ster-μm Valid format: NN.NNN, where NN.NNN = TBS	Yes	Yes	Postlaunch
Group: Scaling_Parameters GROUP: Scaling_Parameters_Low	B6L_Lmin_Lmax	Static	float32 array (2 values)	Postcalibration 8-bit dynamic range scaling factors for band 6, low gain, W/m^2-ster-μm Valid format: NN.NNN, where NN.NNN = TBS	Yes	Yes	Postlaunch
Group: Scaling_Parameters GROUP: Scaling_Parameters_Low	B7L_Lmin_Lmax	Static	float32 array (2 values)	Postcalibration 8-bit dynamic range scaling factors for band 7, low gain, W/m^2-ster-μm Valid format: NN.NNN, where NN.NNN = TBS	Yes	Yes	Postlaunch
Group: Scaling_Parameters GROUP: Scaling_Parameters_Low	B8L_Lmin_Lmax	Static	float32 array (2 values)	Postcalibration 8-bit dynamic range scaling factors for band 8, low gain, W/m^2-ster-μm Valid format: NN.NNN, where NN.NNN = TBS	Yes	Yes	Postlaunch
Group: Scaling_Parameters GROUP: Scaling_Parameters_High	B1H_Lmin_Lmax	Static	float32 array (2 values)	Postcalibration 8-bit dynamic range scaling factors for band 1, high gain, W/m^2-ster-μm Valid format: NN.NNN, where NN.NNN = TBS	Yes	Yes	Postlaunch
Group: Scaling_Parameters GROUP: Scaling_Parameters_High	B2H_Lmin_Lmax	Static	float32 array (2 values)	Postcalibration 8-bit dynamic range scaling factors for band 2, high gain, W/m^2-ster-μm Valid format: NN.NNN, where NN.NNN = TBS	Yes	Yes	Postlaunch
Group: Scaling_Parameters GROUP: Scaling_Parameters_High	B3H_Lmin_Lmax	Static	float32 array (2 values)	Postcalibration 8-bit dynamic range scaling factors for band 3, high gain, W/m^2-ster-μm Valid format: NN.NNN, where NN.NNN = TBS	Yes	Yes	Postlaunch
Group: Scaling_Parameters GROUP: Scaling_Parameters_High	B4H_Lmin_Lmax	Static	float32 array (2 values)	Postcalibration 8-bit dynamic range scaling factors for band 4, high gain, W/m^2-ster-μm Valid format: NN.NNN, where NN.NNN = TBS	Yes	Yes	Postlaunch

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Scaling_Parameters GROUP: Scaling_Parameters_High	B5H_Lmin_Lmax	Static	float32 array (2 values)	Postcalibration 8-bit dynamic range scaling factors for band 5, high gain, W/m^2-ster-μm Valid format: NN.NNN, where NN.NNN = TBS	Yes	Yes	Postlaunch
Group: Scaling_Parameters GROUP: Scaling_Parameters_High	B6H_Lmin_Lmax	Static	float32 array (2 values)	Postcalibration 8-bit dynamic range scaling factors for band 6, high gain, W/m^2-ster-μm Valid format: NN.NNN, where NN.NNN = TBS	Yes	Yes	Postlaunch
Group: Scaling_Parameters GROUP: Scaling_Parameters_High	B7H_Lmin_Lmax	Static	float32 array (2 values)	Postcalibration 8-bit dynamic range scaling factors for band 7, high gain, W/m^2-ster-μm Valid format: NN.NNN, where NN.NNN = TBS	Yes	Yes	Postlaunch
Group: Scaling_Parameters GROUP: Scaling_Parameters_High	B8H_Lmin_Lmax	Static	float32 array (2 values)	Postcalibration 8-bit dynamic range scaling factors for band 8, high gain, W/m^2-ster-μm Valid format: NN.NNN, where NN.NNN = TBS	Yes	Yes	Postlaunch
Group: MTF_Compensation	B1_weights_along	Dynamic	float64 array (5 values)	Weighting function coefficients used to compute along scan MTFC for band 1 Valid format: NN.NNNNN, where NN.NNNNN = TBS	No	Yes	LPSO
Group: MTF_Compensation	B1_weights_across	Dynamic	float64 array (5 values)	Weighting function coefficients used to compute across scan MTFC for band 1 Valid format: NN.NNNNN, where NN.NNNNN = TBS	No	Yes	LPSO
Group: MTF_Compensation	B2_weights_along	Dynamic	float64 array (5 values)	Weighting function coefficients used to compute along scan MTFC for band 2 Valid format: NN.NNNNN, where NN.NNNNN = TBS	No	Yes	LPSO
Group: MTF_Compensation	B2_weights_across	Dynamic	float64 array (5 values)	Weighting function coefficients used to compute across scan MTFC for band 2 Valid format: NN.NNNNN, where NN.NNNNN = TBS	No	Yes	LPSO
Group: MTF_Compensation	B3_weights_along	Dynamic	float64 array (5 values)	Weighting function coefficients used to compute along scan MTFC for band 3 Valid format: NN.NNNNN, where NN.NNNNN = TBS	No	Yes	LPSO
Group: MTF_Compensation	B3_weights_across	Dynamic	float64 array (5 values)	Weighting function coefficients used to compute across scan MTFC for band 3 Valid format: NN.NNNNN, where NN.NNNNN = TBS	No	Yes	LPSO
Group: MTF_Compensation	B4_weights_along	Dynamic	float64 array (5 values)	Weighting function coefficients used to compute along scan MTFC for band 4 Valid format: NN.NNNNN, where NN.NNNNN = TBS	No	Yes	LPSO
Group: MTF_Compensation	B4_weights_across	Dynamic	float64 array (5 values)	Weighting function coefficients used to compute across scan MTFC for band 4 Valid format: NN.NNNNN, where NN.NNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: MTF_Compensation	B5_weights_along	Dynamic	float64 array (5 values)	Weighting function coefficients used to compute along scan MTFC for band 5 Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	LPSO
Group: MTF_Compensation	B5_weights_across	Dynamic	float64 array (5 values)	Weighting function coefficients used to compute across scan MTFC for band 5 Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	LPSO
Group: MTF_Compensation	B6_weights_along	Dynamic	float64 array (5 values)	Weighting function coefficients used to compute along scan MTFC for band 6 Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	LPSO
Group: MTF_Compensation	B6_weights_across	Dynamic	float64 array (5 values)	Weighting function coefficients used to compute across scan MTFC for band 6 Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	LPSO
Group: MTF_Compensation	B7_weights_along	Dynamic	float64 array (5 values)	Weighting function coefficients used to compute along scan MTFC for band 7 Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	LPSO
Group: MTF_Compensation	B7_weights_across	Dynamic	float64 array (5 values)	Weighting function coefficients used to compute across scan MTFC for band 7 Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	LPSO
Group: MTF_Compensation	B8_weights_along	Dynamic	float64 array (5 values)	Weighting function coefficients used to compute along scan MTFC for band 8 Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	LPSO
Group: MTF_Compensation	B8_weights_across	Dynamic	float64 array (5 values)	Weighting function coefficients used to compute across scan MTFC for band 8 Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	LPSO
Group: Memory_Effect GROUP: ME_Magnitudes	B1_ME_Magnitude	Dynamic	float32 array (16 values)	Band 1 memory effect magnitude measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Memory_Effect GROUP: ME_Magnitudes	B2_ME_Magnitude	Dynamic	float32 array (16 values)	Band 2 memory effect magnitude measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Memory_Effect GROUP: ME_Magnitudes	B3_ME_Magnitude	Dynamic	float32 array (16 values)	Band 3 memory effect magnitude measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Memory_Effect GROUP: ME_Magnitudes	B4_ME_Magnitude	Dynamic	float32 array (16 values)	Band 3 memory effect magnitude measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Memory_Effect GROUP: ME_Magnitudes	B5_ME_Magnitude	Dynamic	float32 array (16 values)	Band 3 memory effect magnitude measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Memory_Effect GROUP: ME_Magnitudes	B6_ME_Magnitude	Dynamic	float32 array (8 values)	Band 3 memory effect magnitude measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Memory_Effect GROUP: ME_Magnitudes	B7_ME_Magnitude	Dynamic	float32 array (16 values)	Band 3 memory effect magnitude measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Memory_Effect GROUP: ME_Magnitudes	B8_ME_Magnitude	Dynamic	float32 array (32 values)	Band 3 memory effect magnitude measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Memory_Effect GROUP: ME_Time_Constants	B1_ME_Time_Constant	Dynamic	float32 array (16 values)	Band 1 time constant measured in minor frames Valid format: NNNN.NNNNNNNN, where NNNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Memory_Effect GROUP: ME_Time_Constants	B2_ME_Time_Constant	Dynamic	float32 array (16 values)	Band 2 time constant measured in minor frames Valid format: NNNN.NNNNNNNN, where NNNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Memory_Effect GROUP: ME_Time_Constants	B3_ME_Time_Constant	Dynamic	float32 array (16 values)	Band 3 time constant measured in minor frames Valid format: NNNN.NNNNNNNN, where NNNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Memory_Effect GROUP: ME_Time_Constants	B4_ME_Time_Constant	Dynamic	float32 array (16 values)	Band 4 time constant measured in minor frames Valid format: NNNN.NNNNNNNN, where NNNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Memory_Effect GROUP: ME_Time_Constants	B5_ME_Time_Constant	Dynamic	float32 array (16 values)	Band 5 time constant measured in minor frames Valid format: NNNN.NNNNNNNN, where NNNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Memory_Effect GROUP: ME_Time_Constants	B6_ME_Time_Constant	Dynamic	float32 array (8 values)	Band 6 time constant measured in minor frames Valid format: NNNN.NNNNNNNN, where NNNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Memory_Effect GROUP: ME_Time_Constants	B7_ME_Time_Constant	Dynamic	float32 array (16 values)	Band 7 time constant measured in minor frames Valid format: NNNN.NNNNNNNN, where NNNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Memory_Effect GROUP: ME_Time_Constants	B8_ME_Time_Constant	Dynamic	float32 array (32 values)	Band 8 time constant measured in minor frames Valid format: NNNN.NNNNNNNN, where NNNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Ghost_Pulse	Ghost_Pulse_Endpoints	Dynamic	float32 array (2 values)	Beginning and ending fractional minor frames that bound IC ghost pulse Valid format: NNNN.NNNN, where NNNN.NNNN = TBS	No	Yes	LPSO
Group: Scan_Correlated_Shift	SCS_Reference_Detectors	Dynamic	uint8 array (8 values)	Scan correlated shift reference detector, one per band Valid format: NN, where NN = TBS	No	Yes	LPSO
Group: Scan_Correlated_Shift GROUP: SCS_Low	B1L_SCS_Magnitudes	Dynamic	float32 array (16 values)	Magnitude of band 1 low-gain shift in digital numbers Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Scan_Correlated_Shift GROUP: SCS_Low	B2L_SCS_Magnitudes	Dynamic	float32 array (16 values)	Magnitude of band 2 low-gain shift in digital numbers Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Scan_Correlated_Shift GROUP: SCS_Low	B3L_SCS_Magnitudes	Dynamic	float32 array (16 values)	Magnitude of band 3 low-gain shift in digital numbers Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Scan_Correlated_Shift GROUP: SCS_Low	B4L_SCS_Magnitudes	Dynamic	float32 array (16 values)	Magnitude of band 4 low-gain shift in digital numbers Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Scan_Correlated_Shift GROUP: SCS_Low	B5L_SCS_Magnitudes	Dynamic	float32 array (16 values)	Magnitude of band 5 low-gain shift in digital numbers Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Scan_Correlated_Shift GROUP: SCS_Low	B7L_SCS_Magnitudes	Dynamic	float32 array (16 values)	Magnitude of band 7 low-gain shift in digital numbers Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Scan_Correlated_Shift GROUP: SCS_Low	B8L_SCS_Magnitudes	Dynamic	float32 array (16 values)	Magnitude of band 8 low-gain shift in digital numbers Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPS
Group: Scan_Correlated_Shift GROUP: SCS_High	B1H_SCS_Magnitudes	Dynamic	float32 array (16 values)	Magnitude of band 1 high-gain shift in digital numbers Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Scan_Correlated_Shift GROUP: SCS_High	B2H_SCS_Magnitudes	Dynamic	float32 array (16 values)	Magnitude of band 2 high-gain shift in digital numbers Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Scan_Correlated_Shift GROUP: SCS_High	B3H_SCS_Magnitudes	Dynamic	float32 array (16 values)	Magnitude of band 3 high-gain shift in digital numbers Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Scan_Correlated_Shift GROUP: SCS_High	B4H_SCS_Magnitudes	Dynamic	float32 array (16 values)	Magnitude of band 4 high-gain shift in digital numbers Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Scan_Correlated_Shift GROUP: SCS_High	B5H_SCS_Magnitudes	Dynamic	float32 array (16 values)	Magnitude of band 5 high-gain shift in digital numbers Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Scan_Correlated_Shift GROUP: SCS_High	B7H_SCS_Magnitudes	Dynamic	float32 array (16 values)	Magnitude of band 7 high-gain shift in digital numbers Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Scan_Correlated_Shift GROUP: SCS_High	B8H_SCS_Magnitudes	Dynamic	float32 array (16 values)	Magnitude of band 8 high-gain shift in digital numbers Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Striping GROUP: Striping_Flag_Low	Correction_Reference_B1_Low	static	uint8	Striping correction methodology flag, relative to band average or reference detector, band 1, low gain Valid format: N, where N = 0 (band average) or 1 (reference detector)	Yes	Yes	Postlaunch

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Striping GROUP: Striping_Flag_Low	Correction_Reference_B2_Low	static	uint8	Striping correction methodology flag, relative to band average or reference detector, band 2, low gain Valid format: N, where N = 0 (band average) or 1 (reference detector)	Yes	Yes	Postlaunch
Group: Striping GROUP: Striping_Flag_Low	Correction_Reference_B3_Low	static	uint8	Striping correction methodology flag, relative to band average or reference detector, band 3, low gain Valid format: N, where N = 0 (band average) or 1 (reference detector)	Yes	Yes	Postlaunch
Group: Striping GROUP: Striping_Flag_Low	Correction_Reference_B4_Low	static	uint8	Striping correction methodology flag, relative to band average or reference detector, band 4, low gain Valid format: N, where N = 0 (band average) or 1 (reference detector)	Yes	Yes	Postlaunch
Group: Striping GROUP: Striping_Flag_Low	Correction_Reference_B5_Low	static	uint8	Striping correction methodology flag, relative to band average or reference detector, band 5, low gain Valid format: N, where N = 0 (band average) or 1 (reference detector)	Yes	Yes	Postlaunch
Group: Striping GROUP: Striping_Flag_Low	Correction_Reference_B6_Low	static	uint8	Striping correction methodology flag, relative to band average or reference detector, band 6, low gain Valid format: N, where N = 0 (band average) or 1 (reference detector)	Yes	Yes	Postlaunch
Group: Striping GROUP: Striping_Flag_Low	Correction_Reference_B7_Low	static	uint8	Striping correction methodology flag, relative to band average or reference detector, band 7 , low gain Valid format: N, where N = 0 (band average) or 1 (reference detector)	Yes	Yes	Postlaunch
Group: Striping GROUP: Striping_Flag_Low	Correction_Reference_B8_Low	static	uint8	Striping correction methodology flag, relative to band average or reference detector, band 8, low gain Valid format: N, where N = 0 (band average) or 1 (reference detector)	Yes	Yes	Postlaunch
Group: Striping GROUP: Striping_Flag_High	Correction_Reference_B1_High	static	uint8	Striping correction methodology flag, relative to band average or reference detector, band 1, high gain Valid format: N, where N = 0 (band average) or 1 (reference detector)	Yes	Yes	Postlaunch
Group: Striping GROUP: Striping_Flag_High	Correction_Reference_B2_High	static	uint8	Striping correction methodology flag, relative to band average or reference detector, band 2, high gain Valid format: N, where N = 0 (band average) or 1 (reference detector)	Yes	Yes	Postlaunch

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Striping GROUP: Striping_Flag_High	Correction_Reference_B3_High	static	uint8	Striping correction methodology flag, relative to band average or reference detector, band 3, high gain Valid format: N, where N = 0 (band average) or 1 (reference detector)	Yes	Yes	Postlaunch
Group: Striping GROUP: Striping_Flag_High	Correction_Reference_B4_High	static	uint8	Striping correction methodology flag, relative to band average or reference detector, band 4, high gain Valid format: N, where N = 0 (band average) or 1 (reference detector)	Yes	Yes	Postlaunch
Group: Striping GROUP: Striping_Flag_High	Correction_Reference_B5_High	static	uint8	Striping correction methodology flag, relative to band average or reference detector, band 5, high gain Valid format: N, where N = 0 (band average) or 1 (reference detector)	Yes	Yes	Postlaunch
Group: Striping GROUP: Striping_Flag_High	Correction_Reference_B6_High	static	uint8	Striping correction methodology flag, relative to band average or reference detector, band 6, high gain Valid format: N, where N = 0 (band average) or 1 (reference detector)	Yes	Yes	Postlaunch
Group: Striping GROUP: Striping_Flag_High	Correction_Reference_B7_High	static	uint8	Striping correction methodology flag, relative to band average or reference detector, band 7, high gain Valid format: N, where N = 0 (band average) or 1 (reference detector)	Yes	Yes	Postlaunch
Group: Striping GROUP: Striping_Flag_High	Correction_Reference_B8_High	static	uint8	Striping correction methodology flag, relative to band average or reference detector, band 8, high gain Valid format: N, where N = 0 (band average) or 1 (reference detector)	Yes	Yes	Postlaunch
Group: Histogram GROUP: Detector_Noise GROUP: Detector_Noise_Low	Detector_Noise_Level_B1_Low	Dynamic	float32 array (16 values)	Standard deviation of shutter region data for each detector of band 1, low gain Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	IAS
Group: Histogram GROUP: Detector_Noise GROUP: Detector_Noise_Low	Detector_Noise_Level_B2_Low	Dynamic	float32 array (16 values)	Standard deviation of shutter region data for each detector of band 2, low gain Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	IAS
Group: Histogram GROUP: Detector_Noise GROUP: Detector_Noise_Low	Detector_Noise_Level_B3_Low	Dynamic	float32 array (16 values)	Standard deviation of shutter region data for each detector of band 3, low gain Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	IAS
Group: Histogram GROUP: Detector_Noise GROUP: Detector_Noise_Low	Detector_Noise_Level_B4_Low	Dynamic	float32 array (16 values)	Standard deviation of shutter region data for each detector of band 4, low gain Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	IAS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Histogram GROUP: Detector_Noise GROUP: Detector_Noise_Low	Detector_Noise_Level_B5_Low	Dynamic	float32 array (16 values)	Standard deviation of shutter region data for each detector of band 5, low gain Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	IAS
Group: Histogram GROUP: Detector_Noise GROUP: Detector_Noise_Low	Detector_Noise_Level_B6_Low	Dynamic	float32 array (8 values)	Standard deviation of shutter region data for each detector of band 6, high gain Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	IAS
Group: Histogram GROUP: Detector_Noise GROUP: Detector_Noise_Low	Detector_Noise_Level_B7_Low	Dynamic	float32 array (16 values)	Standard deviation of shutter region data for each detector of band 7, high gain Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	IAS
Group: Histogram GROUP: Detector_Noise GROUP: Detector_Noise_Low	Detector_Noise_Level_B8_Low	Dynamic	float32 array (32 values)	Standard deviation of shutter region data for each detector of band 8, high gain Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	IAS
Group: Histogram GROUP: Detector_Noise GROUP: Detector_Noise_High	Detector_Noise_Level_B1_high	Dynamic	float32 array (16 values)	Standard deviation of shutter region data for each detector of band 1, high gain Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	IAS
Group: Histogram GROUP: Detector_Noise GROUP: Detector_Noise_High	Detector_Noise_Level_B2_high	Dynamic	float32 array (16 values)	Standard deviation of shutter region data for each detector of band 2, high gain Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	IAS
Group: Histogram GROUP: Detector_Noise GROUP: Detector_Noise_High	Detector_Noise_Level_B3_high	Dynamic	float32 array (16 values)	Standard deviation of shutter region data for each detector of band 3, high gain Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	IAS
Group: Histogram GROUP: Detector_Noise GROUP: Detector_Noise_High	Detector_Noise_Level_B4_high	Dynamic	float32 array (16 values)	Standard deviation of shutter region data for each detector of band 4, high gain Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	IAS
Group: Histogram GROUP: Detector_Noise GROUP: Detector_Noise_High	Detector_Noise_Level_B5_high	Dynamic	float32 array (16 values)	Standard deviation of shutter region data for each detector of band 5, high gain Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	IAS
Group: Histogram GROUP: Detector_Noise GROUP: Detector_Noise_High	Detector_Noise_Level_B6_high	Dynamic	float32 array (8 values)	Standard deviation of shutter region data for each detector of band 6, high gain Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	IAS
Group: Histogram GROUP: Detector_Noise GROUP: Detector_Noise_High	Detector_Noise_Level_B7_high	Dynamic	float32 array (16 values)	Standard deviation of shutter region data for each detector of band 7, high gain Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	IAS
Group: Histogram GROUP: Detector_Noise GROUP: Detector_Noise_High	Detector_Noise_Level_B8_high	Dynamic	float32 array (32 values)	Standard deviation of shutter region data for each detector of band 8, high gain Valid format: NN.NNNN, where NN.NNNN = TBS	No	Yes	IAS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Histogram GROUP: Reference_Detectors	Reference_Detector_B1	Dynamic	uint8	Detector used as a reference when computing relative detector gains and biases (least noisy), band 1 Valid format: NN, where NN = TBS	Yes	Yes	IAS
Group: Histogram GROUP: Reference_Detectors	Reference_Detector_B2	Dynamic	uint8	Detector used as a reference when computing relative detector gains and biases (least noisy), band 2 Valid format: NN, where NN = TBS	Yes	Yes	IAS
Group: Histogram GROUP: Reference_Detectors	Reference_Detector_B3	Dynamic	uint8	Detector used as a reference when computing relative detector gains and biases (least noisy), band 3 Valid format: NN, where NN = TBS	Yes	Yes	IAS
Group: Histogram GROUP: Reference_Detectors	Reference_Detector_B4	Dynamic	uint8	Detector used as a reference when computing relative detector gains and biases (least noisy), band 4 Valid format: NN, where NN = TBS	Yes	Yes	IAS
Group: Histogram GROUP: Reference_Detectors	Reference_Detector_B5	Dynamic	uint8	Detector used as a reference when computing relative detector gains and biases (least noisy), band 5 Valid format: NN, where NN = TBS	Yes	Yes	IAS
Group: Histogram GROUP: Reference_Detectors	Reference_Detector_B6	Dynamic	uint8	Detector used as a reference when computing relative detector gains and biases (least noisy), band 6 Valid format: NN, where NN = TBS	Yes	Yes	IAS
Group: Histogram GROUP: Reference_Detectors	Reference_Detector_B7	Dynamic	uint8	Detector used as a reference when computing relative detector gains and biases (least noisy), band 7 Valid format: NN, where NN = TBS	Yes	Yes	IAS
Group: Histogram GROUP: Reference_Detectors	Reference_Detector_B8	Dynamic	uint8	Detector used as a reference when computing relative detector gains and biases (least noisy), band 8 Valid format: NN, where NN = TBS	Yes	Yes	IAS
Group: Histogram GROUP: Saturation_Thresholds	Saturation_Bin_Threshold_B1	Dynamic	uint16	Number of pixels that a bin must have to be tested as a saturation bin, band 1 Valid format: NNNNN, where NNNNN = TBS	No	Yes	IAS
Group: Histogram GROUP: Saturation_Thresholds	Saturation_Bin_Threshold_B2	Dynamic	uint16	Number of pixels that a bin must have to be tested as a saturation bin, band 2 Valid format: NNNNN, where NNNNN = TBS	No	Yes	IAS
Group: Histogram GROUP: Saturation_Thresholds	Saturation_Bin_Threshold_B3	Dynamic	uint16	Number of pixels that a bin must have to be tested as a saturation bin, band 3 Valid format: NNNNN, where NNNNN = TBS	No	Yes	IAS
Group: Histogram GROUP: Saturation_Thresholds	Saturation_Bin_Threshold_B4	Dynamic	uint16	Number of pixels that a bin must have to be tested as a saturation bin, band 4 Valid format: NNNNN, where NNNNN = TBS	No	Yes	IAS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Histogram GROUP: Saturation_Thresholds	Saturation_Bin_Threshold_B5	Dynamic	uint16	Number of pixels that a bin must have to be tested as a saturation bin, band 5 Valid format: NNNNN, where NNNNN = TBS	No	Yes	IAS
Group: Histogram GROUP: Saturation_Thresholds	Saturation_Bin_Threshold_B6	Dynamic	uint16	Number of pixels that a bin must have to be tested as a saturation bin, band 6 Valid format: NNNNN, where NNNNN = TBS	No	Yes	IAS
Group: Histogram GROUP: Saturation_Thresholds	Saturation_Bin_Threshold_B7	Dynamic	uint16	Number of pixels that a bin must have to be tested as a saturation bin, band 7 Valid format: NNNNN, where NNNNN = TBS	No	Yes	IAS
Group: Histogram GROUP: Saturation_Thresholds	Saturation_Bin_Threshold_B8	Dynamic	uint16	Number of pixels that a bin must have to be tested as a saturation bin, band 8 Valid format: NN, where NNNN = TBS	No	Yes	IAS
Group: Histogram GROUP: Adjacent_Bins	Adjacent_Bin_Number_B1	Dynamic	uint8	Bins adjacent to possible saturation bin that must have fewer pixels than "adjacent bin threshold" to declare possible bin as saturation bin, band 1 Valid format: N, where N = 2(default)	No	Yes	IAS
Group: Histogram GROUP: Adjacent_Bins GROUP: Bin_Number	Adjacent_Bin_Number_B2	Dynamic	uint8	Bins adjacent to possible saturation bin that must have fewer pixels than "adjacent bin threshold" to declare possible bin as saturation bin, band 2 Valid format: N, where N = 2(default)	No	Yes	IAS
Group: Histogram GROUP: Adjacent_Bins GROUP: Bin_Number	Adjacent_Bin_Number_B3	Dynamic	uint8	Bins adjacent to possible saturation bin that must have fewer pixels than "adjacent bin threshold" to declare possible bin as saturation bin, band 3 Valid format: N, where N = 2(default)	No	Yes	IAS
Group: Histogram GROUP: Adjacent_Bins GROUP: Bin_Number	Adjacent_Bin_Number_B4	Dynamic	uint8	Bins adjacent to possible saturation bin that must have fewer pixels than "adjacent bin threshold" to declare possible bin as saturation bin, band 4 Valid format: N, where N = 2(default)	No	Yes	IAS
Group: Histogram GROUP: Adjacent_Bins GROUP: Bin_Number	Adjacent_Bin_Number_B5	Dynamic	uint8	Bins adjacent to possible saturation bin that must have fewer pixels than "adjacent bin threshold" to declare possible bin as saturation bin, band 5 Valid format: N, where N = 2(default)	No	Yes	IAS
Group: Histogram GROUP: Adjacent_Bins GROUP: Bin_Number	Adjacent_Bin_Number_B6	Dynamic	uint8	Bins adjacent to possible saturation bin that must have fewer pixels than "adjacent bin threshold" to declare possible bin as saturation bin, band 6 Valid format: N, where N = 2(default)	No	Yes	IAS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Histogram GROUP: Adjacent_Bins GROUP: Bin_Number	Adjacent_Bin_Number_B7	Dynamic	uint8	Bins adjacent to possible saturation bin that must have fewer pixels than "adjacent bin threshold" to declare possible bin as saturation bin, band 7 Valid format: N, where N = 2(default)	No	Yes	IAS
Group: Histogram GROUP: Adjacent_Bins GROUP: Bin_Number	Adjacent_Bin_Number_B8	Dynamic	uint8	Bins adjacent to possible saturation bin that must have fewer pixels than "adjacent bin threshold" to declare possible bin as saturation bin, band 8 Valid format: N, where N = 2(default)	No	Yes	IAS
Group: Histogram GROUP: Adjacent_Bins GROUP: Bin_Threshold	Adjacent_Bin_Threshold_B1	Dynamic	uint8	Number of adjacent bin pixels that cannot be exceeded for band 1 candidate saturation bin to be valid saturation bin Valid format: NN, where NN = 10 (default)	No	Yes	IAS
Group: Histogram GROUP: Adjacent_Bins GROUP: Bin_Threshold	Adjacent_Bin_Threshold_B2	Dynamic	uint8	Number of adjacent bin pixels that cannot be exceeded for band 2 candidate saturation bin to be valid saturation bin Valid format: NN, where NN = 10 (default)	No	Yes	IAS
Group: Histogram GROUP: Adjacent_Bins GROUP: Bin_Threshold	Adjacent_Bin_Threshold_B3	Dynamic	uint8	Number of adjacent bin pixels that cannot be exceeded for band 3 candidate saturation bin to be valid saturation bin Valid format: NN, where NN = 10 (default)	No	Yes	IAS
Group: Histogram GROUP: Adjacent_Bins GROUP: Bin_Threshold	Adjacent_Bin_Threshold_B4	Dynamic	uint8	Number of adjacent bin pixels that cannot be exceeded for band 4 candidate saturation bin to be valid saturation bin Valid format: NN, where NN = 10 (default)	No	Yes	IAS
Group: Histogram GROUP: Adjacent_Bins GROUP: Bin_Threshold	Adjacent_Bin_Threshold_B5	Dynamic	uint8	Number of adjacent bin pixels that cannot be exceeded for band 5 candidate saturation bin to be valid saturation bin Valid format: NN, where NN = 10 (default)	No	Yes	IAS
Group: Histogram GROUP: Adjacent_Bins GROUP: Bin_Threshold	Adjacent_Bin_Threshold_B6	Dynamic	uint8	Number of adjacent bin pixels that cannot be exceeded for band 6 candidate saturation bin to be valid saturation bin Valid format: NN, where NN = 10 (default)	No	Yes	IAS
Group: Histogram GROUP: Adjacent_Bins GROUP: Bin_Threshold	Adjacent_Bin_Threshold_B7	Dynamic	uint8	Number of adjacent bin pixels that cannot be exceeded for band 7 candidate saturation bin to be valid saturation bin Valid format: NN, where NN = 10 (default)	No	Yes	IAS
Group: Histogram GROUP: Adjacent_Bins GROUP: Bin_Threshold	Adjacent_Bin_Threshold_B8	Dynamic	uint8	Number of adjacent bin pixels that cannot be exceeded for band 8 candidate saturation bin to be valid saturation bin Valid format: NN, where NN = 10 (default)	No	Yes	IAS
Group: Histogram GROUP: Starting_Pixel	Start_pixel_B1	Dynamic	uint8	Leftmost pixel in window to be tested, band 1 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Histogram GROUP: Starting_Pixel	Start_pixel_B2	Dynamic	uint8	Leftmost pixel in window to be tested, band 2 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Starting_Pixel	Start_pixel_B3	Dynamic	uint8	Leftmost pixel in window to be tested, band 3 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Starting_Pixel	Start_pixel_B4	Dynamic	uint8	Leftmost pixel in window to be tested, band 4 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Starting_Pixel	Start_pixel_B5	Dynamic	uint8	Leftmost pixel in window to be tested, band 5 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Starting_Pixel	Start_pixel_B6	Dynamic	uint8	Leftmost pixel in window to be tested, band 6 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Starting_Pixel	Start_pixel_B7	Dynamic	uint8	Leftmost pixel in window to be tested, band 7 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Starting_Pixel	Start_pixel_B8	Dynamic	uint8	Leftmost pixel in window to be tested, band 8 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Window_Width	Window_Samples_B1	Dynamic	uint8	Width of window, in pixels, to be tested, band 1 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Window_Width	Window_Samples_B2	Dynamic	uint8	Width of window, in pixels, to be tested, band 2 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Window_Width	Window_Samples_B3	Dynamic	uint8	Width of window, in pixels, to be tested, band 3 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Window_Width	Window_Samples_B4	Dynamic	uint8	Width of window, in pixels, to be tested, band 4 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Window_Width	Window_Samples_B5	Dynamic	uint8	Width of window, in pixels, to be tested, band 5 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Window_Width	Window_Samples_B6	Dynamic	uint8	Width of window, in pixels, to be tested, band 6 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Window_Width	Window_Samples_B7	Dynamic	uint8	Width of window, in pixels, to be tested, band 7 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Window_Width	Window_Samples_B8	Dynamic	uint8	Width of window, in pixels, to be tested, band 8 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Histogram GROUP: Window_Length	Window_Scans_B1	Dynamic	uint8	Number of scans in window to be tested, band 1 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Window_Length	Window_Scans_B2	Dynamic	uint8	Number of scans in window to be tested, band 2 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Window_Length	Window_Scans_B3	Dynamic	uint8	Number of scans in window to be tested, band 3 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Window_Length	Window_Scans_B4	Dynamic	uint8	Number of scans in window to be tested, band 4 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Window_Length	Window_Scans_B5	Dynamic	uint8	Number of scans in window to be tested, band 5 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Window_Length	Window_Scans_B6	Dynamic	uint8	Number of scans in window to be tested, band 6 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Window_Length	Window_Scans_B7	Dynamic	uint8	Number of scans in window to be tested, band 7 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Window_Length	Window_Scans_B8	Dynamic	uint8	Number of scans in window to be tested, band 8 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Overlapping_Scans	Overlap_Scans_B1	Dynamic	uint8	Number of overlapping scans between windows to be tested, band 1 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Overlapping_Scans	Overlap_Scans_B2	Dynamic	uint8	Number of overlapping scans between windows to be tested, band 2 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Overlapping_Scans	Overlap_Scans_B3	Dynamic	uint8	Number of overlapping scans between windows to be tested, band 3 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Overlapping_Scans	Overlap_Scans_B4	Dynamic	uint8	Number of overlapping scans between windows to be tested, band 4 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Overlapping_Scans	Overlap_Scans_B5	Dynamic	uint8	Number of overlapping scans between windows to be tested, band 5 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Overlapping_Scans	Overlap_Scans_B6	Dynamic	uint8	Number of overlapping scans between windows to be tested, band 6 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Histogram GROUP: Overlapping_Scans	Overlap_Scans_B7	Dynamic	uint8	Number of overlapping scans between windows to be tested, band 7 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Histogram GROUP: Overlapping_Scans	Overlap_Scans_B8	Dynamic	uint8	Number of overlapping scans between windows to be tested, band 8 Valid format: NNN, where NNN = (TBS)	No	Yes	IAS
Group: Impulse_Noise	Median_Filter_Width	Static	uint8	Width of median filter Valid format: N, where N = 2	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Standard_Deviation	B1L__Standard_Deviation	Dynamic	float32 array (16 values)	Band 1 low-gain random noise standard deviation Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Standard_Deviation	B2L__Standard_Deviation	Dynamic	float32 array (16 values)	Band 2 low-gain random noise standard deviation Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Standard_Deviation	B3L__Standard_Deviation	Dynamic	float32 array (16 values)	Band 3 low-gain random noise standard deviation Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Standard_Deviation	B4L__Standard_Deviation	Dynamic	float32 array (16 values)	Band 4 low-gain random noise standard deviation Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Standard_Deviation	B5L__Standard_Deviation	Dynamic	float32 array (16 values)	Band 5 low-gain random noise standard deviation Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Standard_Deviation	B6L__Standard_Deviation	Dynamic	float32 array (8 values)	Band 6 low-gain random noise standard deviation Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Standard_Deviation	B7L__Standard_Deviation	Dynamic	float32 array (16 values)	Band 7 low-gain random noise standard deviation Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Standard_Deviation	B8L__Standard_Deviation	Dynamic	float32 array (32 values)	Band 8 low-gain random noise standard deviation Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Standard_Deviation	B1H__Standard_Deviation	Dynamic	float32 array (16 values)	Band 1 high-gain random noise standard deviation Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Standard_Deviation	B2H__Standard_Deviation	Dynamic	float32 array (16 values)	Band 2 high-gain random noise standard deviation Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Standard_Deviation	B3H__Standard_Deviation	Dynamic	float32 array (16 values)	Band 3 high-gain random noise standard deviation Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Standard_Deviation	B4H__Standard_Deviation	Dynamic	float32 array (16 values)	Band 4 high-gain random noise standard deviation Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Impulse_Noise GROUP: IN_Standard_Deviation	B5H__Standard_Deviation	Dynamic	float32 array (16 values)	Band 5 high-gain random noise standard deviation Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Standard_Deviation	B6H__Standard_Deviation	Dynamic	float32 array (8 values)	Band 6 high-gain random noise standard deviation Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Standard_Deviation	B7H__Standard_Deviation	Dynamic	float32 array (16 values)	Band 7 high-gain random noise standard deviation Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Standard_Deviation	B8H__Standard_Deviation	Dynamic	float32 array (32 values)	Band 8 high-gain random noise standard deviation Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Threshold	B1L__Threshold	Dynamic	float32 array (16 values)	Band 1 low-gain noise threshold Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Threshold	B2L__Threshold	Dynamic	float32 array (16 values)	Band 2 low-gain noise threshold Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Threshold	B3L__Threshold	Dynamic	float32 array (16 values)	Band 3 low-gain noise threshold Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Threshold	B4L__Threshold	Dynamic	float32 array (16 values)	Band 4 low-gain noise threshold Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Threshold	B5L__Threshold	Dynamic	float32 array (16 values)	Band 5 low-gain noise threshold Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Threshold	B6L__Threshold	Dynamic	float32 array (8 values)	Band 6 low-gain noise threshold Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Threshold	B7L__Threshold	Dynamic	float32 array (16 values)	Band 7 low-gain noise threshold Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Threshold	B8L__Threshold	Dynamic	float32 array (32 values)	Band 8 low-gain noise threshold Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Threshold	B1H__Threshold	Dynamic	float32 array (16 values)	Band 1 high-gain noise threshold Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Threshold	B2H__Threshold	Dynamic	float32 array (16 values)	Band 2 high-gain noise threshold Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Threshold	B3H__Threshold	Dynamic	float32 array (16 values)	Band 3 high-gain noise threshold Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Threshold	B4H__Threshold	Dynamic	float32 array (16 values)	Band 4 high-gain noise threshold Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Threshold	B5H__Threshold	Dynamic	float32 array (16 values)	Band 5 high-gain noise threshold Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Threshold	B6H__Threshold	Dynamic	float32 array (8 values)	Band 6 high-gain noise threshold Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Impulse_Noise GROUP: IN_Threshold	B7H__Threshold	Dynamic	float32 array (16 values)	Band 7 high-gain noise threshold Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Impulse_Noise GROUP: IN_Threshold	B8H__Threshold	Dynamic	float32 array (32 values)	Band 8 high-gain noise threshold Valid format: NN.NNNNNNNN, where NN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise	Frequency_Components	Dynamic	uint8	Number of frequency components derived during waveform analysis for coherent noise correction Valid format: NN, where NN = 10	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Means	B1_Frequency_Mean	Dynamic	float32 array (10 values)	Band 1 frequency means measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Means	B2_Frequency_Mean	Dynamic	float32 array (10 values)	Band 2 frequency means measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Means	B3_Frequency_Mean	Dynamic	float32 array (10 values)	Band 3 frequency means measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Means	B4_Frequency_Mean	Dynamic	float32 array (10 values)	Band 4 frequency means measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Means	B5_Frequency_Mean	Dynamic	float32 array (10 values)	Band 5 frequency means measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Means	B6_Frequency_Mean	Dynamic	float32 array (10 values)	Band 6 frequency means measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Means	B7_Frequency_Mean	Dynamic	float32 array (10 values)	Band 7 frequency means measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Means	B8_Frequency_Mean	Dynamic	float32 array (10 values)	Band 8 frequency means measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Sigmas	B1_Frequency_Sigma	Dynamic	float32 array (10 values)	Band 1 frequency sigmas measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Sigmas	B2_Frequency_Sigma	Dynamic	float32 array (10 values)	Band 2 frequency sigmas measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Sigmas	B3_Frequency_Sigma	Dynamic	float32 array (10 values)	Band 3 frequency sigmas measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Sigmas	B4_Frequency_Sigma	Dynamic	float32 array (10 values)	Band 4 frequency sigmas measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Sigmas	B5_Frequency_Sigma	Dynamic	float32 array (10 values)	Band 5 frequency sigmas measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Sigmas	B6_Frequency_Sigma	Dynamic	float32 array (10 values)	Band 6 frequency sigmas measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Sigmas	B7_Frequency_Sigma	Dynamic	float32 array (10 values)	Band 7 frequency sigmas measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Sigmas	B8_Frequency_Sigma	Dynamic	float32 array (10 values)	Band 8 frequency sigmas measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Minimums	B1_Frequency_Min	Dynamic	float32 array (10 values)	Band 1 frequency minimums measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Minimums	B2_Frequency_Min	Dynamic	float32 array (10 values)	Band 2 frequency minimums measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Minimums	B3_Frequency_Min	Dynamic	float32 array (10 values)	Band 3 frequency minimums measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Minimums	B4_Frequency_Min	Dynamic	float32 array (10 values)	Band 4 frequency minimums measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Minimums	B5_Frequency_Min	Dynamic	float32 array (10 values)	Band 5 frequency minimums measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Minimums	B6_Frequency_Min	Dynamic	float32 array (10 values)	Band 6 frequency minimums measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Minimums	B7_Frequency_Min	Dynamic	float32 array (10 values)	Band 7 frequency minimums measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Minimums	B8_Frequency_Min	Dynamic	float32 array (10 values)	Band 8 frequency minimums measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Maximums	B1_Frequency_Max	Dynamic	float32 array (10 values)	Band 1 frequency maximums measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Maximums	B2_Frequency_Max	Dynamic	float32 array (10 values)	Band 2 frequency maximums measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Maximums	B3_Frequency_Max	Dynamic	float32 array (10 values)	Band 3 frequency maximums measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Maximums	B4_Frequency_Max	Dynamic	float32 array (10 values)	Band 4 frequency maximums measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Maximums	B5_Frequency_Max	Dynamic	float32 array (10 values)	Band 5 frequency maximums measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Maximums	B6_Frequency_Max	Dynamic	float32 array (10 values)	Band 6 frequency maximums measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Maximums	B7_Frequency_Max	Dynamic	float32 array (10 values)	Band 7 frequency maximums measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Frequency_Parameters GROUP: Frequency_Maximums	B8_Frequency_Max	Dynamic	float32 array (10 values)	Band 8 frequency maximums measured in inverse minor frames Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Means	B1_Phase_Mean	Dynamic	float32 array (10 values)	Band 1 phase means measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Means	B2_Phase_Mean	Dynamic	float32 array (10 values)	Band 2 phase means measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Means	B3_Phase_Mean	Dynamic	float32 array (10 values)	Band 3 phase means measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Means	B4_Phase_Mean	Dynamic	float32 array (10 values)	Band 4 phase means measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Means	B5_Phase_Mean	Dynamic	float32 array (10 values)	Band 5 phase means measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Means	B6_Phase_Mean	Dynamic	float32 array (10 values)	Band 6 phase means measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Means	B7_Phase_Mean	Dynamic	float32 array (10 values)	Band 7 phase means measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Means	B8_Phase_Mean	Dynamic	float32 array (10 values)	Band 8 phase means measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Sigmas	B1_Phase_Sigma	Dynamic	float32 array (10 values)	Band 1 phase sigmas measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Sigmas	B2_Phase_Sigma	Dynamic	float32 array (10 values)	Band 2 phase sigmas measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Sigmas	B3_Phase_Sigma	Dynamic	float32 array (10 values)	Band 3 phase sigmas measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Sigmas	B4_Phase_Sigma	Dynamic	float32 array (10 values)	Band 4 phase sigmas measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Sigmas	B5_Phase_Sigma	Dynamic	float32 array (10 values)	Band 5 phase sigmas measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Sigmas	B6_Phase_Sigma	Dynamic	float32 array (10 values)	Band 6 phase sigmas measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Sigmas	B7_Phase_Sigma	Dynamic	float32 array (10 values)	Band 7 phase sigmas measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Sigmas	B8_Phase_Sigma	Dynamic	float32 array (10 values)	Band 8 phase sigmas measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Minimums	B1_Phase_Min	Dynamic	float32 array (10 values)	Band 1 phase minimums measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Minimums	B2_Phase_Min	Dynamic	float32 array (10 values)	Band 2 phase minimums measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Minimums	B3_Phase_Min	Dynamic	float32 array (10 values)	Band 3 phase minimums measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Minimums	B4_Phase_Min	Dynamic	float32 array (10 values)	Band 4 phase minimums measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Minimums	B5_Phase_Min	Dynamic	float32 array (10 values)	Band 5 phase minimums measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Minimums	B6_Phase_Min	Dynamic	float32 array (10 values)	Band 6 phase minimums measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Minimums	B7_Phase_Min	Dynamic	float32 array (10 values)	Band 7 phase minimums measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Minimums	B8_Phase_Min	Dynamic	float32 array (10 values)	Band 8 phase minimums measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Maximums	B1_Phase_Max	Dynamic	float32 array (10 values)	Band 1 phase maximums measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Maximums	B2_Phase_Max	Dynamic	float32 array (10 values)	Band 2 phase maximums measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Maximums	B3_Phase_Max	Dynamic	float32 array (10 values)	Band 3 phase maximums measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Maximums	B4_Phase_Max	Dynamic	float32 array (10 values)	Band 4 phase maximums measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Maximums	B5_Phase_Max	Dynamic	float32 array (10 values)	Band 5 phase maximums measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Maximums	B6_Phase_Max	Dynamic	float32 array (10 values)	Band 6 phase maximums measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Maximums	B7_Phase_Max	Dynamic	float32 array (10 values)	Band 7 phase maximums measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Phase_Parameters GROUP: Phase_Maximums	B8_Phase_Max	Dynamic	float32 array (10 values)	Band 8 phase maximums measured in radians Valid format: NNNNNNNN, where NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Means	B1_Magnitude_Mean	Dynamic	float32 array (10 values)	Band 1 magnitudes means measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Means	B2_Magnitude_Mean	Dynamic	float32 array (10 values)	Band 2 magnitudes means measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Means	B3_Magnitude_Mean	Dynamic	float32 array (10 values)	Band 3 magnitudes means measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Means	B4_Magnitude_Mean	Dynamic	float32 array (10 values)	Band 4 magnitudes means measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Means	B5_Magnitude_Mean	Dynamic	float32 array (10 values)	Band 5 magnitudes means measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Means	B6_Magnitude_Mean	Dynamic	float32 array (10 values)	Band 6 magnitudes means measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Means	B7_Magnitude_Mean	Dynamic	float32 array (10 values)	Band 7 magnitudes means measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Means	B8_Magnitude_Mean	Dynamic	float32 array (10 values)	Band 8 magnitudes means measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Sigmas	B1_Magnitude_Sigma	Dynamic	float32 array (10 values)	Band 1 magnitudes sigmas measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Sigmas	B2_Magnitude_Sigma	Dynamic	float32 array (10 values)	Band 2 magnitudes sigmas measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Sigmas	B3_Magnitude_Sigma	Dynamic	float32 array (10 values)	Band 3 magnitudes sigmas measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Sigmas	B4_Magnitude_Sigma	Dynamic	float32 array (10 values)	Band 4 magnitudes sigmas measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Sigmas	B5_Magnitude_Sigma	Dynamic	float32 array (10 values)	Band 5 magnitudes sigmas measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Sigmas	B6_Magnitude_Sigma	Dynamic	float32 array (10 values)	Band 6 magnitudes sigmas measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Sigmas	B7_Magnitude_Sigma	Dynamic	float32 array (10 values)	Band 7 magnitudes sigmas measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Sigmas	B8_Magnitude_Sigma	Dynamic	float32 array (10 values)	Band 8 magnitudes sigmas measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Minimums	B1_Magnitude_Min	Dynamic	float32 array (10 values)	Band 1 magnitudes minimums measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Minimums	B2_Magnitude_Min	Dynamic	float32 array (10 values)	Band 2 magnitudes minimums measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Minimums	B3_Magnitude_Min	Dynamic	float32 array (10 values)	Band 3 magnitudes minimums measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Minimums	B4_Magnitude_Min	Dynamic	float32 array (10 values)	Band 4 magnitudes minimums measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Minimums	B5_Magnitude_Min	Dynamic	float32 array (10 values)	Band 5 magnitudes minimums measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Minimums	B6_Magnitude_Min	Dynamic	float32 array (10 values)	Band 6 magnitudes minimums measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Minimums	B7_Magnitude_Min	Dynamic	float32 array (10 values)	Band 7 magnitudes minimums measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Minimums	B8_Magnitude_Min	Dynamic	float32 array (10 values)	Band 8 magnitudes minimums measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Maximums	B1_Magnitude_Max	Dynamic	float32 array (10 values)	Band 1 magnitudes maximums measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Maximums	B2_Magnitude_Max	Dynamic	float32 array (10 values)	Band 2 magnitudes maximums measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Maximums	B3_Magnitude_Max	Dynamic	float32 array (10 values)	Band 3 magnitudes maximums measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Maximums	B4_Magnitude_Max	Dynamic	float32 array (10 values)	Band 4 magnitudes maximums measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Maximums	B5_Magnitude_Max	Dynamic	float32 array (10 values)	Band 5 magnitudes maximums measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Maximums	B6_Magnitude_Max	Dynamic	float32 array (10 values)	Band 6 magnitudes maximums measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Maximums	B7_Magnitude_Max	Dynamic	float32 array (10 values)	Band 7 magnitudes maximums measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Coherent_Noise GROUP: CN_Magnitude_Parameters GROUP: Magnitude_Maximums	B8_Magnitude_Max	Dynamic	float32 array (10 values)	Band 8 magnitudes maximums measured in DNs Valid format: NNN.NNNNNNNN, where NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_Lo w	High_AD_Level_B1_low	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at high end; band 1, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_Lo w	High_AD_Level_B2_low	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at high end; band 2, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_Lo w	High_AD_Level_B3_low	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at high end; band 3, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_Lo_w	High_AD_Level_B4_low	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at high end; band 4, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_Lo_w	High_AD_Level_B5_low	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at high end; band 5, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_Lo_w	High_AD_Level_B6_low	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at high end; band 6, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_Lo_w	High_AD_Level_B7_low	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at high end; band 7, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_Lo_w	High_AD_Level_B8_low	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at high end; band 8, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_Lo_w	Low_AD_Level_B1_low	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at low end; band 1, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_Lo_w	Low_AD_Level_B2_low	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at low end; band 2, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_Lo_w	Low_AD_Level_B3_low	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at low end; band 3, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_Lo_w	Low_AD_Level_B4_low	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at low end; band 4, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_Lo_w	Low_AD_Level_B5_low	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at low end; band 5, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_Lo_w	Low_AD_Level_B6_low	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at low end; band 6, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_Lo_w	Low_AD_Level_B7_low	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at low end; band 7, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_Lo_w	Low_AD_Level_B8_low	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at low end; band 8, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_High	High_AD_Level_B1_high	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at high end; band 1, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_High	High_AD_Level_B2_high	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at high end; band 2, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: 4AD_Converter_Saturation_High	High_AD_Level_B3_high	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at high end; band 3, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_High	High_AD_Level_B4_high	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at high end; band 4, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_High	High_AD_Level_B5_high	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at high end; band 5, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_High	High_AD_Level_B6_high	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at high end; band 6, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_High	High_AD_Level_B7_high	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at high end; band 7, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_High	High_AD_Level_B8_high	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at high end; band 8, gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_High	Low_AD_Level_B1_high	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at low end; band 1, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_High	Low_AD_Level_B2_high	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at low end; band 2, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_High	Low_AD_Level_B3_high	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at low end; band 3, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_High	Low_AD_Level_B4_high	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at low end; band 4, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_High	Low_AD_Level_B5_high	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at low end; band 5, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_High	Low_AD_Level_B6_high	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at low end; band 6, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_High	Low_AD_Level_B7_high	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at low end; band 7, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: AD_Converter_Saturation GROUP: AD_Converter_Saturation_High	Low_AD_Level_B8_high	Dynamic	uint8 array (16 values)	Digital count at which analog-to-digital converter saturates at low end; band 8, gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_Low	High_Analog_Level_B1_low	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at high end; band 1, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_Low	High_Analog_Level_B2_low	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at high end: band 2, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_Low	High_Analog_Level_B3_low	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at high end: band 3, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_Low	High_Analog_Level_B4_low	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at high end: band 4, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_Low	High_Analog_Level_B5_low	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at high end: band 5, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_Low	High_Analog_Level_B6_low	Dynamic	uint8 array (8 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at high end: band 6, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_Low	High_Analog_Level_B7_low	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at high end: band 7, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_Low	High_Analog_Level_B8_low	Dynamic	uint8 array (32 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at high end: band 8, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_Low	Low_Analog_Level_B1_low	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at low end: band 1, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_Low	Low_Analog_Level_B2_low	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at low end: band 2, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_Low	Low_Analog_Level_B3_low	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at low end: band 3, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_Low	Low_Analog_Level_B4_low	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at low end; band 4, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_Low	Low_Analog_Level_B5_low	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at low end; band 5, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_Low	Low_Analog_Level_B6_low	Dynamic	uint8 array (8 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at low end; band 6, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_Low	Low_Analog_Level_B7_low	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at low end; band 7, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_Low	Low_Analog_Level_B8_low	Dynamic	uint8 array (32 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at low end; band 8, low gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_High	High_Analog_Level_B1_high	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at high end; band 1, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_High	High_Analog_Level_B2_high	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at high end; band 2, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_High	High_Analog_Level_B3_high	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at high end; band 3, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_High	High_Analog_Level_B4_high	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at high end; band 4, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_High	High_Analog_Level_B5_high	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at high end; band 5, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_High	High_Analog_Level_B6_high	Dynamic	uint8 array (8 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at high end: band 6, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_High	High_Analog_Level_B7_high	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at high end: band 7, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_High	High_Analog_Level_B8_high	Dynamic	uint8 array (32 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at high end: band 8, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_High	Low_Analog_Level_B1_high	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at low end: band 1, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_High	Low_Analog_Level_B2_high	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at low end: band 2, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_High	Low_Analog_Level_B3_high	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at low end: band 3, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_High	Low_Analog_Level_B4_high	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at low end: band 4, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_High	Low_Analog_Level_B5_high	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at low end: band 5, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_High	Low_Analog_Level_B6_high	Dynamic	uint8 array (8 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at low end: band 6, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_High	Low_Analog_Level_B7_high	Dynamic	uint8 array (16 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at low end: band 7, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Detector_Saturation GROUP: Analog_Signal_Saturation GROUP: Analog_Signal_Saturation_High	Low_Analog_Level_B8_high	Dynamic	uint8 array (32 values)	Digital count corresponding to signal level at which analog portion of signal chain saturates at low end; band 8, high gain Valid format: NNN, where NNN = 255 (default)	Yes	Yes	SBRS
Group: Reference_Temperatures GROUP: Reference_Low	B1L_RTemp_Prelaunch	Static	float64	Band 1 prelaunch low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_Low	B1L_RTemp_Postlaunch	Static	float64	Band 1 postlaunch low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Reference_Temperatures GROUP: Reference_Low	B1L_RTemp_Current	Dynamic	float64	Band 1 current low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_Low	B2L_RTemp_Prelaunch	Static	float64	Band 2 prelaunch low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_Low	B2L_RTemp_Postlaunch	Static	float64	Band 2 postlaunch low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Reference_Temperatures GROUP: Reference_Low	B2L_RTemp_Current	Dynamic	float64	Band 2 current low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_Low	B3L_RTemp_Prelaunch	Static	float64	Band 3 prelaunch low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_Low	B3L_RTemp_Postlaunch	Static	float64	Band 3 postlaunch low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Reference_Temperatures GROUP: Reference_Low	B3L_RTemp_Current	Dynamic	float64	Band 3 current low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_Low	B4L_RTemp_Prelaunch	Static	float64	Band 4 prelaunch low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_Low	B4L_RTemp_Postlaunch	Static	float64	Band 4 postlaunch low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reference_Temperatures GROUP: Reference_Low	B4L_RTemp_Current	Dynamic	float64	Band 4 current low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_Low	B5L_RTemp_Prelaunch	Static	float64	Band 5 prelaunch low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_Low	B5L_RTemp_Postlaunch	Static	float64	Band 5 postlaunch low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Reference_Temperatures GROUP: Reference_Low	B5L_RTemp_Current	Dynamic	float64	Band 5 current low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_Low	B6L_RTemp_Prelaunch	Static	float64	Band 6 prelaunch low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	BL10 in thermal vacuum
Group: Reference_Temperatures GROUP: Reference_Low	B6L_RTemp_Postlaunch	Static	float64	Band 6 postlaunch low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Reference_Temperatures GROUP: Reference_Low	B6L_RTemp_Current	Dynamic	float64	Band 6 current low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	BL10 in thermal vacuum
Group: Reference_Temperatures GROUP: Reference_Low	B7L_RTemp_Prelaunch	Static	float64	Band 7 prelaunch low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_Low	B7L_RTemp_Postlaunch	Static	float64	Band 7 postlaunch low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Reference_Temperatures GROUP: Reference_Low	B7L_RTemp_Current	Dynamic	float64	Band 7 current low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_Low	B8L_RTemp_Prelaunch	Static	float64	Band 8 prelaunch low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_Low	B8L_RTemp_Postlaunch	Static	float64	Band 8 postlaunch low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reference_Temperatures GROUP: Reference_Low	B8L_RTemp_Current	Dynamic	float64	Band 8 current low-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_High	B1H_RTemp_Prelaunch	Static	float64	Band 1 prelaunch high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_High	B1H_RTemp_Postlaunch	Static	float64	Band 1 postlaunch high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Reference_Temperatures GROUP: Reference_High	B1H_RTemp_Current	Dynamic	float64	Band 1 current high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_High	B2H_RTemp_Prelaunch	Static	float64	Band 2 prelaunch high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_High	B2H_RTemp_Postlaunch	Static	float64	Band 2 postlaunch high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Reference_Temperatures GROUP: Reference_High	B2H_RTemp_Current	Dynamic	float64	Band 2 current high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_High	B3H_RTemp_Prelaunch	Static	float64	Band 3 prelaunch high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_High	B3H_RTemp_Postlaunch	Static	float64	Band 3 postlaunch high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Reference_Temperatures GROUP: Reference_High	B3H_RTemp_Current	Dynamic	float64	Band 3 current high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_High	B4H_RTemp_Prelaunch	Static	float64	Band 4 prelaunch high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_High	B4H_RTemp_Postlaunch	Static	float64	Band 4 postlaunch high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reference_Temperatures GROUP: Reference_High	B4H_RTemp_Current	Dynamic	float64	Band 4 current high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_High	B5H_RTemp_Prelaunch	Static	float64	Band 5 prelaunch high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_High	B5H_RTemp_Postlaunch	Static	float64	Band 5 postlaunch high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Reference_Temperatures GROUP: Reference_High	B5H_RTemp_Current	Dynamic	float64	Band 5 current high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_High	B6H_RTemp_Prelaunch	Static	float64	Band 6 prelaunch high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_High	B6H_RTemp_Postlaunch	Static	float64	Band 6 postlaunch high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Reference_Temperatures GROUP: Reference_High	B6H_RTemp_Current	Dynamic	float64	Band 6 current high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_High	B7H_RTemp_Prelaunch	Static	float64	Band 7 prelaunch high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_High	B7H_RTemp_Postlaunch	Static	float64	Band 7 postlaunch high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Reference_Temperatures GROUP: Reference_High	B7H_RTemp_Current	Dynamic	float64	Band 7 current high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_High	B8H_RTemp_Prelaunch	Static	float64	Band 8 prelaunch high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Reference_Temperatures GROUP: Reference_High	B8H_RTemp_Postlaunch	Static	float64	Band 8 postlaunch high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reference_Temperatures GROUP: Reference_High	B8H_RTemp_Current	Dynamic	float64	Band 8 current high-gain calibration reference temperature in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02 telemetry
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B1L_SCoeff_Prelaunch	Static	float64 array (16 values)	Band 1 prelaunch low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B1L_SCoeff_Postlaunch	Static	float64 array (16 values)	Band 1 postlaunch low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B1L_SCoeff_Current	Dynamic	float64 array (16 values)	Band 1 current low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B2L_SCoeff_Prelaunch	Static	float64 array (16 values)	Band 2 prelaunch low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B2L_SCoeff_Postlaunch	Static	float64 array (16 values)	Band 2 postlaunch low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B2L_SCoeff_Current	Dynamic	float64 array (16 values)	Band 2 current low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B3L_SCoeff_Prelaunch	Static	float64 array (16 values)	Band 3 prelaunch low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B3L_SCoeff_Postlaunch	Static	float64 array (16 values)	Band 3 postlaunch low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B3L_SCoeff_Current	Dynamic	float64 array (16 values)	Band 3 current low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B4L_SCoeff_Prelaunch	Static	float64 array (16 values)	Band 4 prelaunch low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B4L_SCoeff_Postlaunch	Static	float64 array (16 values)	Band 4 postlaunch low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B4L_SCoeff_Current	Dynamic	float64 array (16 values)	Band 4 current low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B5L_SCoeff_Prelaunch	Static	float64 array (16 values)	Band 5 prelaunch low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B5L_SCoeff_Postlaunch	Static	float64 array (16 values)	Band 5 postlaunch low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B5L_SCoeff_Current	Dynamic	float64 array (16 values)	Band 5 current low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B6L_SCoeff_Prelaunch	Static	float64 array (8 values)	Band 6 prelaunch low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B6L_SCoeff_Postlaunch	Static	float64 array (8 values)	Band 6 postlaunch low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B6L_SCoeff_Current	Dynamic	float64 array (8 values)	Band 6 current low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B6L_SCoeffOff_Prelaunch	Static	float64 array (8 values)	Band 6 prelaunch offset calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B6L_SCoeffOff_Postlaunc h	Static	float64 array (8 values)	Band 6 postlaunch offset calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B6L_SCoeffOff_Current	Dynamic	float64 array (8 values)	Band 6 current offset calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B7L_SCoeff_Prelaunch	Static	float64 array (16 values)	Band 7 prelaunch low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B7L_SCoeff_Postlaunch	Static	float64 array (16 values)	Band 7 postlaunch low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B7L_SCoeff_Current	Dynamic	float64 array (16 values)	Band 7 current low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B8L_SCoeff_Prelaunch	Static	float64 array (32 values)	Band 8 prelaunch low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B8L_SCoeff_Postlaunch	Static	float64 array (32 values)	Band 8 postlaunch low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Sensitivity_Temperatures GROUP: Sensitivity_Low	B8L_SCoeff_Current	Dynamic	float64 array (32 values)	Band 8 current low-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B1H_SCoeff_Prelaunch	Static	float64 array (16 values)	Band 1 prelaunch high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B1H_SCoeff_Postlaunch	Static	float64 array (16 values)	Band 1 postlaunch high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B1H_SCoeff_Current	Dynamic	float64 array (16 values)	Band 1 current high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B2H_SCoeff_Prelaunch	Static	float64 array (16 values)	Band 2 prelaunch high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B2H_SCoeff_Postlaunch	Static	float64 array (16 values)	Band 2 postlaunch high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B2H_SCoeff_Current	Dynamic	float64 array (16 values)	Band 2 current high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B3H_SCoeff_Prelaunch	Static	float64 array (16 values)	Band 3 prelaunch high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B3H_SCoeff_Postlaunch	Static	float64 array (16 values)	Band 3 postlaunch high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B3H_SCoeff_Current	Dynamic	float64 array (16 values)	Band 3 current high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B4H_SCoeff_Prelaunch	Static	float64 array (16 values)	Band 4 prelaunch high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B4H_SCoeff_Postlaunch	Static	float64 array (16 values)	Band 4 postlaunch high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B4H_SCoeff_Current	Dynamic	float64 array (16 values)	Band 4 current high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B5H_SCoeff_Prelaunch	Static	float64 array (16 values)	Band 5 prelaunch high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B5H_SCoeff_Postlaunch	Static	float64 array (16 values)	Band 5 postlaunch high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B5H_SCoeff_Current	Dynamic	float64 array (16 values)	Band 5 current high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B6H_SCoeff_Prelaunch	Static	float64 array (8 values)	Band 6 prelaunch high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B6H_SCoeff_Postlaunch	Static	float64 array (8 values)	Band 6 postlaunch high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B6H_SCoeff_Current	Dynamic	float64 array (8 values)	Band 6 current high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B6H_SCoeffOff_Prelaunch	Static	float64 array (8 values)	Band 6 prelaunch offset calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B6H_SCoeffOff_Postlaunch	Static	float64 array (8 values)	Band 6 postlaunch offset calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B6H_SCoeffOff_Current	Dynamic	float64 array (8 values)	Band 6 current offset calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B7H_SCoeff_Prelaunch	Static	float64 array (16 values)	Band 7 prelaunch high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B7H_SCoeff_Postlaunch	Static	float64 array (16 values)	Band 7 postlaunch high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B7H_SCoeff_Current	Dynamic	float64 array (16 values)	Band 7 current high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B8H_SCoeff_Prelaunch	Static	float64 array (32 values)	Band 8 prelaunch high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B8H_SCoeff_Postlaunch	Static	float64 array (32 values)	Band 8 postlaunch high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Postlaunch
Group: Sensitivity_Temperatures GROUP: Sensitivity_High	B8H_SCoeff_Current	Dynamic	float64 array (32 values)	Band 8 current high-gain calibration temperature sensitivity coefficient Valid format: NNN.NNNN, where NNN.NNNN = TBS	No	Yes	Thermal vacuum
Group: Lamp_Radiance GROUP: Trending_Coeffs	Lamp1_Coeffs		float32 array (2 values)	Time since launch coefficients for Lamp 1 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Lamp_Radiance GROUP: Trending_Coeffs	Lamp2_Coeffs		float32 array (2 values)	Time since launch coefficients for Lamp 2 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B1L_Rad_State1_Prelaunch	Static	float32 array (16 values)	Band 1 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 off; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B1L_Rad_State1_Postlaunch	Static	float32 array (16 values)	Band 1 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 off; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B1L_Rad_State1_Current	Dynamic	float32 array (16 values)	Band 1 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 off; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B1L_Rad_State2_Prelaunch	Static	float32 array (16 values)	Band 1 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B1L_Rad_State2_Postlaunch	Static	float32 array (16 values)	Band 1 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B1L_Rad_State2_Current	Dynamic	float32 array (16 values)	Band 1 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B1L_Rad_State3_Prelaunch	Static	float32 array (16 values)	Band 1 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B1L_Rad_State3_Postlaunch	Static	float32 array (16 values)	Band 1 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B1L_Rad_State3_Current	Dynamic	float32 array (16 values)	Band 1 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B2L_Rad_State1_Prelaunch	Static	float32 array (16 values)	Band 2 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 off; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B2L_Rad_State1_Postlaunch	Static	float32 array (16 values)	Band 2 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 off; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B2L_Rad_State1_Current	Dynamic	float32 array (16 values)	Band 2 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 off; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B2L_Rad_State2_Prelaunch	Static	float32 array (16 values)	Band 2 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B2L_Rad_State2_Postlaunch	Static	float32 array (16 values)	Band 2 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B2L_Rad_State2_Current	Dynamic	float32 array (16 values)	Band 2 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B2L_Rad_State3_Prelaunch	Static	float32 array (16 values)	Band 2 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B2L_Rad_State3_Postlaunch	Static	float32 array (16 values)	Band 2 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B2L_Rad_State3_Current	Dynamic	float32 array (16 values)	Band 2 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B3L_Rad_State1_Prelaunch	Static	float32 array (16 values)	Band 3 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B3L_Rad_State1_Postlaunch	Static	float32 array (16 values)	Band 3 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B3L_Rad_State1_Current	Dynamic	float32 array (16 values)	Band 3 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B3L_Rad_State2_Prelaunch	Static	float32 array (16 values)	Band 3 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B3L_Rad_State2_Postlaunch	Static	float32 array (16 values)	Band 3 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B3L_Rad_State2_Current	Dynamic	float32 array (16 values)	Band 3 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B3L_Rad_State3_Prelaunch	Static	float32 array (16 values)	Band 3 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B3L_Rad_State3_Postlaunch	Static	16 values) float32 array (Band 3 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B3L_Rad_State3_Current	Dynamic	float32 array (16 values)	Band 3 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B4L_Rad_State1_Prelaunch	Static	float32 array (16 values)	Band 4 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B4L_Rad_State1_Postlaunch	Static	float32 array (16 values)	Band 4 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B4L_Rad_State1_Current	Dynamic	float32 array (16 values)	Band 4 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B4L_Rad_State2_Prelaunch	Static	float32 array (16 values)	Band 4 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B4L_Rad_State2_Postlaunch	Static	float32 array (16 values)	Band 4 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B4L_Rad_State2_Current	Dynamic	float32 array (16 values)	Band 4 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B4L_Rad_State3_Prelaunch	Static	float32 array (16 values)	Band 4 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B4L_Rad_State3_Postlaunch	Static	float32 array (16 values)	Band 4 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B4L_Rad_State3_Current	Dynamic	float32 array (16 values)	Band 4 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B5L_Rad_State1_Prelaunch	Static	float32 array (16 values)	Band 5 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B5L_Rad_State1_Postlaunch	Static	float32 array (16 values)	Band 5 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B5L_Rad_State1_Current	Dynamic	float32 array (16 values)	Band 5 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B5L_Rad_State2_Prelaunch	Static	float32 array (16 values)	Band 5 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B5L_Rad_State2_Postlaunch	Static	float32 array (16 values)	Band 5 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B5L_Rad_State2_Current	Dynamic	float32 array (16 values)	Band 5 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B5L_Rad_State3_Prelaunch	Static	float32 array (16 values)	Band 5 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B5L_Rad_State3_Postlaunch	Static	float32 array (16 values)	Band 5 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B5L_Rad_State3_Current	Dynamic	float32 array (16 values)	Band 5 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B7L_Rad_State1_Prelaunch	Static	float32 array (16 values)	Band 7 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B7L_Rad_State1_Postlaunch	Static	float32 array (16 values)	Band 7 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B7L_Rad_State1_Current	Dynamic	float32 array (16 values)	Band 7 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B7L_Rad_State2_Prelaunch	Static	float32 array (16 values)	Band 7 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B7L_Rad_State2_Postlaunch	Static	float32 array (16 values)	Band 7 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B7L_Rad_State2_Current	Dynamic	float32 array (16 values)	Band 7 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B7L_Rad_State3_Prelaunch	Static	float32 array (16 values)	Band 7 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B7L_Rad_State3_Postlaunch	Static	float32 array (16 values)	Band 7 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B7L_Rad_State3_Current	Dynamic	float32 array (16 values)	Band 7 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B8L_Rad_State1_Prelaunch	Static	float32 array (32 values)	Band 8 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B8L_Rad_State1_Postlaunch	Static	float32 array (32 values)	Band 8 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B8L_Rad_State1_Current	Dynamic	float32 array (32 values)	Band 8 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B8L_Rad_State2_Prelaunch	Static	float32 array (32 values)	Band 8 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B8L_Rad_State2_Postlaunch	Static	float32 array (32 values)	Band 8 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B8L_Rad_State2_Current	Dynamic	float32 array (32 values)	Band 8 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B8L_Rad_State3_Prelaunch	Static	float32 array (32 values)	Band 8 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B8L_Rad_State3_Postlaunch	Static	float32 array (32 values)	Band 8 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_Low	B8L_Rad_State3_Current	Dynamic	float32 array (32 values)	Band 8 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; low-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B1H_Rad_State1_Prelaunch	Static	float32 array (16 values)	Band 1 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 off; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B1H_Rad_State1_Postlaunch	Static	float32 array (16 values)	Band 1 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 off; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B1H_Rad_State1_Current	Dynamic	float32 array (16 values)	Band 1 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 off; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B1H_Rad_State2_Prelaunch	Static	float32 array (16 values)	Band 1 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B1H_Rad_State2_Postlaunch	Static	float32 array (16 values)	Band 1 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B1H_Rad_State2_Current	Dynamic	float32 array (16 values)	Band 1 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B1H_Rad_State3_Prelaunch	Static	float32 array (16 values)	Band 1 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B1H_Rad_State3_Postlaunch	Static	float32 array (16 values)	Band 1 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B1H_Rad_State3_Current	Dynamic	float32 array (16 values)	Band 1 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B2H_Rad_State1_Prelaunch	Static	float32 array (16 values)	Band 2 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B2H_Rad_State1_Postlaunch	Static	float32 array (16 values)	Band 2 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B2H_Rad_State1_Current	Dynamic	float32 array (16 values)	Band 2 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B2H_Rad_State2_Prelaunch	Static	float32 array (16 values)	Band 2 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B2H_Rad_State2_Postlaunch	Static	float32 array (16 values)	Band 2 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B2H_Rad_State2_Current	Dynamic	float32 array (16 values)	Band 2 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B2H_Rad_State3_Prelaunch	Static	float32 array (16 values)	Band 2 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B2H_Rad_State3_Postlaunch	Static	float32 array (16 values)	Band 2 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B2H_Rad_State3_Current	Dynamic	float32 array (16 values)	Band 2 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B3H_Rad_State1_Prelaunch	Static	float32 array (16 values)	Band 3 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B3H_Rad_State1_Postlaunch	Static	float32 array (16 values)	Band 3 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B3H_Rad_State1_Current	Dynamic	float32 array (16 values)	Band 3 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B3H_Rad_State2_Prelaunch	Static	float32 array (16 values)	Band 3 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B3H_Rad_State2_Postlaunch	Static	float32 array (16 values)	Band 3 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B3H_Rad_State2_Current	Dynamic	float32 array (16 values)	Band 3 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B3H_Rad_State3_Prelaunch	Static	float32 array (16 values)	Band 3 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B3H_Rad_State3_Postlaunch	Static	float32 array (16 values)	Band 3 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B3H_Rad_State3_Current	Dynamic	float32 array (16 values)	Band 3 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B4H_Rad_State1_Prelaunch	Static	float32 array (16 values)	Band 4 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B4H_Rad_State1_Postlaunch	Static	float32 array (16 values)	Band 4 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B4H_Rad_State1_Current	Dynamic	float32 array (16 values)	Band 4 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B4H_Rad_State2_Prelaunch	Static	float32 array (16 values)	Band 4 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B4H_Rad_State2_Postlaunch	Static	float32 array (16 values)	Band 4 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B4H_Rad_State2_Current	Dynamic	float32 array (16 values)	Band 4 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B4H_Rad_State3_Prelaunch	Static	float32 array (16 values)	Band 4 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B4H_Rad_State3_Postlaunch	Static	float32 array (16 values)	Band 4 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B4H_Rad_State3_Current	Dynamic	float32 array (16 values)	Band 4 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B5H_Rad_State1_Prelaunch	Static	float32 array (16 values)	Band 5 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B5H_Rad_State1_Postlaunch	Static	float32 array (16 values)	Band 5 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B5H_Rad_State1_Current	Dynamic	float32 array (16 values)	Band 5 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B5H_Rad_State2_Prelaunch	Static	float32 array (16 values)	Band 5 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B5H_Rad_State2_Postlaunch	Static	float32 array (16 values)	Band 5 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B5H_Rad_State2_Current	Dynamic	float32 array (16 values)	Band 5 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B5H_Rad_State3_Prelaunch	Static	float32 array (16 values)	Band 5 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B5H_Rad_State3_Postlaunch	Static	float32 array (16 values)	Band 5 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B5H_Rad_State3_Current	Dynamic	float32 array (16 values)	Band 5 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B7H_Rad_State1_Prelaunch	Static	float32 array (16 values)	Band 7 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B7H_Rad_State1_Postlaunch	Static	float32 array (16 values)	Band 7 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B7H_Rad_State1_Current	Dynamic	float32 array (16 values)	Band 7 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B7H_Rad_State2_Prelaunch	Static	float32 array (16 values)	Band 7 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B7H_Rad_State2_Postlaunch	Static	float32 array (16 values)	Band 7 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B7H_Rad_State2_Current	Dynamic	float32 array (16 values)	Band 7 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B7H_Rad_State3_Prelaunch	Static	float32 array (16 values)	Band 7 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B7H_Rad_State3_Postlaunch	Static	float32 array (16 values)	Band 7 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B7H_Rad_State3_Current	Dynamic	float32 array (16 values)	Band 7 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B8H_Rad_State1_Prelaunch	Static	float32 array (32 values)	Band 8 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B8H_Rad_State1_Postlaunch	Static	float32 array (32 values)	Band 8 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B8H_Rad_State1_Current	Dynamic	float32 array (32 values)	Band 8 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 1 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B8H_Rad_State2_Prelaunch	Static	float32 array (32 values)	Band 8 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B8H_Rad_State2_Postlaunch	Static	float32 array (32 values)	Band 8 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B8H_Rad_State2_Current	Dynamic	float32 array (32 values)	Band 8 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 2 – lamp 1 off, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B8H_Rad_State3_Prelaunch	Static	float32 array (32 values)	Band 8 prelaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B8H_Rad_State3_Postlaunch	Static	float32 array (32 values)	Band 8 postlaunch internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	Postlaunch
Group: Lamp_Radiance GROUP: Lamp_Radiance_High	B8H_Rad_State3_Current	Dynamic	float32 array (32 values)	Band 8 current internal calibrator lamp effective spectral radiance in W/m^2-ster-μm; State 3 – lamp 1 on, lamp 2 on; high-gain mode Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	AC02/ AC48
Group: Lamp_Reference	Lmp_Rtemp_Prelaunch	Static	float32 array (14 values)	Prelaunch internal calibrator lamp radiance reference temperatures in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	No	LPSO
Group: Lamp_Reference	Lmp_Rtemp_Postlaunch	Static	float32 array (14 values)	Postlaunch internal calibrator lamp radiance reference temperatures in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	LPSO
Group: Lamp_Reference	Lmp_Rtemp_Current	Dynamic	float32 array (14 values)	Current internal calibrator lamp radiance reference temperatures in degrees C Valid format: NNN.NNN, where NNN.NNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B1L_Coefficients_Detector1	Dynamic	float32 array (18 values)	IC coefficients for band 1, low gain, detector 1 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B1L_Coefficients_Detector2	Dynamic	float32 array (18 values)	IC coefficients for band 1, low gain, detector 2 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B1L_Coefficients_Detector3	Dynamic	float32 array (18 values)	IC coefficients for band 1, low gain, detector 3 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B1L_Coefficients_Detector4	Dynamic	float32 array (18 values)	IC coefficients for band 1, low gain, detector 4 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B1L_Coefficients_Detector5	Dynamic	float32 array (18 values)	IC coefficients for band 1, low gain, detector 5 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B1L_Coefficients_Detector6	Dynamic	float32 array (18 values)	IC coefficients for band 1, low gain, detector 6 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B1L_Coefficients_Detector7	Dynamic	float32 array (18 values)	IC coefficients for band 1, low gain, detector 7 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B1L_Coefficients_Detector8	Dynamic	float32 array (18 values)	IC coefficients for band 1, low gain, detector 8 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B1L_Coefficients_Detector9	Dynamic	float32 array (18 values)	IC coefficients for band 1, low gain, detector 9 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B1L_Coefficients_Detector10	Dynamic	float32 array (18 values)	IC coefficients for band 1, low gain, detector 10 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B1L_Coefficients_Detector11	Dynamic	float32 array (18 values)	IC coefficients for band 1, low gain, detector 11 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B1L_Coefficients_Detector12	Dynamic	float32 array (18 values)	IC coefficients for band 1, low gain, detector 12 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B1L_Coefficients_Detector13	Dynamic	float32 array (18 values)	IC coefficients for band 1, low gain, detector 13 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B1L_Coefficients_Detector14	Dynamic	float32 array (18 values)	IC coefficients for band 1, low gain, detector 14 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B1L_Coefficients_Detector15	Dynamic	float32 array (18 values)	IC coefficients for band 1, low gain, detector 15 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B1L_Coefficients_Detector16	Dynamic	float32 array (18 values)	IC coefficients for band 1, low gain, detector 16 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B2L_Coefficients_Detector1	Dynamic	float32 array (18 values)	IC coefficients for band 2, low gain, detector 1 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B2L_Coefficients_Detector2	Dynamic	float32 array (18 values)	IC coefficients for band 2, low gain, detector 2 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B2L_Coefficients_Detector3	Dynamic	float32 array (18 values)	IC coefficients for band 2, low gain, detector 3 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B2L_Coefficients_Detector4	Dynamic	float32 array (18 values)	IC coefficients for band 2, low gain, detector 4 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B2L_Coefficients_Detector5	Dynamic	float32 array (18 values)	IC coefficients for band 2, low gain, detector 5 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B2L_Coefficients_Detector6	Dynamic	float32 array (18 values)	IC coefficients for band 2, low gain, detector 6 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B2L_Coefficients_Detector7	Dynamic	float32 array (18 values)	IC coefficients for band 2, low gain, detector 7 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B2L_Coefficients_Detector8	Dynamic	float32 array (18 values)	IC coefficients for band 2, low gain, detector 8 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B2L_Coefficients_Detector9	Dynamic	float32 array (18 values)	IC coefficients for band 2, low gain, detector 9 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B2L_Coefficients_Detector10	Dynamic	float32 array (18 values)	IC coefficients for band 2, low gain, detector 10 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B2L_Coefficients_Detector11	Dynamic	float32 array (18 values)	IC coefficients for band 2, low gain, detector 11 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B2L_Coefficients_Detector12	Dynamic	float32 array (18 values)	IC coefficients for band 2, low gain, detector 12 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B2L_Coefficients_Detector13	Dynamic	float32 array (18 values)	IC coefficients for band 2, low gain, detector 13 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B2L_Coefficients_Detector14	Dynamic	float32 array (18 values)	IC coefficients for band 2, low gain, detector 14 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B2L_Coefficients_Detector15	Dynamic	float32 array (18 values)	IC coefficients for band 2, low gain, detector 15 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B2L_Coefficients_Detector16	Dynamic	float32 array (18 values)	IC coefficients for band 2, low gain, detector 16 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B3L_Coefficients_Detector1	Dynamic	float32 array (18 values)	IC coefficients for band 3, low gain, detector 1 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B3L_Coefficients_Detector2	Dynamic	float32 array (18 values)	IC coefficients for band 3, low gain, detector 2 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B3L_Coefficients_Detector3	Dynamic	float32 array (18 values)	IC coefficients for band 3, low gain, detector 3 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B3L_Coefficients_Detector4	Dynamic	float32 array (18 values)	IC coefficients for band 3, low gain, detector 4 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B3L_Coefficients_Detector5	Dynamic	float32 array (18 values)	IC coefficients for band 3, low gain, detector 5 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B3L_Coefficients_Detector6	Dynamic	float32 array (18 values)	IC coefficients for band 3, low gain, detector 6 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B3L_Coefficients_Detector7	Dynamic	float32 array (18 values)	IC coefficients for band 3, low gain, detector 7 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B3L_Coefficients_Detector8	Dynamic	float32 array (18 values)	IC coefficients for band 3, low gain, detector 8 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B3L_Coefficients_Detector9	Dynamic	float32 array (18 values)	IC coefficients for band 3, low gain, detector 9 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B3L_Coefficients_Detector10	Dynamic	float32 array (18 values)	IC coefficients for band 3, low gain, detector 10 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B3L_Coefficients_Detector11	Dynamic	float32 array (18 values)	IC coefficients for band 3, low gain, detector 11 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B3L_Coefficients_Detector12	Dynamic	float32 array (18 values)	IC coefficients for band 3, low gain, detector 12 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B3L_Coefficients_Detector13	Dynamic	float32 array (18 values)	IC coefficients for band 3, low gain, detector 13 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B3L_Coefficients_Detector14	Dynamic	float32 array (18 values)	IC coefficients for band 3, low gain, detector 14 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B3L_Coefficients_Detector15	Dynamic	float32 array (18 values)	IC coefficients for band 3, low gain, detector 15 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B3L_Coefficients_Detector16	Dynamic	float32 array (18 values)	IC coefficients for band 3, low gain, detector 16 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B4L_Coefficients_Detector1	Dynamic	float32 array (18 values)	IC coefficients for band 4, low gain, detector 1 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B4L_Coefficients_Detector2	Dynamic	float32 array (18 values)	IC coefficients for band 4, low gain, detector 2 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B4L_Coefficients_Detector3	Dynamic	float32 array (18 values)	IC coefficients for band 4, low gain, detector 3 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B4L_Coefficients_Detector4	Dynamic	float32 array (18 values)	IC coefficients for band 4, low gain, detector 4 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B4L_Coefficients_Detector5	Dynamic	float32 array (18 values)	IC coefficients for band 4, low gain, detector 5 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B4L_Coefficients_Detector6	Dynamic	float32 array (18 values)	IC coefficients for band 4, low gain, detector 6 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B4L_Coefficients_Detector7	Dynamic	float32 array (18 values)	IC coefficients for band 4, low gain, detector 7 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B4L_Coefficients_Detector8	Dynamic	float32 array (18 values)	IC coefficients for band 4, low gain, detector 8 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B4L_Coefficients_Detector9	Dynamic	float32 array (18 values)	IC coefficients for band 4, low gain, detector 9 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B4L_Coefficients_Detector10	Dynamic	float32 array (18 values)	IC coefficients for band 4, low gain, detector 10 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B4L_Coefficients_Detector11	Dynamic	float32 array (18 values)	IC coefficients for band 4, low gain, detector 11 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B4L_Coefficients_Detector12	Dynamic	float32 array (18 values)	IC coefficients for band 4, low gain, detector 12 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B4L_Coefficients_Detector13	Dynamic	float32 array (18 values)	IC coefficients for band 4, low gain, detector 13 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B4L_Coefficients_Detector14	Dynamic	float32 array (18 values)	IC coefficients for band 4, low gain, detector 14 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B4L_Coefficients_Detector15	Dynamic	float32 array (18 values)	IC coefficients for band 4, low gain, detector 15 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B4L_Coefficients_Detector16	Dynamic	float32 array (18 values)	IC coefficients for band 4, low gain, detector 16 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B5L_Coefficients_Detector1	Dynamic	float32 array (18 values)	IC coefficients for band 5, low gain, detector 1 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B5L_Coefficients_Detector2	Dynamic	float32 array (18 values)	IC coefficients for band 5, low gain, detector 2 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B5L_Coefficients_Detector3	Dynamic	float32 array (18 values)	IC coefficients for band 5, low gain, detector 3 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B5L_Coefficients_Detector4	Dynamic	float32 array (18 values)	IC coefficients for band 5, low gain, detector 4 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B5L_Coefficients_Detector5	Dynamic	float32 array (18 values)	IC coefficients for band 5, low gain, detector 5 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B5L_Coefficients_Detector6	Dynamic	float32 array (18 values)	IC coefficients for band 5, low gain, detector 6 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B5L_Coefficients_Detector7	Dynamic	float32 array (18 values)	IC coefficients for band 5, low gain, detector 7 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B5L_Coefficients_Detector8	Dynamic	float32 array (18 values)	IC coefficients for band 5, low gain, detector 8 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B5L_Coefficients_Detector9	Dynamic	float32 array (18 values)	IC coefficients for band 5, low gain, detector 9 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B5L_Coefficients_Detector10	Dynamic	float32 array (18 values)	IC coefficients for band 5, low gain, detector 10 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B5L_Coefficients_Detector11	Dynamic	float32 array (18 values)	IC coefficients for band 5, low gain, detector 11 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B5L_Coefficients_Detector12	Dynamic	float32 array (18 values)	IC coefficients for band 5, low gain, detector 12 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B5L_Coefficients_Detector13	Dynamic	float32 array (18 values)	IC coefficients for band 5, low gain, detector 13 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B5L_Coefficients_Detector14	Dynamic	float32 array (18 values)	IC coefficients for band 5, low gain, detector 14 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B5L_Coefficients_Detector15	Dynamic	float32 array (18 values)	IC coefficients for band 5, low gain, detector 15 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B5L_Coefficients_Detector16	Dynamic	float32 array (18 values)	IC coefficients for band 5, low gain, detector 16 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B7L_Coefficients_Detector1	Dynamic	float32 array (18 values)	IC coefficients for band 7, low gain, detector 1 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B7L_Coefficients_Detector2	Dynamic	float32 array (18 values)	IC coefficients for band 7, low gain, detector 2 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B7L_Coefficients_Detector3	Dynamic	float32 array (18 values)	IC coefficients for band 7, low gain, detector 3 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B7L_Coefficients_Detector4	Dynamic	float32 array (18 values)	IC coefficients for band 7, low gain, detector 4 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B7L_Coefficients_Detector5	Dynamic	float32 array (18 values)	IC coefficients for band 7, low gain, detector 5 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B7L_Coefficients_Detector6	Dynamic	float32 array (18 values)	IC coefficients for band 7, low gain, detector 6 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B7L_Coefficients_Detector7	Dynamic	float32 array (18 values)	IC coefficients for band 7, low gain, detector 7 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B7L_Coefficients_Detector8	Dynamic	float32 array (18 values)	IC coefficients for band 7, low gain, detector 8 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B7L_Coefficients_Detector9	Dynamic	float32 array (18 values)	IC coefficients for band 7, low gain, detector 9 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B7L_Coefficients_Detector10	Dynamic	float32 array (18 values)	IC coefficients for band 7, low gain, detector 10 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B7L_Coefficients_Detector11	Dynamic	float32 array (18 values)	IC coefficients for band 7, low gain, detector 11 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B7L_Coefficients_Detector12	Dynamic	float32 array (18 values)	IC coefficients for band 7, low gain, detector 12 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B7L_Coefficients_Detector13	Dynamic	float32 array (18 values)	IC coefficients for band 7, low gain, detector 13 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B7L_Coefficients_Detector14	Dynamic	float32 array (18 values)	IC coefficients for band 7, low gain, detector 14 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B7L_Coefficients_Detector15	Dynamic	float32 array (18 values)	IC coefficients for band 7, low gain, detector 15 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B7L_Coefficients_Detector16	Dynamic	float32 array (18 values)	IC coefficients for band 7, low gain, detector 16 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector1	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 1 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector2	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 2 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector3	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 3 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector4	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 4 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector5	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 5 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector6	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 6 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector7	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 7 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector8	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 8 Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector9	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 9 Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector10	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 10 Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector11	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 11 Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector12	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 12 Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector13	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 13 Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector14	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 14 Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector15	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 15 Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector16	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 16 Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector17	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 17 Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector18	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 18 Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector19	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 19 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector 20	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 20 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector 21	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 21 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector 22	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 22 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector 23	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 23 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector 24	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 24 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector 25	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 25 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector 26	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 26 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector 27	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 27 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector 28	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 28 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector 29	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 29 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector 30	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 30 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector 31	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 31 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_Low	B8L_Coefficients_Detector 32	Dynamic	float32 array (18 values)	IC coefficients for band 8, low gain, detector 32 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B1H_Coefficients_Detector1	Dynamic	float32 array (18 values)	IC coefficients for band 1, high gain, detector 1 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B1H_Coefficients_Detector2	Dynamic	float32 array (18 values)	IC coefficients for band 1, high gain, detector 2 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B1H_Coefficients_Detector3	Dynamic	float32 array (18 values)	IC coefficients for band 1, high gain, detector 3 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B1H_Coefficients_Detector4	Dynamic	float32 array (18 values)	IC coefficients for band 1, high gain, detector 4 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B1H_Coefficients_Detector5	Dynamic	float32 array (18 values)	IC coefficients for band 1, high gain, detector 5 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B1H_Coefficients_Detector6	Dynamic	float32 array (18 values)	IC coefficients for band 1, high gain, detector 6 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B1H_Coefficients_Detector7	Dynamic	float32 array (18 values)	IC coefficients for band 1, high gain, detector 7 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B1H_Coefficients_Detector8	Dynamic	float32 array (18 values)	IC coefficients for band 1, high gain, detector 8 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B1H_Coefficients_Detector9	Dynamic	float32 array (18 values)	IC coefficients for band 1, high gain, detector 9 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B1H_Coefficients_Detector10	Dynamic	float32 array (18 values)	IC coefficients for band 1, high gain, detector 10 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B1H_Coefficients_Detector11	Dynamic	float32 array (18 values)	IC coefficients for band 1, high gain, detector 11 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B1H_Coefficients_Detector12	Dynamic	float32 array (18 values)	IC coefficients for band 1, high gain, detector 12 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B1H_Coefficients_Detector13	Dynamic	float32 array (18 values)	IC coefficients for band 1, high gain, detector 13 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B1H_Coefficients_Detector14	Dynamic	float32 array (18 values)	IC coefficients for band 1, high gain, detector 14 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B1H_Coefficients_Detector15	Dynamic	float32 array (18 values)	IC coefficients for band 1, high gain, detector 15 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B1H_Coefficients_Detector16	Dynamic	float32 array (18 values)	IC coefficients for band 1, high gain, detector 16 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B2H_Coefficients_Detector1	Dynamic	float32 array (18 values)	IC coefficients for band 2, high gain, detector 1 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B2H_Coefficients_Detector2	Dynamic	float32 array (18 values)	IC coefficients for band 2, high gain, detector 2 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B2H_Coefficients_Detector3	Dynamic	float32 array (18 values)	IC coefficients for band 2, high gain, detector 3 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B2H_Coefficients_Detector4	Dynamic	float32 array (18 values)	IC coefficients for band 2, high gain, detector 4 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B2H_Coefficients_Detector5	Dynamic	float32 array (18 values)	IC coefficients for band 2, high gain, detector 5 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B2H_Coefficients_Detector6	Dynamic	float32 array (18 values)	IC coefficients for band 2, high gain, detector 6 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B2H_Coefficients_Detector7	Dynamic	float32 array (18 values)	IC coefficients for band 2, high gain, detector 7 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B2H_Coefficients_Detector8	Dynamic	float32 array (18 values)	IC coefficients for band 2, high gain, detector 8 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B2H_Coefficients_Detector9	Dynamic	float32 array (18 values)	IC coefficients for band 2, high gain, detector 9 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B2H_Coefficients_Detector10	Dynamic	float32 array (18 values)	IC coefficients for band 2, high gain, detector 10 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B2H_Coefficients_Detector11	Dynamic	float32 array (18 values)	IC coefficients for band 2, high gain, detector 11 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B2H_Coefficients_Detector12	Dynamic	float32 array (18 values)	IC coefficients for band 2, high gain, detector 12 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B2H_Coefficients_Detector13	Dynamic	float32 array (18 values)	IC coefficients for band 2, high gain, detector 13 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B2H_Coefficients_Detector14	Dynamic	float32 array (18 values)	IC coefficients for band 2, high gain, detector 14 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B2H_Coefficients_Detector15	Dynamic	float32 array (18 values)	IC coefficients for band 2, high gain, detector 15 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B2H_Coefficients_Detector16	Dynamic	float32 array (18 values)	IC coefficients for band 2, high gain, detector 16 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B3H_Coefficients_Detector1	Dynamic	float32 array (18 values)	IC coefficients for band 3, high gain, detector 1 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B3H_Coefficients_Detector2	Dynamic	float32 array (18 values)	IC coefficients for band 3, high gain, detector 2 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B3H_Coefficients_Detector3	Dynamic	float32 array (18 values)	IC coefficients for band 3, high gain, detector 3 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B3H_Coefficients_Detector4	Dynamic	float32 array (18 values)	IC coefficients for band 3, high gain, detector 4 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B3H_Coefficients_Detector5	Dynamic	float32 array (18 values)	IC coefficients for band 3, high gain, detector 5 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B3H_Coefficients_Detector6	Dynamic	float32 array (18 values)	IC coefficients for band 3, high gain, detector 6 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B3H_Coefficients_Detector7	Dynamic	float32 array (18 values)	IC coefficients for band 3, high gain, detector 7 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B3H_Coefficients_Detector8	Dynamic	float32 array (18 values)	IC coefficients for band 3, high gain, detector 8 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B3H_Coefficients_Detector9	Dynamic	float32 array (18 values)	IC coefficients for band 3, high gain, detector 9 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B3H_Coefficients_Detector10	Dynamic	float32 array (18 values)	IC coefficients for band 3, high gain, detector 10 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B3H_Coefficients_Detector11	Dynamic	float32 array (18 values)	IC coefficients for band 3, high gain, detector 11 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B3H_Coefficients_Detector12	Dynamic	float32 array (18 values)	IC coefficients for band 3, high gain, detector 12 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B3H_Coefficients_Detector13	Dynamic	float32 array (18 values)	IC coefficients for band 3, high gain, detector 13 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B3H_Coefficients_Detector14	Dynamic	float32 array (18 values)	IC coefficients for band 3, high gain, detector 14 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B3H_Coefficients_Detector15	Dynamic	float32 array (18 values)	IC coefficients for band 3, high gain, detector 15 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B3H_Coefficients_Detector16	Dynamic	float32 array (18 values)	IC coefficients for band 3, high gain, detector 16 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B4H_Coefficients_Detector1	Dynamic	float32 array (18 values)	IC coefficients for band 4, high gain, detector 1 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B4H_Coefficients_Detector2	Dynamic	float32 array (18 values)	IC coefficients for band 4, high gain, detector 2 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B4H_Coefficients_Detector3	Dynamic	float32 array (18 values)	IC coefficients for band 4, high gain, detector 3 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B4H_Coefficients_Detector4	Dynamic	float32 array (18 values)	IC coefficients for band 4, high gain, detector 4 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B4H_Coefficients_Detector5	Dynamic	float32 array (18 values)	IC coefficients for band 4, high gain, detector 5 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B4H_Coefficients_Detector6	Dynamic	float32 array (18 values)	IC coefficients for band 4, high gain, detector 6 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B4H_Coefficients_Detector7	Dynamic	float32 array (18 values)	IC coefficients for band 4, high gain, detector 7 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B4H_Coefficients_Detector8	Dynamic	float32 array (18 values)	IC coefficients for band 4, high gain, detector 8 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B4H_Coefficients_Detector9	Dynamic	float32 array (18 values)	IC coefficients for band 4, high gain, detector 9 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B4H_Coefficients_Detector10	Dynamic	float32 array (18 values)	IC coefficients for band 4, high gain, detector 10 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B4H_Coefficients_Detector11	Dynamic	float32 array (18 values)	IC coefficients for band 4, high gain, detector 11 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B4H_Coefficients_Detector12	Dynamic	float32 array (18 values)	IC coefficients for band 4, high gain, detector 12 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B4H_Coefficients_Detector13	Dynamic	float32 array (18 values)	IC coefficients for band 4, high gain, detector 13 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B4H_Coefficients_Detector14	Dynamic	float32 array (18 values)	IC coefficients for band 4, high gain, detector 14 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B4H_Coefficients_Detector15	Dynamic	float32 array (18 values)	IC coefficients for band 4, high gain, detector 15 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B4H_Coefficients_Detector16	Dynamic	float32 array (18 values)	IC coefficients for band 4, high gain, detector 16 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B5H_Coefficients_Detector1	Dynamic	float32 array (18 values)	IC coefficients for band 5, high gain, detector 1 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B5H_Coefficients_Detector2	Dynamic	float32 array (18 values)	IC coefficients for band 5, high gain, detector 2 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B5H_Coefficients_Detector3	Dynamic	float32 array (18 values)	IC coefficients for band 5, high gain, detector 3 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B5H_Coefficients_Detector4	Dynamic	float32 array (18 values)	IC coefficients for band 5, high gain, detector 4 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B5H_Coefficients_Detector5	Dynamic	float32 array (18 values)	IC coefficients for band 5, high gain, detector 5 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B5H_Coefficients_Detector6	Dynamic	float32 array (18 values)	IC coefficients for band 5, high gain, detector 6 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B5H_Coefficients_Detector7	Dynamic	float32 array (18 values)	IC coefficients for band 5, high gain, detector 7 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B5H_Coefficients_Detector8	Dynamic	float32 array (18 values)	IC coefficients for band 5, high gain, detector 8 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B5H_Coefficients_Detector9	Dynamic	float32 array (18 values)	IC coefficients for band 5, high gain, detector 9 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B5H_Coefficients_Detector10	Dynamic	float32 array (18 values)	IC coefficients for band 5, high gain, detector 10 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B5H_Coefficients_Detector11	Dynamic	float32 array (18 values)	IC coefficients for band 5, high gain, detector 11 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B5H_Coefficients_Detector12	Dynamic	float32 array (18 values)	IC coefficients for band 5, high gain, detector 12 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B5H_Coefficients_Detector13	Dynamic	float32 array (18 values)	IC coefficients for band 5, high gain, detector 13 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B5H_Coefficients_Detector14	Dynamic	float32 array (18 values)	IC coefficients for band 5, high gain, detector 14 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B5H_Coefficients_Detector15	Dynamic	float32 array (18 values)	IC coefficients for band 5, high gain, detector 15 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B5H_Coefficients_Detector16	Dynamic	float32 array (18 values)	IC coefficients for band 5, high gain, detector 16 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B7H_Coefficients_Detector1	Dynamic	float32 array (18 values)	IC coefficients for band 7, high gain, detector 1 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B7H_Coefficients_Detector2	Dynamic	float32 array (18 values)	IC coefficients for band 7, high gain, detector 2 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B7H_Coefficients_Detector3	Dynamic	float32 array (18 values)	IC coefficients for band 7, high gain, detector 3 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B7H_Coefficients_Detector4	Dynamic	float32 array (18 values)	IC coefficients for band 7, high gain, detector 4 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B7H_Coefficients_Detector5	Dynamic	float32 array (18 values)	IC coefficients for band 7, high gain, detector 5 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B7H_Coefficients_Detector6	Dynamic	float32 array (18 values)	IC coefficients for band 7, high gain, detector 6 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B7H_Coefficients_Detector7	Dynamic	float32 array (18 values)	IC coefficients for band 7, high gain, detector 7 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B7H_Coefficients_Detector8	Dynamic	float32 array (18 values)	IC coefficients for band 7, high gain, detector 8 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B7H_Coefficients_Detector9	Dynamic	float32 array (18 values)	IC coefficients for band 7, high gain, detector 9 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B7H_Coefficients_Detector10	Dynamic	float32 array (18 values)	IC coefficients for band 7, high gain, detector 10 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B7H_Coefficients_Detector11	Dynamic	float32 array (18 values)	IC coefficients for band 7, high gain, detector 11 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B7H_Coefficients_Detector12	Dynamic	float32 array (18 values)	IC coefficients for band 7, high gain, detector 12 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B7H_Coefficients_Detector13	Dynamic	float32 array (18 values)	IC coefficients for band 7, high gain, detector 13 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B7H_Coefficients_Detector14	Dynamic	float32 array (18 values)	IC coefficients for band 7, high gain, detector 14 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B7H_Coefficients_Detector15	Dynamic	float32 array (18 values)	IC coefficients for band 7, high gain, detector 15 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B7H_Coefficients_Detector16	Dynamic	float32 array (18 values)	IC coefficients for band 7, high gain, detector 16 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector1	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 1 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector2	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 2 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector3	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 3 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector4	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 4 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector5	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 5 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector6	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 6 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector7	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 7 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector8	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 8 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector9	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 9 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector10	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 10 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector11	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 11 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector12	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 12 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector13	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 13 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector14	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 14 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector15	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 15 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector16	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 16 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector17	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 17 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector18	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 18 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector19	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 19 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector 20	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 20 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector 21	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 21 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector 22	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 22 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector 23	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 23 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector 24	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 24 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector 25	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 25 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector 26	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 26 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector 27	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 27 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector 28	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 28 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector 29	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 29 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector 30	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 30 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector 31	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 31 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: Reflective_IC_Coeffs GROUP: Reflect_IC_Coeffs_High	B8H_Coefficients_Detector 32	Dynamic	float32 array (18 values)	IC coefficients for band 8, high gain, detector 32 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	LPSO
Group: FASC_Parameters	FASC_Reference_Detectors	Dynamic	uint8 array (8 values)	FASC algorithm reference detectors, one per band Valid format: NN, where NN = TBS	No	No	LPSO
Group: B6_IC_Coeffs GROUP: B6_IC_Coeffs_Low	B6L_Coefficients_Detector1	Static	float32 array (11 values)	Internal calibrator coefficients for band 6, low gain, detector 1 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	Bl10 thermal vacuum
Group: B6_IC_Coeffs GROUP: B6_IC_Coeffs_Low	B6L_Coefficients_Detector 2	Static	float32 array (11 values)	Internal calibrator coefficients for band 6, low gain, detector 2 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	Bl10 thermal vacuum
Group: B6_IC_Coeffs GROUP: B6_IC_Coeffs_Low	B6L_Coefficients_Detector3	Static	float32 array (11 values)	Internal calibrator coefficients for band 6, low gain, detector 3 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	Bl10 thermal vacuum
Group: B6_IC_Coeffs GROUP: B6_IC_Coeffs_Low	B6L_Coefficients_Detector4	Static	float32 array (11 values)	Internal calibrator coefficients for band 6, low gain, detector 4 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	Bl10 thermal vacuum
Group: B6_IC_Coeffs GROUP: B6_IC_Coeffs_Low	B6L_Coefficients_Detector5	Static	float32 array (11 values)	Internal calibrator coefficients for band 6, low gain, detector 5 Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	Yes	Bl10 thermal vacuum

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: B6_IC_Coeffs GROUP: B6_IC_Coeffs_Low	B6L_Coefficients_Detector6	Static	float32 array (11 values)	Internal calibrator coefficients for band 6, low gain, detector 6 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	Bl10 thermal vacuum
Group: B6_IC_Coeffs GROUP: B6_IC_Coeffs_Low	B6L_Coefficients_Detector7	Static	float32 array (11 values)	Internal calibrator coefficients for band 6, low gain, detector 7 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	Bl10 thermal vacuum
Group: B6_IC_Coeffs GROUP: B6_IC_Coeffs_Low	B6L_Coefficients_Detector8	Static	float32 array (11 values)	Internal calibrator coefficients for band 6, low gain, detector 8 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	Bl10 thermal vacuum
Group: B6_IC_Coeffs GROUP: B6_IC_Coeffs_High	B6H_Coefficients_Detector1	Static	float32 array (11 values)	Internal calibrator coefficients for band 6, high gain, detector 1 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	Bl10 thermal vacuum
Group: B6_IC_Coeffs GROUP: B6_IC_Coeffs_High	B6H_Coefficients_Detector2	Static	float32 array (11 values)	Internal calibrator coefficients for band 6, high gain, detector 2 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	Bl10 thermal vacuum
Group: B6_IC_Coeffs GROUP: B6_IC_Coeffs_High	B6H_Coefficients_Detector3	Static	float32 array (11 values)	Internal calibrator coefficients for band 6, high gain, detector 3 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	Bl10 thermal vacuum
Group: B6_IC_Coeffs GROUP: B6_IC_Coeffs_High	B6H_Coefficients_Detector4	Static	float32 array (11 values)	Internal calibrator coefficients for band 6, high gain, detector 4 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	Bl10 thermal vacuum
Group: B6_IC_Coeffs GROUP: B6_IC_Coeffs_High	B6H_Coefficients_Detector5	Static	float32 array (11 values)	Internal calibrator coefficients for band 6, high gain, detector 5 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	Bl10 thermal vacuum
Group: B6_IC_Coeffs GROUP: B6_IC_Coeffs_High	B6H_Coefficients_Detector6	Static	float32 array (11 values)	Internal calibrator coefficients for band 6, high gain, detector 6 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	Bl10 thermal vacuum
Group: B6_IC_Coeffs GROUP: B6_IC_Coeffs_High	B6H_Coefficients_Detector7	Static	float32 array (11 values)	Internal calibrator coefficients for band 6, high gain, detector 7 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	Bl10 thermal vacuum
Group: B6_IC_Coeffs GROUP: B6_IC_Coeffs_High	B6H_Coefficients_Detector8	Static	float32 array (11 values)	Internal calibrator coefficients for band 6, high gain, detector 8 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	Bl10 thermal vacuum
Group: B6_View_Coeffs	B6_View_Coefficients_Detector1	Static	float32 array (11 values)	View factor coefficients for band 6, detector 1 Valid format: SNNN.NNNNNNNN, where S = + or - and NNN.NNNNNNNN = TBS	No	Yes	LPSO

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: B6_View_Coeffs	B6_View_Coefficients_Detector2	Static	float32 array (11 values)	View factor coefficients for band 6, detector 2 Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	Yes	LPSO
Group: B6_View_Coeffs	B6_View_Coefficients_Detector3	Static	float32 array (11 values)	View factor coefficients for band 6, detector 3 Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	Yes	LPSO
Group: B6_View_Coeffs	B6_View_Coefficients_Detector4	Static	float32 array (11 values)	View factor coefficients for band 6, detector 4 Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	Yes	LPSO
Group: B6_View_Coeffs	B6_View_Coefficients_Detector5	Static	float32 array (11 values)	View factor coefficients for band 6, detector 5 Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	Yes	LPSO
Group: B6_View_Coeffs	B6_View_Coefficients_Detector6	Static	float32 array (11 values)	View factor coefficients for band 6, detector 6 Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	Yes	LPSO
Group: B6_View_Coeffs	B6_View_Coefficients_Detector7	Static	float32 array (11 values)	View factor coefficients for band 6, detector 7 Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	Yes	LPSO
Group: B6_View_Coeffs	B6_View_Coefficients_Detector8	Static	float32 array (11 values)	View factor coefficients for band 6, detector 8 Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	Yes	LPSO
Group: Thermistor_Coeffs	Black_Body_Isolated_Temp	Static	float32 array (65 values) <u> </u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Black_Body_Control_Temp	Static	float32 array (65 values) <u> </u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Cold_FP_Control_Temp	Static	float32 array (65 values) <u> </u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Cold_FP_Monitor_Temp	Static	float32 array (65 values) <u> </u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Cal_Shutter_Flag_Temp	Static	float32 array (65 values) <u> </u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Thermistor_Coeffs	Backup_Shutter_Flag_Temp	Static	float32 array <u>(65 values)</u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Baffle_Heater_Temp	Static	float32 array <u>(65 values)</u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Silicon_FP_Array_Temp	Static	float32 array <u>(65 values)</u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Primary_Mirror_Temp	Static	float32 array <u>(65 values)</u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Secondary_Mirror_Temp	Static	float32 array <u>(65 values)</u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Scan_Line_Corrector_Temp	Static	float32 array <u>(65 values)</u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Baffle3_Tube_Temp	Static	float32 array <u>(65 values)</u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Baffle2_Support_Temp	Static	float32 array <u>(65 values)</u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Cal_Lamp_Housing_Temp	Static	float32 array <u>(65 values)</u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Cal_Shutter_Hub_Temp	Static	float32 array <u>(65 values)</u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Ambient_Preamp_HighCh_Temp	Static	float32 array <u>(65 values)</u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Ambient_Preamp_LowCh_Temp	Static	float32 array <u>(65 values)</u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Thermistor_Coeffs	Postamp_Temp_B4	Static	float32 array <u>(65 values)</u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Cold_Preamp_B7_Temp	Static	float32 array <u>(65 values)</u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Pan_Band_Postamp_Temp	Static	float32 array <u>(65 values)</u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Telescope_Housing_Tem p	Static	float32 array <u>(65 values)</u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Primary_Mirror_Mask_Temp	Static	float32 array <u>(6 values)</u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Secondary_Mirror_Mask_Temps	Static	float32 array <u>(6 values)</u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Telescope_Baseplate	Static	float32 array <u>(6 values)</u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Mux1_Power_Supply_Temp	Static	float32 array <u>(6 values)</u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Mux1_Electronics_Temp	Static	float32 array <u>(6 values)</u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	Mux2_Power_Supply_Temp	Static	float32 array <u>(6 values)</u>	Calibration coefficients for raw data Valid format: SNNN.NNNNNNN, where S = + or – and NNN.NNNNNNN = TBS	No	No	SBRS

Parameter Groups	Parameter Name	Value Type	Data Type	Description	LPS Need	LPG Need	Prelaunch Source
Group: Thermistor_Coeffs	Mux2_Electronics_Temp	Static	float32 array (6 values)	Calibration coefficients for raw data Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	MEM_Heat_Sink_PS1_Temp	Static	float32 array (6 values)	Calibration coefficients for raw data Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	No	SBRS
Group: Thermistor_Coeffs	MEM_Heat_Sink_PS2_Temp	Static	float32 array (6 values)	Calibration coefficients for raw data Valid format: SNNN.NNNNNNNN, where S = + or – and NNN.NNNNNNNN = TBS	No	No	SBRS
Group: Fill_Patterns	Band_Fill_Pattern	Static	uint8 array (2 values)	Fill pattern used by LPS for filling erroneous or missing image data minor frames Valid format: NNN, where NNN = (0, 255) (alternating 0, 255's)	Yes	Yes	LPSO
Group: Engineering_Data	Telemetry_Conversion	Static	float64 array (6 values)	Fifth-order coefficients used to convert PCD telemetry values from counts to engineering units (EUs) EU = A0 + A1(C) + A2(C1) + A3(C3) + A4(C4) + A5(C5) Valid format: NNNNN.NNNNNNNN, where NNNNN.NNNNNNNN = TBS	No	No	LMC
Group: Engineering_Data	Position_Conversion	Static	float64	Coefficient used to convert spacecraft position from counts to EUs (meters) EU = A1 * C Valid format: N.NESNN, where N.NESNN = 2.0E-08	No	No	LMC
Group: Engineering_Data	Velocity_Conversion	Static	float64	Coefficient used to convert spacecraft velocity from counts to meters per milliseconds EU = A1 * C Valid format: N.NESNN, where N.NESNN = 2.0E-28	No	No	LMC

Section 3. CPF ODL

3.1 Introduction

The ODL syntax employs the following conventions:

- Parameter definition is in the form of parameter = value.
- Value can be either a scalar or an array. Array values are enclosed in parentheses and are separated by commas.
- Parameter arrays can and do exist on multiple lines.
- A carriage return <CR> and line feed <LF> end each line in the file.
- Blank spaces and lines are ignored.
- Each line of comments must begin with /* and end with */, including comments embedded on the same line as a parameter definition.
- Quotation marks are required for values that are text strings, including single characters. The exceptions to this rule are the GROUP and END_GROUP identifiers or values, which do not use quotation marks. The first two parameters in the file, Effective_Date_Begin and Effective_Date_End, also do not have quotations. ODL recognizes dates if they follow prescribed formats.
- Case is not significant, but uppercase is used for GROUP names to aid in readability.
- Indentation is not significant but is used for readability.
- The reserve word END concludes the file.

Unavailable parameter values are denoted by TBS (to be supplied). Most will be derived during prelaunch instrument and spacecraft testing and analysis. Formats for TBS numerical parameters are accurate; however, negative signs are not explicitly stated. A data dictionary that declares each parameter's data type and value range must be defined.

3.2 ODL Construct

```
GROUP = FILE_ATTRIBUTES
    Effective_Date_Begin      = YYYY-MM-SS
    Effective_Date_End        = YYYY-MM-SS
    CPF_File_Name             = "L7TCPFyyymdd_yyymdd.nn" L7YYYYDDDIASCAL.Vnn"
| END_GROUP = FILE_ATTRIBUTES

GROUP = EARTH_CONSTANTS
    Ellipsoid_Name            = "WGS84"
    Semi_Major_Axis           = 6378137.000
    Semi_Minor_Axis           = 6356752.314
    Ellipticity                = 0.003352811
    Eccentricity              = 0.0033528107006694380
```

```

Earth_Spin_Rate      = 72.92115855E-06
Gravity_Constant     = 3.986012E14
J2_Earth_Model_Term = 1082.64E-06
END_GROUP = EARTH_CONSTANTS

GROUP = ORBIT_PARAMETERS
WRS_Cycle_Days       = 16
WRS_Cycle_Orbits     = 233
Scenes_Per_Orbit     = 248
Orbital_Period       = 5933.0472
Angular_Momentum     = 53.104278E7
Orbit_Radius          = 7083.437
Orbit_Semimajor_Axis = 7077.900
Orbit_Semiminor_Axis = 7069.580
Orbit_Eccentricity   = 0.00118
Inclination_Angle    = 98.2098
Argument_Of_Perigee  = 90.0
Descending_Node_Row   = 60
Long_Path1_Row60     = -64.6
Descending_Node_Time_Min = "09:45"
Descending_Node_Time_Max = "10:00"
Nodal_Regression_Rate = 0.9856473
END_GROUP = ORBIT_PARAMETERS

GROUP = SCANNER_PARAMETERS
Lines_Per_Scan_30     = 16
Lines_Per_Scan_60     = 8
Lines_Per_Scan_15     = 32
Scans_Per_Scene        = 374
Swath_Angle            = 0.26868
Scan_Rate              = 2.21095
Dwell_Time_30          = 9.6109603
Dwell_Time_60          = 4.8060000
Dwell_Time_15          = 19.2220000
IC_Line_Length_30      = 1100
IC_Line_Length_60      = 550
IC_Line_Length_15      = 2200
Scan_Line_Length_30    = 6320
Scan_Line_Length_60    = 3160
Scan_Line_Length_15    = 12640
Filter_Frequency_30    = 52.02
Filter_Frequency_60    = 26.01
Filter_Frequency_15    = 115.0
IFOV_B1234             = 42.5000
IFOV_B57_along_scan   = 42.5000
IFOV_B57_across_scan  = 42.5000
IFOV_B6                 = 85.0000
IFOV_B8_along_scan    = 18.5000
IFOV_B8_across_scan   = 21.3000
Scan_Period             = 142.92200
Scan_Frequency          = 6.9968
Active_Scan_Time        = 60743.013
Turn_Around_Time        = 10.719
END_GROUP = SCANNER_PARAMETERS

GROUP = SPACECRAFT_PARAMETERS
ADS_Interval           = 2.0
ADS_Roll_Offset         = 0.375
ADS_Yaw_Offset          = 0.875
ADS_Pitch_Offset        = 1.375
Data_Rate               = 84.903
END_GROUP = SPACECRAFT_PARAMETERS

GROUP = MIRROR_PARAMETERS
GROUP = ANGLES_SME1_SAM
Forward_Along_SME1_SAM = (N.NNNNNEN, N.NNNNNEN,.....) /* 6 values TBS by SBRS */
Forward_Cross_SME1_SAM = (N.NNNNNEN, N.NNNNNEN,.....) /* 6 values TBS by SBRS */
Forward_Angle1_SME1_SAM = 67171.0
Forward_Angle2_SME1_SAM = 67159.0
Reverse_Along_SME1_SAM = (N.NNNNNEN, N.NNNNNEN,.....) /* TBS by SBRS */
Reverse_Cross_SME1_SAM = (N.NNNNNEN, N.NNNNNEN,.....) /* TBS by SBRS */
Reverse_Angle1_SME1_SAM = 67159.0

```

```

Reverse_angle2_SME1_SAM = 67171.0
END_GROUP = ANGLES_SME1_SAM
GROUP = ANGLES_SME2_SAM
Forward_Along_SME2_SAM      = N.NNNNEN, N.NNNNEN,.....) /* 6 values TBS by SBRS */
Forward_Cross_SME2_SAM     = N.NNNNEN, N.NNNNEN,.....) /* 6 values TBS by SBRS */
Forward_Angle1_SME2_SAM    = 67182.0
Forward_Angle2_SME2_SAM    = 67160.0
Reverse_Along_SME2_SAM     = (N.NNNNEN, N.NNNNEN,.....) /* 6 values TBS by SBRS */
Reverse_Cross_SME2_SAM    = (N.NNNNEN, N.NNNNEN,.....) /* 6 values TBS by SBRS */
Reverse_Angle1_SME2_SAM   = 67160.0
Reverse_Angle2_SME2_SAM   = 67182.0
END_GROUP = ANGLES_SME2_SAM
GROUP = ANGLES_SME1_BUMP
Forward_Along_SME1_Bump    = (N.NNNNEN, N.NNNNEN,.....) /* 6 values TBS by SBRS */
Forward_Cross_SME1_Bump   = (N.NNNNEN, N.NNNNEN,.....) /* 6 values TBS by SBRS */
Forward_Angle1_SME1_Bump  = 67171.0
Forward_Angle2_SME1_Bump  = 67159.0
Reverse_Along_SME1_Bump   = (N.NNNNEN, N.NNNNEN,.....) /* 6 values TBS by SBRS */
Reverse_Cross_SME1_Bump  = (N.NNNNEN, N.NNNNEN,.....) /* 6 values TBS by SBRS */
Reverse_Angle1_SME1_Bump = 67159.0
Reverse_Angle2_SME1_Bump = 67171.0
END_GROUP = ANGLES_SME1_BUMP
GROUP = ANGLES_SME2_BUMP
Forward_Along_SME2_Bump    = (N.NNNNEN, N.NNNNEN,.....) /* 6 values TBS by SBRS */
Forward_Cross_SME2_Bump   = (N.NNNNEN, N.NNNNEN,.....) /* 6 values TBS by SBRS */
Forward_Angle1_SME2_Bump  = 67182.0
Forward_Angle2_SME2_Bump  = 67162.0
Reverse_Along_SME2_Bump   = (N.NNNNEN, N.NNNNEN,.....) /* 6 values TBS by SBRS */
Reverse_Cross_SME2_Bump  = (N.NNNNEN, N.NNNNEN,.....) /* 6 values TBS by SBRS */
Reverse_Angle1_SME2_Bump = 67160.0
Reverse_Angle2_SME2_Bump = 67182.0
END_GROUP = ANGLES_SME2_BUMP
Error_Conversion_Factor = 0.18845E-6
END_GROUP = MIRROR_PARAMETERS

GROUP = SCAN_LINE_CORRECTOR
Primary_Angular_Velocity = 0.00966
Secondary_Angular_Velocity = 0.00960
Primary_Corrector_Motion = (N.NNNNN, N.NNNNN,.....) /* 6 values TBS by SBRS */
Secondary_Corrector_Motion = (N.NNNNN, N.NNNNN,.....) /* 6 values TBS by SBRS */
END_GROUP = SCAN_LINE_CORRECTOR

GROUP = FOCAL_PLANE_PARAMETERS
GROUP = BAND_OFFSETS
Along_Scan_Band_Offsets = (NNNN.NNN, NNNN.NNN,.....) /* 8 values TBS by SBRS */
Across_Scan_Band_Offsets = (NNNN.NNN, NNNN.NNN,.....) /* 8 values TBS by SBRS */
Forward_Focal_Plane_Offsets = (NNNN.NNN, NNNN.NNN,.....) /* 8 values TBS by SBRS */
Reverse_Focal_Plane_Offsets = (NNNN.NNN, NNNN.NNN,.....) /* 8 values TBS by SBRS */
END_GROUP = BAND_OFFSETS
GROUP = DETECTOR_OFFSETS
Forward_Along_Scan_DO_B1 = (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */
Reverse_Along_Scan_DO_B1 = (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */
Forward_Along_Scan_DO_B2 = (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */
Reverse_Along_Scan_DO_B2 = (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */
Forward_Along_Scan_DO_B3 = (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */
Reverse_Along_Scan_DO_B3 = (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */
Forward_Along_Scan_DO_B4 = (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */
Reverse_Along_Scan_DO_B4 = (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */
Forward_Along_Scan_DO_B5 = (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */
Reverse_Along_Scan_DO_B5 = (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */
Forward_Along_Scan_DO_B6 = (NNN.NNN, NNN.NNN,.....) /* 8 values TBS by SBRS */
Reverse_Along_Scan_DO_B6 = (NNN.NNN, NNN.NNN,.....) /* 8 values TBS by SBRS */
Forward_Along_Scan_DO_B7 = (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */
Reverse_Along_Scan_DO_B7 = (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */
Forward_Along_Scan_DO_B8 = (NNN.NNN, NNN.NNN,.....) /* 32 values TBS by SBRS */
Reverse_Along_Scan_DO_B8 = (NNN.NNN, NNN.NNN,.....) /* 32 values TBS by SBRS */
Forward_Across_Scan_DO_B1 = (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */
Reverse_Across_Scan_DO_B1 = (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */
Forward_Across_Scan_DO_B2 = (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */
Reverse_Across_Scan_DO_B2 = (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */
Forward_Across_Scan_DO_B3 = (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */
Reverse_Across_Scan_DO_B3 = (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */

```

```

Forward_Across_Scan_DO_B4= (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */
Reverse_Across_Scan_DO_B4= (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */
Forward_Across_Scan_DO_B5= (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */
Reverse_Across_Scan_DO_B5= (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */
Forward_Across_Scan_DO_B6= (NNN.NNN, NNN.NNN,.....) /* 8 values TBS by SBRS */
Reverse_Across_Scan_DO_B6= (NNN.NNN, NNN.NNN,.....) /* 8 values TBS by SBRS */
Forward_Across_Scan_DO_B7= (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */
Reverse_Across_Scan_DO_B7= (NNN.NNN, NNN.NNN,.....) /* 16 values TBS by SBRS */
Forward_Across_Scan_DO_B8= (NNN.NNN, NNN.NNN,.....) /* 32 values TBS by SBRS */
Reverse_Across_Scan_DO_B8= (NNN.NNN, NNN.NNN,.....) /* 32 values TBS by SBRS */
END_GROUP = DETECTOR_OFFSETS
GROUP = ODD_EVEN_OFFSETS
    Forward_Even_Detector_Shift = (NNN.NNN, NNN.NNN,.....) /* 8 values TBS by SBRS */
    Forward_Odd_Detector_Shift = (NNN.NNN, NNN.NNN,.....) /* 8 values TBS by SBRS */
    Reverse_Even_Detector_Shift = (NNN.NNN, NNN.NNN,.....) /* 8 values TBS by SBRS */
    Reverse_Odd_Detector_Shift = (NNN.NNN, NNN.NNN,.....) /* 8 values TBS by SBRS */
END_GROUP = ODD_EVEN_OFFSETS
END_GROUP = FOCAL_PLANE_PARAMETERS

GROUP = ATTITUDE_PARAMETERS
    Gyro_To_Attitude_Matrix = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 9 values TBS by SBRS */
    ADSA_To_ETM+_Matrix = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 9 values TBS by SBRS */
    Attitude_To_ETM+_Matrix = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 9 values TBS by SBRS */
    Spacecraft_Roll_Bias = N.NNNNNNNN /* TBS by LMC */
    Spacecraft_Pitch_Bias = N.NNNNNNNN /* TBS by LMC */
    Spacecraft_Yaw_Bias = N.NNNNNNNN /* TBS by LMC */
END_GROUP = ATTITUDE_PARAMETERS

GROUP = TIME_PARAMETERS
    Scan_Time = 60743.0
    Forward_First_Half_Time = 30371.4
    Forward_Second_Half_Time = 30371.6
    Reverse_First_Half_Time = 30371.6
    Reverse_Second_Half_Time = 30371.4
END_GROUP = TIME_PARAMETERS

GROUP = TRANSFER_FUNCTION
GROUP = IMU
    Fn = 2.201 /* 1 value TBS by SBRS */
    Zeta = 0.7022 /* 1 value TBS by SBRS */
    Tau = 1.4468E-3 /* 1 value TBS by SBRS */
    P = -3.259E-3 /* 1 value TBS by SBRS */
    Ak = 1.00121 /* 1 value TBS by SBRS */
END_GROUP = IMU
GROUP = ADS
    ADS_num = (N.NNNNEN, N.NNNNEN,.....) /* 18 values TBS by SBRS */
    ADS_den = (N.NNNNEN, N.NNNNEN,.....) /* 18 values TBS by SBRS */
    ADS_num_temp = (N.NNNNEN, N.NNNNEN,.....) /* 18 values TBS by SBRS */
    ADS_den_temp = (N.NNNNEN, N.NNNNEN,.....) /* 18 values TBS by SBRS */
END_GROUP = ADS
GROUP = PREFILTER
    ADSPre_W = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 5 values TBS by SBRS */
    ADSPre_H = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 5 values TBS by SBRS */
    ADSPre_T = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 5 values TBS by SBRS */
END_GROUP = PREFILTER
END_GROUP = TRANSFER_FUNCTION

GROUP = UT1_TIME_PARAMETERS
    UT1_Year = (YYYY, YYYY,.....) /* 180 values TBS NEOS */
    UT1_Month = ("MMM", "MMM",.....) /* 180 values TBS NEOS */
    UT1_Day = (NN,NN,.....) /* 180 values TBS NEOS */
    UT1_Modified_Julian = (NNNNNN,NNNNNN,.....) /* 180 values TBS NEOS */
    UT1_X = (N.NNNNN, N.NNNNN,.....) /* 180 values TBS NEOS */
    UT1_Y = (N.NNNNN, N.NNNNN,.....) /* 180 values TBS NEOS */
    UT1_UTC = (N.NNNNN, N.NNNNN,.....) /* 180 values TBS NEOS */
END_GROUP = UT1_TIME_PARAMETERS

GROUP = DETECTOR_STATUS
    Status_Band1 = (NNNNN, NNNNN,.....) /* 16 values TBS by SBRS */
    Status_Band2 = (NNNNN, NNNNN,.....) /* 16 values TBS by SBRS */
    Status_Band3 = (NNNNN, NNNNN,.....) /* 16 values TBS by SBRS */
    Status_Band4 = (NNNNN, NNNNN,.....) /* 16 values TBS by SBRS */

```

```

Status_Band5      = (NNNNN, NNNNN,.....) /* 16 values TBS by SBRS */
Status_Band6      = (NNNNN, NNNNN,.....) /* 8 values TBS by SBRS */
Status_Band7      = (NNNNN, NNNNN,.....) /* 16 values TBS by SBRS */
Status_Band8      = (NNNNN, NNNNN,.....) /* 32 values TBS by SBRS */
END_GROUP = DETECTOR_STATUS

GROUP = DETECTOR_GAINS
GROUP = DETECTOR_GAINS_LOW
B1L_Prelaunch    = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B1L_Postlaunch   = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B1L_Current      = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B2L_Prelaunch    = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B2L_Postlaunch   = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B2L_Current      = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B3L_Prelaunch    = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B3L_Postlaunch   = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B3L_Current      = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B4L_Prelaunch    = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B4L_Postlaunch   = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B4L_Current      = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B5L_Prelaunch    = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B5L_Postlaunch   = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B5L_Current      = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B6L_Prelaunch    = (NNN.NNNNN, NNN.NNNNN,.....) /* 8 values TBS by SBRS */
B6L_Postlaunch   = (NNN.NNNNN, NNN.NNNNN,.....) /* 8 values TBS by SBRS */
B6L_Current      = (NNN.NNNNN, NNN.NNNNN,.....) /* 8 values TBS by SBRS */
B7L_Prelaunch    = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B7L_Postlaunch   = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B7L_Current      = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B8L_Prelaunch    = (NNN.NNNNN, NNN.NNNNN,.....) /* 32 values TBS by SBRS */
B8L_Postlaunch   = (NNN.NNNNN, NNN.NNNNN,.....) /* 32 values TBS by SBRS */
B8L_Current      = (NNN.NNNNN, NNN.NNNNN,.....) /* 32 values TBS by SBRS */
END_GROUP = DETECTOR_GAINS_LOW
GROUP = DETECTOR_GAINS_HIGH
B1H_Prelaunch    = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B1H_Postlaunch   = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B1H_Current      = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B2H_Prelaunch    = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B2H_Postlaunch   = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B2H_Current      = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B3H_Prelaunch    = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B3H_Postlaunch   = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B3H_Current      = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B4H_Prelaunch    = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B4H_Postlaunch   = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B4H_Current      = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B5H_Prelaunch    = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B5H_Postlaunch   = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B5H_Current      = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B6H_Prelaunch    = (NNN.NNNNN, NNN.NNNNN,.....) /* 8 values TBS by SBRS */
B6H_Postlaunch   = (NNN.NNNNN, NNN.NNNNN,.....) /* 8 values TBS by SBRS */
B6H_Current      = (NNN.NNNNN, NNN.NNNNN,.....) /* 8 values TBS by SBRS */
B7H_Prelaunch    = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B7H_Postlaunch   = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B7H_Current      = (NNN.NNNNN, NNN.NNNNN,.....) /* 16 values TBS by SBRS */
B8H_Prelaunch    = (NNN.NNNNN, NNN.NNNNN,.....) /* 32 values TBS by SBRS */
B8H_Postlaunch   = (NNN.NNNNN, NNN.NNNNN,.....) /* 32 values TBS by SBRS */
B8H_Current      = (NNN.NNNNN, NNN.NNNNN,.....) /* 32 values TBS by SBRS */
END_GROUP = DETECTOR_GAINS_HIGH
GROUP = DETECTOR_GAINS

GROUP = BIAS LOCATIONS
Forward_Bias_Location_30= NNN          /* TBS by LPSO */
Reverse_Bias_Length_30 = NNN           /* TBS by LPSO */
Forward_Bias_Location_60= NNN          /* TBS by LPSO */
Reverse_Bias_Length_60 = NNN           /* TBS by LPSO */
Forward_Bias_Location_15= NNN          /* TBS by LPSO */
Reverse_Bias_Length_15 = NNN           /* TBS by LPSO */
END_GROUP = BIAS LOCATIONS

GROUP = DETECTOR_BIASES_B6
GROUP = DETECTOR_BIASES_B6_LOW

```

```

B6L_Bias_Prelaunch = (NNN.NNNN, NNN.NNNN,.....) /* 8 values TBS by SBRS */
B6L_Bias_PostLaunch = (NNN.NNNN, NNN.NNNN,.....) /* 8 values TBS by SBRS */
B6L_Bias_Current = (NNN.NNNN, NNN.NNNN,.....) /* 8 values TBS by SBRS */
END_GROUP = DETECTOR_BIASES_B6_LOW
GROUP = DETECTOR_BIASES_B6_HIGH
B6H_Bias_Prelaunch = (NNN.NNNN, NNN.NNNN,.....) /* 8 values TBS by SBRS */
B6H_Bias_PostLaunch = (NNN.NNNN, NNN.NNNN,.....) /* 8 values TBS by SBRS */
B6H_Bias_Current = (NNN.NNNN, NNN.NNNN,.....) /* 8 values TBS by SBRS */
END_GROUP = DETECTOR_BIASES_B6_HIGH
END_GROUP = DETECTOR_BIASES_B6

GROUP = ACCA_BIASES
GROUP = ACCA_BIASES_LOW
B1L_ACCA_Bias = (NNN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
B2L_ACCA_Bias = (NNN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
B3L_ACCA_Bias = (NNN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
B4L_ACCA_Bias = (NNN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
B5L_ACCA_Bias = (NNN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
B6L_ACCA_Bias = (NNN.NNNN, NN.NNNN,.....) /* 8 values TBS by LPSO */
B7L_ACCA_Bias = (NNN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
B8L_ACCA_Bias = (NNN.NNNN, NN.NNNN,.....) /* 32 values TBS by LPSO */
END_GROUP = ACCA_BIASES_LOW
GROUP = ACCA_BIASES_HIGH
B1H_ACCA_Bias = (NNN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
B2H_ACCA_Bias = (NNN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
B3H_ACCA_Bias = (NNN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
B4H_ACCA_Bias = (NNN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
B5H_ACCA_Bias = (NNN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
B6H_ACCA_Bias = (NNN.NNNN, NN.NNNN,.....) /* 8 values TBS by LPSO */
B7H_ACCA_Bias = (NNN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
B8H_ACCA_Bias = (NNN.NNNN, NN.NNNN,.....) /* 32 values TBS by LPSO */
END_GROUP = ACCA_BIASES_HIGH
END_GROUP = ACCA_BIASES

GROUP = ACCA_THRESHOLDS
Thresh_B3 = 0.3000
Thresh_B3_Lower = 0.06
Thresh_B56_High = 225.000
Thresh_B56_Low = 210.000
Thresh_B6 = 300.000
Thresh_B45_Ratio = 1.0750
Thresh_B42_Ratio = 2.0000
Thresh_B43_Ratio = 2.0000
Thresh_NDSI_Max = 0.7000
Thresh_NDSI_Min = -0.2500
Thresh_NDSI_Snow = 0.8000
Cloud_Percent_Min = 0.4000
Desert_Index = 0.5000
Thresh_Snow_Percent = 1.000
Thermal_Effect_High = 40.000
Thermal_Effect_Low = 30.000
B6max_Maxthresh_Diff = 2.000
END_GROUP = ACCA_THRESHOLDS

GROUP = SOLAR_SPECTRAL_IRRADIANCES
B1_Solar_Irradiance = 1957.00
B2_Solar_Irradiance = 1829.00
B3_Solar_Irradiance = 1557.00
B4_Solar_Irradiance = 1047.00
B5_Solar_Irradiance = 219.30
B7_Solar_Irradiance = 74.52
B8_Solar_Irradiance = (NNNN.NNN) /* 1 values TBS by LPSO */
END_GROUP = SOLAR_SPECTRAL_IRRADIANCES

GROUP = THERMAL_CONSTANTS
K1_Constant = 607.76
K2_Constant = 12605.60

```

| END_GROUP = THERMAL_CONSTANTS

```

GROUP = SCALING_PARAMETERS
GROUP = SCALING_PARAMETERS_LOW
    B1L_Lmin_Lmax      = (NN.NNNN, NN.NNNN) /* 2 values TBS by LPSO */
    B2L_Lmin_Lmax      = (NN.NNNN, NN.NNNN) /* 2 values TBS by LPSO */
    B3L_Lmin_Lmax      = (NN.NNNN, NN.NNNN) /* 2 values TBS by LPSO */
    B4L_Lmin_Lmax      = (NN.NNNN, NN.NNNN) /* 2 values TBS by LPSO */
    B5L_Lmin_Lmax      = (NN.NNNN, NN.NNNN) /* 2 values TBS by LPSO */
    B6L_Lmin_Lmax      = (NN.NNNN, NN.NNNN) /* 2 values TBS by LPSO */
    B7L_Lmin_Lmax      = (NN.NNNN, NN.NNNN) /* 2 values TBS by LPSO */
    B8L_Lmin_Lmax      = (NN.NNNN, NN.NNNN) /* 2 values TBS by LPSO */
END_GROUP = SCALING_PARAMETERS_LOW
GROUP = SCALING_PARAMETERS_HIGH
    B1H_Lmin_Lmax      = (NN.NNNN, NN.NNNN) /* 2 values TBS by LPSO */
    B2H_Lmin_Lmax      = (NN.NNNN, NN.NNNN) /* 2 values TBS by LPSO */
    B3H_Lmin_Lmax      = (NN.NNNN, NN.NNNN) /* 2 values TBS by LPSO */
    B4H_Lmin_Lmax      = (NN.NNNN, NN.NNNN) /* 2 values TBS by LPSO */
    B5H_Lmin_Lmax      = (NN.NNNN, NN.NNNN) /* 2 values TBS by LPSO */
    B6H_Lmin_Lmax      = (NN.NNNN, NN.NNNN) /* 2 values TBS by LPSO */
    B7H_Lmin_Lmax      = (NN.NNNN, NN.NNNN) /* 2 values TBS by LPSO */
    B8H_Lmin_Lmax      = (NN.NNNN, NN.NNNN) /* 2 values TBS by LPSO */
END_GROUP = SCALING_PARAMETERS_HIGH
END_GROUP = SCALING_PARAMETERS

GROUP = MTF_COMPENSATION
    B1_weights_along   = (NN.NNNN, NN.NNNN,...) /* 5 values TBS by LPSO */
    B1_weights_across  = (NN.NNNN, NN.NNNN,...) /* 5 values TBS by LPSO */
    B2_weights_along   = (NN.NNNN, NN.NNNN,...) /* 5 values TBS by LPSO */
    B2_weights_across  = (NN.NNNN, NN.NNNN,...) /* 5 values TBS by LPSO */
    B3_weights_along   = (NN.NNNN, NN.NNNN,...) /* 5 values TBS by LPSO */
    B3_weights_across  = (NN.NNNN, NN.NNNN,...) /* 5 values TBS by LPSO */
    B4_weights_along   = (NN.NNNN, NN.NNNN,...) /* 5 values TBS by LPSO */
    B4_weights_across  = (NN.NNNN, NN.NNNN,...) /* 5 values TBS by LPSO */
    B5_weights_along   = (NN.NNNN, NN.NNNN,...) /* 5 values TBS by LPSO */
    B5_weights_across  = (NN.NNNN, NN.NNNN,...) /* 5 values TBS by LPSO */
    B6_weights_along   = (NN.NNNN, NN.NNNN,...) /* 5 values TBS by LPSO */
    B6_weights_across  = (NN.NNNN, NN.NNNN,...) /* 5 values TBS by LPSO */
    B7_weights_along   = (NN.NNNN, NN.NNNN,...) /* 5 values TBS by LPSO */
    B7_weights_across  = (NN.NNNN, NN.NNNN,...) /* 5 values TBS by LPSO */
    B8_weights_along   = (NN.NNNN, NN.NNNN,...) /* 5 values TBS by LPSO */
    B8_weights_across  = (NN.NNNN, NN.NNNN,...) /* 5 values TBS by LPSO */
END_GROUP = MTF_COMPENSATION

GROUP = MEMORY_EFFECT
GROUP = ME_MAGNITUDES
    B1_ME_Magnitude    = (NNN.NNNNNNNN, NNN.NNNNNNNN,...) /* 16 values TBS by LPSO */
    B2_ME_Magnitude    = (NNN.NNNNNNNN, NNN.NNNNNNNN,...) /* 16 values TBS by LPSO */
    B3_ME_Magnitude    = (NNN.NNNNNNNN, NNN.NNNNNNNN,...) /* 16 values TBS by LPSO */
    B4_ME_Magnitude    = (NNN.NNNNNNNN, NNN.NNNNNNNN,...) /* 16 values TBS by LPSO */
    B5_ME_Magnitude    = (NNN.NNNNNNNN, NNN.NNNNNNNN,...) /* 16 values TBS by LPSO */
    B6_ME_Magnitude    = (NNN.NNNNNNNN, NNN.NNNNNNNN,...) /* 8 values TBS by LPSO */
    B7_ME_Magnitude    = (NNN.NNNNNNNN, NNN.NNNNNNNN,...) /* 16 values TBS by LPSO */
    B8_ME_Magnitude    = (NNN.NNNNNNNN, NNN.NNNNNNNN,...) /* 32 values TBS by LPSO */
END_GROUP = ME_EFFECT_MAGNITUDES
GROUP = ME_TIME_CONSTANTS
    B1_ME_Time_Constant = (NNNN.NNNNNNNN, NNNN.NNNNNNNN,...) /* 16 values TBS by LPSO */
    B2_ME_Time_Constant = (NNNN.NNNNNNNN, NNNN.NNNNNNNN,...) /* 16 values TBS by LPSO */
    B3_ME_Time_Constant = (NNNN.NNNNNNNN, NNNN.NNNNNNNN,...) /* 16 values TBS by LPSO */
    B4_ME_Time_Constant = (NNNN.NNNNNNNN, NNNN.NNNNNNNN,...) /* 16 values TBS by LPSO */
    B5_ME_Time_Constant = (NNNN.NNNNNNNN, NNNN.NNNNNNNN,...) /* 16 values TBS by LPSO */
    B6_ME_Time_Constant = (NNNN.NNNNNNNN, NNNN.NNNNNNNN,...) /* 8 values TBS by LPSO */
    B7_ME_Time_Constant = (NNNN.NNNNNNNN, NNNN.NNNNNNNN,...) /* 16 values TBS by LPSO */
    B8_ME_Time_Constant = (NNNN.NNNNNNNN, NNNN.NNNNNNNN,...) /* 32 values TBS by LPSO */
END_GROUP = ME_TIME_CONSTANTS
END_GROUP = MEMORY_EFFECT

GROUP = GHOST_PULSE
    Ghost_Pulse_Endpoints = (NNNN.NNNN, NNNN.NNNN) /* 2 values TBS by LPSO */
END_GROUP = GHOST_PULSE

```

```

GROUP = SCAN_CORRELATED_SHIFT
SCS_Reference_Detectors= (NN, NN,.....) /* 8 values TBS by LPSO */
GROUP = SCS_LOW
B1L_SCS_Magnitudes      = (NNN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B2L_SCS_Magnitudes      = (NNN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B3L_SCS_Magnitudes      = (NNN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B4L_SCS_Magnitudes      = (NNN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B5L_SCS_Magnitudes      = (NNN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B7L_SCS_Magnitudes      = (NNN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B8L_SCS_Magnitudes      = (NNN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
_____
END_GROUP = SCS_LOW
GROUP = SCS_HIGH
B1H_SCS_Magnitudes      = (NNN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B2H_SCS_Magnitudes      = (NNN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B3H_SCS_Magnitudes      = (NNN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B4H_SCS_Magnitudes      = (NNN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B5H_SCS_Magnitudes      = (NNN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B7H_SCS_Magnitudes      = (NNN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B8H_SCS_Magnitudes      = (NNN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
_____
END_GROUP = SCS_HIGH
END_GROUP = SCAN_CORRELATED_SHIFT

GROUP = STRIPPING
GROUP = STRIPPING_FLAG_LOW
Correction_Reference_B1_Low = N /* 1 value TBS by LPSO */
Correction_Reference_B2_Low = N /* 1 value TBS by LPSO */
Correction_Reference_B3_Low = N /* 1 value TBS by LPSO */
Correction_Reference_B4_Low = N /* 1 value TBS by LPSO */
Correction_Reference_B5_Low = N /* 1 value TBS by LPSO */
Correction_Reference_B6_Low = N /* 1 value TBS by LPSO */
Correction_Reference_B7_Low = N /* 1 value TBS by LPSO */
Correction_Reference_B8_Low = N /* 1 value TBS by LPSO */
END_GROUP = STRIPPING_FLAG_LOW
GROUP = STRIPPING_FLAG_HIGH
Correction_Reference_B1_High= N /* 1 value TBS by LPSO */
Correction_Reference_B2_High= N /* 1 value TBS by LPSO */
Correction_Reference_B3_High= N /* 1 value TBS by LPSO */
Correction_Reference_B4_High= N /* 1 value TBS by LPSO */
Correction_Reference_B5_High= N /* 1 value TBS by LPSO */
Correction_Reference_B6_High= N /* 1 value TBS by LPSO */
Correction_Reference_B7_High= N /* 1 value TBS by LPSO */
Correction_Reference_B8_High= N /* 1 value TBS by LPSO */
END_GROUP = STRIPPING_FLAG_HIGH
END_GROUP = STRIPPING

GROUP = HISTOGRAM
GROUP = DETECTOR_NOISE
GROUP = DETECTOR_NOISE_LOW
Detector_Noise_Level_B1_Low= (NN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
Detector_Noise_Level_B2_Low= (NN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
Detector_Noise_Level_B3_Low= (NN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
Detector_Noise_Level_B4_Low= (NN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
Detector_Noise_Level_B5_Low= (NN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
Detector_Noise_Level_B6_Low= (NN.NNNN, NN.NNNN,.....) /* 8 values TBS by LPSO */
Detector_Noise_Level_B7_Low= (NN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
Detector_Noise_Level_B8_Low= (NN.NNNN, NN.NNNN,.....) /* 32 values TBS by LPSO */
END_GROUP = DETECTOR_NOISE_LOW
GROUP = DETECTOR_NOISE_HIGH
Detector_Noise_Level_B1_high= (NN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
Detector_Noise_Level_B2_high= (NN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
Detector_Noise_Level_B3_high= (NN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
Detector_Noise_Level_B4_high= (NN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
Detector_Noise_Level_B5_high= (NN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
Detector_Noise_Level_B6_high= (NN.NNNN, NN.NNNN,.....) /* 8 values TBS by LPSO */
Detector_Noise_Level_B7_high= (NN.NNNN, NN.NNNN,.....) /* 16 values TBS by LPSO */
Detector_Noise_Level_B8_high= (NN.NNNN, NN.NNNN,.....) /* 32 values TBS by LPSO */
END_GROUP = DETECTOR_NOISE_HIGH
END_GROUP = DETECTOR_NOISE
GROUP = REFERENCE_DETECTORS
Reference_Detector_B1 = NN/* 1 value TBS by LPSO */

```

```

Reference_Detector_B2 = NN/* 1 value TBS by LPSO */
Reference_Detector_B3 = NN/* 1 value TBS by LPSO */
Reference_Detector_B4 = NN/* 1 value TBS by LPSO */
Reference_Detector_B5 = NN/* 1 value TBS by LPSO */
Reference_Detector_B6 = NN/* 1 value TBS by LPSO */
Reference_Detector_B7 = NN/* 1 value TBS by LPSO */
Reference_Detector_B8 = NN/* 1 value TBS by LPSO */
END_GROUP = REFERENCE_DETECTORS
GROUP = SATURATION_THRESHOLDS
Saturation_Bin_Threshold_B1 = NNNNN /* 1 value TBS by LPSO */
Saturation_Bin_Threshold_B2 = NNNNN /* 1 value TBS by LPSO */
Saturation_Bin_Threshold_B3 = NNNNN /* 1 value TBS by LPSO */
Saturation_Bin_Threshold_B4 = NNNNN /* 1 value TBS by LPSO */
Saturation_Bin_Threshold_B5 = NNNNN /* 1 value TBS by LPSO */
Saturation_Bin_Threshold_B6 = NNNNN /* 1 value TBS by LPSO */
Saturation_Bin_Threshold_B7 = NNNNN /* 1 value TBS by LPSO */
Saturation_Bin_Threshold_B8 = NNNNN /* 1 value TBS by LPSO */
END_GROUP = SATURATION_THRESHOLDS
GROUP = ADJACENT_BINS
GROUP = BIN_NUMBER
Adjacent_Bin_Number_B1 = 2
Adjacent_Bin_Number_B2 = 2
Adjacent_Bin_Number_B3 = 2
Adjacent_Bin_Number_B4 = 2
Adjacent_Bin_Number_B5 = 2
Adjacent_Bin_Number_B6 = 2
Adjacent_Bin_Number_B7 = 2
Adjacent_Bin_Number_B8 = 2
END_GROUP = BIN_NUMBER
GROUP = BIN_THRESHOLD
Adjacent_Bin_Threshold_B1 = 10
Adjacent_Bin_Threshold_B2 = 10
Adjacent_Bin_Threshold_B3 = 10
Adjacent_Bin_Threshold_B4 = 10
Adjacent_Bin_Threshold_B5 = 10
Adjacent_Bin_Threshold_B6 = 10
Adjacent_Bin_Threshold_B7 = 10
Adjacent_Bin_Threshold_B8 = 10
END_GROUP = BIN_THRESHOLD
END_GROUP = ADJACENT_BINS
GROUP = STARTING_PIXEL
Start_pixel_B1 = NNN /* 1 value TBS by LPSO */
Start_pixel_B2 = NNN /* 1 value TBS by LPSO */
Start_pixel_B3 = NNN /* 1 value TBS by LPSO */
Start_pixel_B4 = NNN /* 1 value TBS by LPSO */
Start_pixel_B5 = NNN /* 1 value TBS by LPSO */
Start_pixel_B6 = NNN /* 1 value TBS by LPSO */
Start_pixel_B7 = NNN /* 1 value TBS by LPSO */
Start_pixel_B8 = NNN /* 1 value TBS by LPSO */
END_GROUP = STARTING_PIXEL
GROUP = WINDOW_WIDTH
Window_Samples_B1 = NNN /* 1 value TBS by LPSO */
Window_Samples_B2 = NNN /* 1 value TBS by LPSO */
Window_Samples_B3 = NNN /* 1 value TBS by LPSO */
Window_Samples_B4 = NNN /* 1 value TBS by LPSO */
Window_Samples_B5 = NNN /* 1 value TBS by LPSO */
Window_Samples_B6 = NNN /* 1 value TBS by LPSO */
Window_Samples_B7 = NNN /* 1 value TBS by LPSO */
Window_Samples_B8 = NNN /* 1 value TBS by LPSO */
END_GROUP = WINDOW_WIDTH
GROUP = WINDOW_LENGTH
Window_Scans_B1 = NNN /* 1 value TBS by LPSO */
Window_Scans_B2 = NNN /* 1 value TBS by LPSO */
Window_Scans_B3 = NNN /* 1 value TBS by LPSO */
Window_Scans_B4 = NNN /* 1 value TBS by LPSO */
Window_Scans_B5 = NNN /* 1 value TBS by LPSO */
Window_Scans_B6 = NNN /* 1 value TBS by LPSO */
Window_Scans_B7 = NNN /* 1 value TBS by LPSO */
Window_Scans_B8 = NNN /* 1 value TBS by LPSO */
END_GROUP = WINDOW_LENGTH
GROUP = OVERLAPPING_SCANS
Overlap_Scans_B1 = NNN /* 1 value TBS by LPSO */

```

```

Overlap_Scans_B2      = NNN      /* 1 value TBS by LPSO */
Overlap_Scans_B3      = NNN      /* 1 value TBS by LPSO */
Overlap_Scans_B4      = NNN      /* 1 value TBS by LPSO */
Overlap_Scans_B5      = NNN      /* 1 value TBS by LPSO */
Overlap_Scans_B6      = NNN      /* 1 value TBS by LPSO */
Overlap_Scans_B7      = NNN      /* 1 value TBS by LPSO */
Overlap_Scans_B8      = NNN      /* 1 value TBS by LPSO */
GROUP = OVERLAPPING_SCANS
END_GROUP = HISTOGRAM

GROUP = IMPULSE_NOISE
Median_Filter_Width   = 2
GROUP = IN_STANDARD_DEVIATION
B1L_Standard_Deviation = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B2L_Standard_Deviation = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B3L_Standard_Deviation = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B4L_Standard_Deviation = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B5L_Standard_Deviation = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B6L_Standard_Deviation = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 8 values TBS by LPSO */
B7L_Standard_Deviation = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B8L_Standard_Deviation = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 32 values TBS by LPSO */
B1H_Standard_Deviation = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B2H_Standard_Deviation = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B3H_Standard_Deviation = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B4H_Standard_Deviation = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B5H_Standard_Deviation = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B6H_Standard_Deviation = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 8 values TBS by LPSO */
B7H_Standard_Deviation = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B8H_Standard_Deviation = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 32 values TBS by LPSO */
END_GROUP = IN_STANDARD_DEVIATION
GROUP = IN_THRESHOLD
B1L_Threshold          = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B2L_Threshold          = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B3L_Threshold          = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B4L_Threshold          = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B5L_Threshold          = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B6L_Threshold          = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 8 values TBS by LPSO */
B7L_Threshold          = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B8L_Threshold          = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 32 values TBS by LPSO */
B1H_Threshold          = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B2H_Threshold          = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B3H_Threshold          = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B4H_Threshold          = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B5H_Threshold          = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B6H_Threshold          = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 8 values TBS by LPSO */
B7H_Threshold          = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 16 values TBS by LPSO */
B8H_Threshold          = (NN.NNNNNNNN, NN.NNNNNNNN,...) /* 32 values TBS by LPSO */
GROUP = IN_THRESHOLD
END_GROUP = IMPULSE_NOISE

GROUP = COHERENT_NOISE
Frequency_Components   = 10
GROUP = CN_FREQUENCY_PARAMETERS
GROUP = FREQUENCY_MEANS
B1_Frequency_Mean       = (N.NNNNNNNN, N.NNNNNNNN,...,...) /* 10 values TBS by LPSO */
B2_Frequency_Mean       = (N.NNNNNNNN, N.NNNNNNNN,...,...) /* 10 values TBS by LPSO */
B3_Frequency_Mean       = (N.NNNNNNNN, N.NNNNNNNN,...,...) /* 10 values TBS by LPSO */
B4_Frequency_Mean       = (N.NNNNNNNN, N.NNNNNNNN,...,...) /* 10 values TBS by LPSO */
B5_Frequency_Mean       = (N.NNNNNNNN, N.NNNNNNNN,...,...) /* 10 values TBS by LPSO */
B6_Frequency_Mean       = (N.NNNNNNNN, N.NNNNNNNN,...,...) /* 10 values TBS by LPSO */
B7_Frequency_Mean       = (N.NNNNNNNN, N.NNNNNNNN,...,...) /* 10 values TBS by LPSO */
B8_Frequency_Mean       = (N.NNNNNNNN, N.NNNNNNNN,...,...) /* 10 values TBS by LPSO */
END_GROUP = FREQUENCY_MEANS
GROUP = FREQUENCY_SIGMAS
B1_Frequency_Sigma      = (N.NNNNNNNN, N.NNNNNNNN,...,...) /* 10 values TBS by LPSO */
B2_Frequency_Sigma      = (N.NNNNNNNN, N.NNNNNNNN,...,...) /* 10 values TBS by LPSO */
B3_Frequency_Sigma      = (N.NNNNNNNN, N.NNNNNNNN,...,...) /* 10 values TBS by LPSO */
B4_Frequency_Sigma      = (N.NNNNNNNN, N.NNNNNNNN,...,...) /* 10 values TBS by LPSO */
B5_Frequency_Sigma      = (N.NNNNNNNN, N.NNNNNNNN,...,...) /* 10 values TBS by LPSO */
B6_Frequency_Sigma      = (N.NNNNNNNN, N.NNNNNNNN,...,...) /* 10 values TBS by LPSO */
B7_Frequency_Sigma      = (N.NNNNNNNN, N.NNNNNNNN,...,...) /* 10 values TBS by LPSO */
B8_Frequency_Sigma      = (N.NNNNNNNN, N.NNNNNNNN,...,...) /* 10 values TBS by LPSO */

```



```

B7_Magnitude_Mean = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
B8_Magnitude_Mean = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
END_GROUP = MAGNITUDE_MEANS
GROUP = MAGNITUDE_SIGMAS
B1_Magnitude_Sigma = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
B2_Magnitude_Sigma = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
B3_Magnitude_Sigma = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
B4_Magnitude_Sigma = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
B5_Magnitude_Sigma = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
B6_Magnitude_Sigma = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
B7_Magnitude_Sigma = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
B8_Magnitude_Sigma = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
END_GROUP = MAGNITUDE_SIGMAS
GROUP = MAGNITUDE_MINIMUMS
B1_Magnitude_Min = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
B2_Magnitude_Min = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
B3_Magnitude_Min = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
B4_Magnitude_Min = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
B5_Magnitude_Min = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
B6_Magnitude_Min = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
B7_Magnitude_Min = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
B8_Magnitude_Min = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
END_GROUP = MAGNITUDE_MINIMUMS
GROUP = MAGNITUDE_MAXIMUMS
B1_Magnitude_Max = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
B2_Magnitude_Max = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
B3_Magnitude_Max = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
B4_Magnitude_Max = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
B5_Magnitude_Max = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
B6_Magnitude_Max = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
B7_Magnitude_Max = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
B8_Magnitude_Max = (N.NNNNNNNN, N.NNNNNNNN,.....) /* 10 values TBS by LPSO */
END_GROUP = MAGNITUDE_MAXIMUMS
GROUP = CN_MAGNITUDE_PARAMETERS
END_GROUP = COHERENT_NOISE

GROUP = DETECTOR_SATURATION
GROUP = AD_CONVERTER_SATURATION
GROUP = AD_CONVERTER_SATURATION_LOW
High_AD_Level_B1_low = (NNN, NNN,.....) /* 16 values TBS by SBRS */
High_AD_Level_B2_low = (NNN, NNN,.....) /* 16 values TBS by SBRS */
High_AD_Level_B3_low = (NNN, NNN,.....) /* 16 values TBS by SBRS */
High_AD_Level_B4_low = (NNN, NNN,.....) /* 16 values TBS by SBRS */
High_AD_Level_B5_low = (NNN, NNN,.....) /* 16 values TBS by SBRS */
High_AD_Level_B6_low = (NNN, NNN,.....) /* 8 values TBS by SBRS */
High_AD_Level_B7_low = (NNN, NNN,.....) /* 16 values TBS by SBRS */
High_AD_Level_B8_low = (NNN, NNN,.....) /* 32 values TBS by SBRS */
Low_AD_Level_B1_low = (NNN, NNN,.....) /* 16 values TBS by SBRS */
Low_AD_Level_B2_low = (NNN, NNN,.....) /* 16 values TBS by SBRS */
Low_AD_Level_B3_low = (NNN, NNN,.....) /* 16 values TBS by SBRS */
Low_AD_Level_B4_low = (NNN, NNN,.....) /* 16 values TBS by SBRS */
Low_AD_Level_B5_low = (NNN, NNN,.....) /* 16 values TBS by SBRS */
Low_AD_Level_B6_low = (NNN, NNN,.....) /* 8 values TBS by SBRS */
Low_AD_Level_B7_low = (NNN, NNN,.....) /* 16 values TBS by SBRS */
Low_AD_Level_B8_low = (NNN, NNN,.....) /* 32 values TBS by SBRS */
END_GROUP = AD_CONVERTER_SATURATION_LOW
GROUP = AD_CONVERTER_SATURATION_HIGH
High_AD_Level_B1_high = (NNN, NNN,.....) /* 16 values TBS by SBRS */
High_AD_Level_B2_high = (NNN, NNN,.....) /* 16 values TBS by SBRS */
High_AD_Level_B3_high = (NNN, NNN,.....) /* 16 values TBS by SBRS */
High_AD_Level_B4_high = (NNN, NNN,.....) /* 16 values TBS by SBRS */
High_AD_Level_B5_high = (NNN, NNN,.....) /* 16 values TBS by SBRS */
High_AD_Level_B6_high = (NNN, NNN,.....) /* 8 values TBS by SBRS */
High_AD_Level_B7_high = (NNN, NNN,.....) /* 16 values TBS by SBRS */
High_AD_Level_B8_high = (NNN, NNN,.....) /* 32 values TBS by SBRS */
Low_AD_Level_B1_high = (NNN, NNN,.....) /* 16 values TBS by SBRS */
Low_AD_Level_B2_high = (NNN, NNN,.....) /* 16 values TBS by SBRS */
Low_AD_Level_B3_high = (NNN, NNN,.....) /* 16 values TBS by SBRS */
Low_AD_Level_B4_high = (NNN, NNN,.....) /* 16 values TBS by SBRS */
Low_AD_Level_B5_high = (NNN, NNN,.....) /* 16 values TBS by SBRS */
Low_AD_Level_B6_high = (NNN, NNN,.....) /* 8 values TBS by SBRS */
Low_AD_Level_B7_high = (NNN, NNN,.....) /* 16 values TBS by SBRS */

```

```

Low_AD_Level_B8_high= (NNN, NNN,.....)      /* 32 values TBS by SBRS */
END_GROUP = AD_CONVERTER_SATURATION_HIGH
END_GROUP = AD_CONVERTER_SATURATION
GROUP = ANALOG_SIGNAL_SATURATION
GROUP = ANALOG_SIGNAL_SATURATION_LOW
    High_Analog_Level_B1_low = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    High_Analog_Level_B2_low = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    High_Analog_Level_B3_low = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    High_Analog_Level_B4_low = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    High_Analog_Level_B5_low = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    High_Analog_Level_B6_low = (NNN, NNN,.....)      /* 8 values TBS by SBRS */
    High_Analog_Level_B7_low = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    High_Analog_Level_B8_low = (NNN, NNN,.....)      /* 32 values TBS by SBRS */
    Low_Analog_Level_B1_low = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    Low_Analog_Level_B2_low = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    Low_Analog_Level_B3_low = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    Low_Analog_Level_B4_low = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    Low_Analog_Level_B5_low = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    Low_Analog_Level_B6_low = (NNN, NNN,.....)      /* 8 values TBS by SBRS */
    Low_Analog_Level_B7_low = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    Low_Analog_Level_B8_low = (NNN, NNN,.....)      /* 32 values TBS by SBRS */
END_GROUP = ANALOG_SIGNAL_SATURATION_LOW
GROUP = ANALOG_SIGNAL_SATURATION_HIGH
    High_Analog_Level_B1_high = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    High_Analog_Level_B2_high = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    High_Analog_Level_B3_high = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    High_Analog_Level_B4_high = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    High_Analog_Level_B5_high = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    High_Analog_Level_B6_high = (NNN, NNN,.....)      /* 8 values TBS by SBRS */
    High_Analog_Level_B7_high = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    High_Analog_Level_B8_high = (NNN, NNN,.....)      /* 32 values TBS by SBRS */
    Low_Analog_Level_B1_high = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    Low_Analog_Level_B2_high = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    Low_Analog_Level_B3_high = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    Low_Analog_Level_B4_high = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    Low_Analog_Level_B5_high = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    Low_Analog_Level_B6_high = (NNN, NNN,.....)      /* 8 values TBS by SBRS */
    Low_Analog_Level_B7_high = (NNN, NNN,.....)      /* 16 values TBS by SBRS */
    Low_Analog_Level_B8_high = (NNN, NNN,.....)      /* 32 values TBS by SBRS */
END_GROUP = ANALOG_SIGNAL_SATURATION_HIGH
END_GROUP = ANALOG_SIGNAL_SATURATION
END_GROUP = DETECTOR_SATURATION

GROUP = REFERENCE_TEMPERATURES
GROUP = REFERENCE_LOW
    B1L_RTemp_Prelaunch = NNN.NNN      /* TBS by SBRS */
    B1L_RTemp_Postlaunch = NNN.NNN      /* TBS by SBRS */
    B1L_RTemp_Current = NNN.NNN      /* TBS by SBRS */
    B2L_RTemp_Prelaunch = NNN.NNN      /* TBS by SBRS */
    B2L_RTemp_Postlaunch = NNN.NNN      /* TBS by SBRS */
    B2L_RTemp_Current = NNN.NNN      /* TBS by SBRS */
    B3L_RTemp_Prelaunch = NNN.NNN      /* TBS by SBRS */
    B3L_RTemp_Postlaunch = NNN.NNN      /* TBS by SBRS */
    B3L_RTemp_Current = NNN.NNN      /* TBS by SBRS */
    B4L_RTemp_Prelaunch = NNN.NNN      /* TBS by SBRS */
    B4L_RTemp_Postlaunch = NNN.NNN      /* TBS by SBRS */
    B4L_RTemp_Current = NNN.NNN      /* TBS by SBRS */
    B5L_RTemp_Prelaunch = NNN.NNN      /* TBS by SBRS */
    B5L_RTemp_Postlaunch = NNN.NNN      /* TBS by SBRS */
    B5L_RTemp_Current = NNN.NNN      /* TBS by SBRS */
    B6L_RTemp_Prelaunch = NNN.NNN      /* TBS by SBRS */
    B6L_RTemp_Postlaunch = NNN.NNN      /* TBS by SBRS */
    B6L_RTemp_Current = NNN.NNN      /* TBS by SBRS */
    B7L_RTemp_Prelaunch = NNN.NNN      /* TBS by SBRS */
    B7L_RTemp_Postlaunch = NNN.NNN      /* TBS by SBRS */
    B7L_RTemp_Current = NNN.NNN      /* TBS by SBRS */
    B8L_RTemp_Prelaunch = NNN.NNN      /* TBS by SBRS */
    B8L_RTemp_Postlaunch = NNN.NNN      /* TBS by SBRS */
    B8L_RTemp_Current = NNN.NNN      /* TBS by SBRS */
END_GROUP = REFERENCE_LOW
GROUP = REFERENCE_HIGH
    B1H_RTemp_Prelaunch = NNN.NNN      /* TBS by SBRS */

```


END_GROUP = REFLECT_IC_COEFFS_HIGH
END_GROUP = REFLECT_IC_COEFFS

GROUP = FASC_PARAMETERS
FASC_Reference_Detectors = (NN, NN,.....) /* 8 values TBS by LPSO */

```

END_GROUP = FASC_PARAMETERS

GROUP = B6_IC_COEFFS
  GROUP = B6_IC_COEFFS_LOW
    B6L_Coefficients_Detector1
    B6L_Coefficients_Detector2
    B6L_Coefficients_Detector3
    B6L_Coefficients_Detector4
    B6L_Coefficients_Detector5
    B6L_Coefficients_Detector6
    B6L_Coefficients_Detector7
    B6L_Coefficients_Detector8
  END_GROUP = B6_IC_COEFFS_LOW
  GROUP = B6_IC_COEFFS_HIGH
    B6H_Coefficients_Detector1
    B6H_Coefficients_Detector2
    B6H_Coefficients_Detector3
    B6H_Coefficients_Detector4
    B6H_Coefficients_Detector5
    B6H_Coefficients_Detector6
    B6H_Coefficients_Detector7
    B6H_Coefficients_Detector8
  END_GROUP = B6_IC_COEFFS_HIGH
END_GROUP = B6_IC_COEFFS

```

```

GROUP = B6_VIEW_COEFFS
  B6_View_Coefficients_Detector1
  B6_View_Coefficients_Detector2
  B6_View_Coefficients_Detector3
  B6_View_Coefficients_Detector4
  B6_View_Coefficients_Detector5
  B6_View_Coefficients_Detector6
  B6_View_Coefficients_Detector7
  B6_View_Coefficients_Detector8
END_GROUP = B6_VIEW_COEFFS

```

```

GROUP = THERMISTOR_COEFFS
  Black_Body_Isolated_Temp
  Black_Body_Control_Temp
  Cold_FP_Control_Temp
  Cold_FP_Monitor_Temp
  Cal_Shutter_Flag_Temp
  Backup_Shutter_Flag_Temp
  Baffle_Heater_Temp
  Silicon_FP_Array_Temp
  Primary_Mirror_Temp
  Secondary_Mirror_Temp
  Scan_Line_Corrector_Temp
  Baffle3_Tube_Temp
  Baffle2_Support_Temp
  Cal_Lamp_Housing_Temp
  Cal_Shutter_Hub_Temp
  Ambient_Preamp_HighCh_Temp
  Ambient_Preamp_LowCh_Temp= (NNN.NNNNNNNN, NNN.NNNNNNN,...) /* 65 values TBS by LPSO */
  Postamp_Temp_B4
  Cold_Preamp_B7_Temp
  Pan_Band_Postamp_Temp
  Telescope_Housing_Temp = (NNN.NNNNNNNN, NNN.NNNNNNN,...) /* 65 values TBS by LPSO */
  Primary_Mirror_Mask_Temp = (NNN.NNNNNNNN, NNN.NNNNNNN,...) /* 6 values TBS by LPSO */
  Secondary_Mirror_Mask_Temp = (NNN.NNNNNNNN, NNN.NNNNNNN,...) /* 6 values TBS by LPSO */
  Telescope_Baseplate = (NNN.NNNNNNNN, NNN.NNNNNNN,...) /* 6 values TBS by LPSO */
  MUX1_Power_Supply_Temp = (NNN.NNNNNNNN, NNN.NNNNNNN,...) /* 6 values TBS by LPSO */
  MUX1_Electronics_Temp = (NNN.NNNNNNNN, NNN.NNNNNNN,...) /* 6 values TBS by LPSO */

```

MUX2_Power_Supply_Temp	= (NNN.NNNNNNNN, NNN.NNNNNNNN,...)	/* 6 values TBS by LPSO */
MUX2_Electronics_Temp	= (NNN.NNNNNNNN, NNN.NNNNNNNN,...)	/* 6 values TBS by LPSO */
MEM_Heat_Sink_PSL_Temp	= (NNN.NNNNNNNN, NNN.NNNNNNNN,...)	/* 6 values TBS by LPSO */
MEM_Heat_Sink_PS2_Temp	= (NNN.NNNNNNNN, NNN.NNNNNNNN,...)	/* 6 values TBS by LPSO */

END_GROUP = THERMISTOR_COEFFS

GROUP = FILL_PATTERNS
 Band_Fill_Pattern = (0, 255)
 END_GROUP_FILL_PATTERNS

GROUP = ENGINEERING_DATA
 Telemetry_Conversion = (NNNN.NNNNNNNN, NNNN.NNNNNNNN,...) /* 6 values TBS by SBRS */
 Position_Conversion = 2.0E-08
 Velocity_Conversion = 2.0E-28
 END_GROUP = ENGINEERING_DATA

END

Acronyms and Abbreviations

0R	Level 0 reformatted (data)
ACCA	automated cloud cover assessment
ADS	angular displacement sensor data
ADSA	attitude displacement sensor assembly
ASCII	American Standard Code for Information Interchange
CPF	calibration parameter file
CCSDS	Consultative Committee for Space Data Systems
DAAC	Distributed Active Archive Center
DN	digital number
ECS	EOSDIS Core System
EDC	EROS Data Center
EOL	end of line
EOS	Earth Observing System
EOSDIS	EOS Data and Information System
EROS	Earth Resources Observation Systems
ETM+	Enhanced Thematic Mapper Plus
EU	engineering unit
FASC	full aperture solar calibrator
HDF	Hierarchical Data Format
I/O	input/output
IAS	Image Assessment System
IC	internal calibrator
IEEE	Institute of Electrical and Electronics Engineers
IFOV	instrument field of view
IMU	inertial measurement unit
ISO	International Organization for Standardization

JPL	Jet Propulsion Laboratory
kHz	kilohertz
km	kilometer
L1R	Level 1 radiometrically corrected (data)
LMC	Lockheed Martin Corporation
LPS	Landsat Processing System
LPSO	Landsat Project Science Office
Mbps	megabit per second
MTFC	modulation transfer function compensation
NEOS	National Earth Orientation Service
NSDI	normalized snow difference index
ODL	Object Description Language
PCD	payload correction data
PVL	Parameter Value Language
SAM	scan angle monitor
SBRS	Santa Barbara Remote Sensing
SME	scan mirror electronics
TBR	to be resolved
TBS	to be submitted
URL	Uniform Resource Locator
UTC	Universal Time Code
UT1	UTC corrected
WRS	Worldwide Reference System